

### Standard Reference Materials:

# HALF LIVES OF MATERIALS USED IN THE PREPARATION OF STANDARD REFERENCE MATERIALS OF NINETEEN RADIOACTIVE NUCLIDES ISSUED BY THE NATIONAL BUREAU OF STANDARDS



U.S. Department of Commerce
National Bureau of Standards

#### THE NATIONAL BUREAU OF STANDARDS

The National Bureau of Standards is a principal focal point in the Federal Government for assuring maximum application of the physical and engineering sciences to the advancement of technology in industry and commerce. Its responsibilities include development and maintenance of the national standards of measurement, and the provisions of means for making measurements consistent with those standards; determination of physical constants and properties of materials; development of methods for testing materials, mechanisms, and structures, and making such tests as may be necessary, particularly for government agencies; cooperation in the establishment of standard practices for incorporation in codes and specifications; advisory service to government agencies on scientific and technical problems; invention and development of devices to serve special needs of the Government; assistance to industry, business, and consumers in the development and acceptance of commercial standards and simplified trade practice recommendations; administration of programs in cooperation with United States business groups and standards organizations for the development of international standards of practice; and maintenance of a clearinghouse for the collection and dissemination of scientific, technical, and engineering information. The scope of the Bureau's activities is suggested in the following listing of its four Institutes and their organizational units.

Institute for Basic Standards. Applied Mathematics. Electricity. Metrology. Mechanics. Heat. Atomic Physics. Physical Chemistry. Laboratory Astrophysics.\* Radiation Physics. Radio Standards Laboratory:\* Radio Standards Physics; Radio Standards Engineering. Office of Standard Reference Data

Institute for Materials Research. Analytical Chemistry. Polymers. Metallurgy. Inorganic Materials. Reactor Radiations. Cryogenics.\* Materials Evaluation Laboratory. Office of Standard Reference Materials.

Institute for Applied Technology. Building Research. Information Technology. Performance Test Development. Electronic Instrumentation. Textile and Apparel Technology Center. Technical Analysis. Office of Weights and Measures. Office of Engineering Standards. Office of Invention and Innovation. Office of Technical Resources. Clearinghouse for Federal Scientific and Technical Information.\*\*

Central Radio Propagation Laboratory.\* Ionospheric Telecommunications. Tropospheric Telecommunications. Space Environment Forecasting. Aeronomy.

<sup>\*</sup> Located at Boulder, Colorado 80301.

<sup>\*\*</sup> Located at 5285 Port Royal Road, Springfield, Virginia 22171.

### Standard Reference Materials:

# Half Lives of Materials Used in the Preparation of Standard Reference Materials of Nineteen Radioactive Nuclides Issued by the National Bureau of Standards

S. C. Anspach, L. M. Cavallo, S. B. Garfinkel, J. M. R. Hutchinson, and C. N. Smith

Institute for Basic Standards
National Bureau of Standards
Washington, D.C.



National Bureau of Standards Miscellaneous Publication 260-9

Issued November 15, 1965

#### PREFACE

Within the frame work of the National Bureau of Standards Institutes the area of standard reference materials is a broad and important one, including the preparation, characterization and distribution of a wide variety of materials in such diverse fields as metallurgy, polymers and inorganic materials. In carrying out such a program there is much interaction with representatives of industry and science, beginning with discussions as to which primary standard materials will do most to advance technology, the furnishing of materials and fabrication of samples, and the characterization and certification of the materials by cooperative efforts. The many groups participating in a standards program are very interested in detailed information on specific aspects of the program —but to date there has been no publication outlet for such written discussions.

To meet this need, NBS Miscellaneous Publication 260 has been reserved for a series of papers in the general area of "standard reference materials". This subject-oriented series will provide a means for rapid dissemination of this detailed information and we hope will stimulate the use of standard reference materials in science and industry.

W. Wayne Meinke, Chief Office of Standard Reference Materials

Library of Congress Catalog Card Number: 65-62744

#### OTHER NBS PUBLICATIONS IN THIS SERIES

- NBS Misc Publ. 260, Standard Reference Materials: Catalog and Price List of Standard Materials Issued by the National Bureau of Standards, January 1965 In press.\* (Supersedes NBS Misc. Publ. 241, March 1962.)
- NBS Misc. Publ. 260-1, Standard Reference Materials: Preparation of NBS White Cast Iron Spectrochemical Standards, June 1964. 30 cents.\*
- NBS Misc. Publ. 260-2, Standard Reference Materials: Preparation of NBS Copper-Base Spectrochemical Standards, October 1964. 35 cents.\*
- NBS Misc. Publ 260-3, Standard Reference Materials: Metallographic Characterization of an NBS Spectrometric Low-Alloy Steel Standard, October 1964. 20 cents.\*
- NBS Misc. Publ 260-4, Standard Reference Materials: Sources of Information on Standard Reference Materials, February 1965. 20 cents.\*
- NBS Misc. Publ. 260-5, Standard Reference Materials: Accuracy of Solution X-Ray Spectrometric Analysis of Copper-Base Alloys, March 1965. 25 cents.\*
- NBS Misc. Publ. 260-6, Standard Reference Materials: Methods for the Chemical Analysis of White Cast Iron Standards, July 1965. 45 cents.\*
- NBS Misc. Publ. 260-7, Standard Reference Materials: Methods for the Chemical Analysis of NBS Copper-Base Spectrochemical Standards. In press.\*
- NBS Misc. Publ. 260-8, Standard Reference Materials: Analysis of Uranium Concentrates at the National Bureau of Standards. In press.\*

<sup>\*</sup> Send orders with remittance to: Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402. Remittance from foreign countries should include an additional one-fourth of the purchase price for postage.

## STANDARD REFERENCE MATERIALS: HALF LIVES OF MATERIALS USED IN THE PREPARATION OF STANDARD REFERENCE MATERIALS OF NINETEEN RADIOACTIVE NUCLIDES ISSUED BY THE NATIONAL BUREAU OF STANDARDS

S. C. Anspach, L. M. Cavallo, S. B. Garfinkel, J. M. R. Hutchinson, and C. N. Smith

Institute for Basic Standards National Bureau of Standards

#### ABSTRACT

Values are given for the half lives of materials used in the preparation of standard samples of Na $^{22}$ , Ca $^{45}$ , Sc $^{46}$ , Mn $^{54}$ , Co $^{57}$ , Co $^{60}$ , Zn $^{65}$ , Kr $^{85}$ , Sr $^{85}$ , Sr $^{89}$ , Sr $^{90}$ , Y $^{88}$ , Nb $^{95}$ , I $^{125}$ , Ce $^{139}$ , Ce $^{141}$ , Pm $^{147}$ , Hg $^{203}$ , Tl $^{204}$ , issued by the National Bureau of Standards. Instrumentation, source preparation, and the determination of impurities are also discussed.

Key Words: Half lives, calcium-45, cerium-139, cerium-141, cobalt-57, cobalt-60, iodine-125, krypton-85, manganese-54, mercury-203, niobium-95, promethium-147, scandium-46, sodium-22, strontium-85, strontium-89, strontium-90, thallium-204, yttrium-88 and zinc-65.

For many years, members of the Radioactivity Section of the National Bureau of Standards have followed the half lives of sources prepared from the same materials used in the preparation of standard samples of radionuclides for distribution. The results of this program have not previously been published, and in view of the widespread distribution of these standards, and the large spread in the reported values of the half lives of many of the radionuclides involved, these results are being presented so that appropriate decay corrections may be applied by users of these standards.

In most cases the purified radioactive material was obtained from commercial sources or Oak Ridge National Laboratory. In some cases, further purification was made in this laboratory, or the material was examined spectrometrically for impurities. When information on the radioactive purity is available, it is given. However, the extent to which the logarithmic plot of the measured activity, over an extended period of time, approximates a straight line is taken as an indication of the radioactive purity.

The instruments used in these determinations were the National Bureau of Standards 4πγ ionization chamber, the National Bureau of Standards 2πβ ionization chamber, and the National Bureau of Standards 4πβ flow proportional counter, all described in NBS Circular No. 594. The determinations consist of individual observations made at convenient time intervals. The half lives and their standard errors were calculated from the straight line fitted to the data by the method of least squares. In some determinations, measurements were made on several

sources from the same material. The value of the half life and the standard error associated with it were computed for each source separately. Each value was then weighted with its error and the weighted average reported. The error reported was computed using the formula:

$$\frac{1}{\sigma} = \sqrt{\left\{\frac{1}{\sigma_1}\right\}^2 + \left\{\frac{1}{\sigma_2}\right\}^2 + \cdots + \left\{\frac{1}{\sigma_n}\right\}^2}$$

With the exception of krypton-85, sources for the 4my ionization chamber were 5 milliliters of radioactive solution, flame-sealed in glass ampoules. The krypton-85 source was approximately 30 mc of gas in a break-seal glass ampoule. Each source was compared with a radium-226 reference source, the ratio of the activity of the source under investigation to that of the radium-226 source constituting one observation. Corrections (if significant) were made for the decay of radium-226, using a half-life value of 1622 years. The temperature and pressure were carefully monitored during each measurement and appropriate corrections made for changes in air density.

Sources for the  $2\pi\beta$  ionization chamber were made by imbedding the radioactive material in epoxy resins mounted in aluminum holders. These were compared with either a radium-226 or a cesium-137 reference source. A half life of 29.5 years was assumed for the Cs<sup>137</sup> reference source.

Sources for the  $4\pi\beta$  proportional counter were prepared by depositing aliquots of radioactive solutions on thin plastic films (~  $4\mu g/cm^2$  to 25  $\mu g/cm^2$  thick) which had either electrically conducting coatings of gold (~  $20~\mu g/cm^2$ ) evaporated on them, or aluminum leaf backings (~  $220~\mu g/cm^2$ ). The aliquots of solution were dried and then covered with films identical to the supporting ones to produce a symmetrical sandwich. The sources were counted in the  $4\pi\beta$  proportional counter, the counts per second at a given time constituting one observation. The  $4\pi$  geometry and the stability of the instrument made measurement of a reference source unnecessary. The dead time of the counting system was checked periodically and small corrections were made.

The material used in the determination of the half lives of Sc 46, Mm 54, Co 57, Sr 85, Y 88, Ce 139, Hg 203, and the Zn 65 issued after 1959, were examined in this laboratory for gamma-ray impurities with a NaI(T1) scintillation spectrometer at the time of the initial measurement. Approximately 10 counts in the full-energy peak (or peaks) characteristic of the radionuclide under investigation were collected. No other peaks greater than 0.1% of this value, were observed.

In the case of the Mn<sup>54</sup> (4997 series), an iron-55 contaminant was removed chemically prior to the standardization. It was estimated that there was less than 0.1% iron-55 remaining.

The  ${\rm Sr}^{89}$  material was examined with both a NaI(T1) scintillation spectrometer and a beta-ray anthracene scintillation spectrometer at the time of the initial and final half-life measurements. The  ${\rm Sr}^{85}$ 

disintegration rate was found to be 0.096% of the  $\mathrm{Sr}^{89}$  initially, with about 30% of this being detected in the  $4\pi\beta$  counter as compared with 99% of the  $\mathrm{Sr}^{89}$ . The  $\mathrm{Sr}^{90}$ -Y<sup>90</sup> disintegration rate was found to be less than 0.02% of the  $\mathrm{Sr}^{89}$  initially, the  $\mathrm{Sr}^{90}$ -Y<sup>90</sup> having the same efficiency as the  $\mathrm{Sr}^{89}$ . The contribution of these contaminants was considered to be insignificant and no corrections were made for them.

A cesium-137-barium-137m impurity in the I<sup>125</sup> (4944 series) was detected spectrometrically and found to have a disintegration rate approximately 0.015% that of the I<sup>125</sup> on the date of issue. The source used for the half-life measurement was, therefore, remeasured 428 days after the final half-life measurement. The activity due to iodine-125 still present was calculated, using a 60-day half life, and subtracted from the measured activity. The remaining activity was assumed to be due to the cesium-137-barium-137m impurity and was subtracted from the half-life data used to determine the value given in Table 1 for iodine-125.

Similarly, the contribution of a cerium-144-praseodymium-144 contaminant, which was observed spectrometrically in the Ce<sup>141</sup>(4946 series), was determined from a measurement of the half-life source 260 days after the final half-life observation, and was subtracted from the data used to determine the value shown in Table 1 for cerium-141. The disintegration rate of the cerium-144-praseodymium-144 contaminant was computed to be approximately 0.64% of that from the Ce<sup>141</sup> on the date of issue of the 4946 series.

A list of references to some of the more recently published values for the half lives of the radionuclides appearing in Table 1, is given here.

Table 1

Nuclide	Half Life	Standard Error	No. of Obser- vations	Number of Half Lives Measured	Standard Sample Number I	Date Issued	Instru- ment Used*	No. of Sources per Batch
Na <sup>22</sup> Ca <sup>45</sup> Sc <sup>46</sup> Mn <sup>54</sup>	2.591y	0.003y	56	2.6	4921	10-14-54	4πγ	2
	2.613y	0.01ly	13	•5	4922 <b>-</b> B	4-29-59	tt	1
	2.603y	0.00ly	29	1.2	{4921 <b>-</b> B 4922 <b>-</b> C	12 <b>-</b> 11 <b>-</b> 61	tī	1
	2.602y	0.01ly	11	•5	4922 <b>-</b> D	6-30-64	, <b>m</b>	1
	162.63d	0.11d	46	5.8	4942	2-1-62	4πβ	14
	83.80d	0.03d	24	2.8	4939	7-20-60	417	1
	311.9d	0.2d	26	1.3	4997 ∫4997 <b>-</b> B	9-1-60 7-24-61	4πy	1 1
	311.9d	0.2d	16	1.5	4997-C	3 <b>-1-</b> 62		
	312.6d	0.4d	14	1.6	4997 <b>-</b> D	10-22-63	11	1
co <sup>57</sup>	271.65d	0.13d	27	2.1	4941	12-19-61	4 <b>17</b>	1
co <sup>60</sup>	5.242y	0.008y	3 <sup>1</sup> 4	1	{4914} {4915	7-24-47	4 <b>17</b>	1
					4914-A 4915-A	10-1-53		
Zn <sup>65</sup>	243.ld	0.7d	1414	3.1	4930	3-1-57	4πγ	3
	244.120	0.12d	<b>5</b> 0	2.1	49 <b>30-</b> в	3-11-60	11	2
	242.78d	0.19d	18	2.1	{4930 <b>-</b> C 1 <sub>4930-D</sub>	8 <b>-</b> 2-61 1-7-62	11 11	1
Kr <sup>85</sup>	10.75у	0.03y	24	•59	{4935 4935 <b>-</b> A	12-10-57	4пу	1
$\mathrm{sr}^{85}$	65.19a	0.13d	6	1.4	4938	8-24-59	4πγ	1
Y <sup>88</sup>	106.520	0.03d	19	2.6	4998	9-10-61	<sup>1</sup> 4 πγ	1
	106.67d	0.03d	18	2.7	4998 <b>-</b> C	3-12-65	11	1
				6				

Table 1 Continued

					<del> </del>			
Nuclide	Half Life	Standard Error	No. of Obser- vations	Number of Half Lives Measured	Standard Sample Number	Date Issued	Instru- ment Used	No. of Sources per Batch
sr <sup>89</sup>	50.70d	0.19d	8	1.8	∫ 494 <b>5</b>	12-5-63	2 <b>π</b> β <sup>i</sup>	1
	50.52d	0.03d	62	5.1	<sup>1</sup> 4945 <sub>7</sub> B_	9-1-64	4πβ	14 .
sr <sup>90</sup>	28.82y	0.14y	69	•39	{ 4919	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	4πβ	6
7.05					4919 <b>-</b> B	14-6-57		
1 <sup>125</sup>	59.83d	0.lld	20	3.3	4944	12-19-62	2πβ <sup>ii</sup>	1
Ce <sup>139</sup>	137.5d	0.3d	9	1.2	4999	1-1-63	4πγ	1
Ce <sup>141</sup>	32.55d	0.007d	30	5.2	4946	1-3-64	4πγ	1
Pm <sup>14</sup> 7	2.618y	0.007у	33	1.3	{4940 4940 <b>-</b> B	5-1-61	4πβ	2
Hg <sup>203</sup>	46.56a	0.02d	9	4.8	4932	3-12-59	4117	1
_	46.577d	. 0.008a	18	5.1	4932-C	5-28-64	417	1
Tl <sup>204</sup>	3.754y	0.004y	53	1.9	4920 <b>-</b> B	6-7-57	4πβ	2

<sup>\* 4</sup>my - 4my ionization chamber

<sup>4</sup>πβ - 4πβ proportional counter

 $<sup>2\</sup>pi\beta$  -  $2\pi\beta$  ionization chamber

 $<sup>^{1}</sup>$ The Sr $^{89}$  source was compared with a Cs $^{137}$  reference source as a Ra $^{226}$  reference of comparable intensity was not available.

ii\_The  $I^{125}$  source was compared with a  $Ra^{226}$  reference source.

#### References \*

Na.22  $(2.6 \pm ?)y$ L. J. Laslett, Phys. Rev. 76, 858 (1949) (2.58±0.03)y W. F. Merritt, P. J. Campion, R. C. Hawkings, Can. J. Phys. 35, 16 (1957) (2.62±0.02)y E. I. Wyatt, S. A. Reynolds, T. H. Handley, W. S. Lyon, H. A. Parker, Nuclear Sci. and Eng. 11, 74 (1961) Ca<sup>45</sup> (164±4)a C.F.G. Delaney, J.H.J. Poole, Phys. Rev. 89, 529 (1953)(166 ± ? )d V. I. Breslav, Trudy Inst. Fiz., Akad. Nauk. Latv. SSR Ser. Fiz. i Tekh. Primenen. Radioaktiv. Izotopov 9, 33 (1956) Chem. Abstr. 51, No. 17490d (1957) (153±2)d H. Thiry, Bull. soc. roy. sci. Liege 26, 29 (1957) (167±3)a J. P. Cali, L. F. Lowe, Nucleonics 17, No. 10, 86 (1959) (165.1±0.7)a E. I. Wyatt, et al, Nuclear Sci. and Eng. 11, 74 (1961)Sc46  $(82.9\pm1.6)a$ G. Rudstam, Thesis, Univ. of Uppsala (1956) (84.1±0.3)d R. P. Schuman, M. E. Jones, A. C. Mewherter, J. Inorg. Nuclear Chem. 3, 160 (1956) (83.89±0.12)d K. W. Geiger, Phys. Rev. 105, 1539 (1957) (84.2±0.2)d H. W. Wright, E. I. Wyatt, S. A. Reynolds, W. S. Lyon, T. H. Handley, Nuclear Sci. and Eng. 2,

427 (1957)

Mm<sup>54</sup> (291±1)d E. W. Backofen, R. H. Herber, Phys. Rev. 97, 743 (1955)

(278±5)d R. P. Schuman, M. E. Jones, A. C. Mewherter,

703 (1956)

- J. Inorg. Nuclear Chem. 3, 160 (1956)

  (290±6)d P. Kafalas, J. W. Irvine, Jr., Phys. Rev. 104,
- (313.5±0.7)d E. I. Wyatt, et al, Nuclear Sci. and Eng. 11, 74 (1961)
- $co^{57}$  (270 ± ?)d J. J. Livingood, G. T. Seaborg, Phys. Rev. 60, 913 (1941)
  - (267 ± ? )d J. M. Cork, M. K. Brice, L. C. Schmid, Phys. Rev. 99, 703 (1955)
- Co<sup>60</sup> (5.24±0.03)y K. W. Geiger, Phys. Rev. 105, 1539 (1957) (5.33±0.04)y J. P. Keene, L. A. Mackenzie, C. W. Gilbert, Phys. in Med. Biol. 2, 360 (1958)
  - (5.263±0.003)y S. G. Gorbics, W. E. Kunz, A. E. Nash, Nucleonics 21, No. 1, 63 (1962)
- Zn<sup>65</sup> (245.0±0.8)d J. Tobailem, J. phys. radium 14, 553
  - (243.5±0.8)d K. W. Geiger, Phys. Rev. 105, 1539 (1957)
  - (246.4±2.2)d H. W. Wright, E. I. Wyatt, S. A. Reynolds,
    W. S. Lyon, T. H. Handley, Nuclear Sci. and
    Eng. 2, 427 (1957)
- Kr<sup>85</sup> (10.57±0.14)y J. F. Turner, AERE N/R 1254 (1953) (10.27±0.18)y R. K. Wanless, H. G. Thode, Can. J. Phys. 31, 517 (1953)

```
Kr^{85}
         (10.76±0.02)y J. Lerner, U.S.A.E.C. TID-16627 (1962)
(Continued)
Sr<sup>85</sup>
         (65\pm3)a
                         M. Ter-Pogossian, F. T. Porter, Phys. Rev. 81,
                         1057 (1951)
         (65.0±0.7)d
                         G. Herrmann, F. Strassmann, Z. Naturforsch lla,
                         946 (1956)
         (64.0±0.2)d
                         H. W. Wright, E. I. Wyatt, S. A. Reynolds,
                         W. S. Lyon, T. H. Handley, Nuclear Sci. and
                         Eng. 2, 427 (1957)
<sub>v</sub>88
         (105 \pm 5)a
                         L. A. DuBridge, J. Marshall, Phys. Rev. 58,
                         7 (1940)
         (104±2)a
                         R. T. Overman, AECD-354 (1946)
         (105\pm1)a
                         O. U. Anders, Thesis, Univ. of Mich. (1957)
                         E. I. Watt, et al, Nuclear Sci. and Eng. 11,
         (108.1±0.3)a
                         74 (1961)
sr<sup>89</sup>
         (50.36±0.18)d R. G. Osmond, M. J. Owers, J. Inorg. Nuclear
                         Chem. 9, 96 (1959)
         (53.6±0.4)d
                         A. R. Sattler, Nuclear Phys. 36, 648 (1962)
sr^{90}
                         M. P. Anikina, R. N. Ivanov, G. M. Kukavadze,
         (29.3±1.6)y
                         B. V. Ershler, Atomnaya Energ. 4, 198 (1958);
                         J. Nuclear Energy 9, 167 (1959)
мь<sup>95</sup>
         (35±1)d
                         D. W. Engelkemeir, E. L. Brady, E. P.
                         Steinberg, NNES 9, 722 (1950)
         (35.0\pm0.5)d
                         J. M. Cork, J. M. LeBlanc, D. W. Martin, W. H.
                         Nester, M. K. Brice, Phys. Rev. 90, 579 (1953)
         (35.0±0.1)d
                         E. I. Watt, et al, Nuclear Sci. and Eng. 11, 74
                         (1961)
```

- 1<sup>125</sup> (60.0±0.5)d G. Friedlander, W. C. Orr, Phys. Rev. 84, 484 (1951)
  - (58.8±0.2)d G. I. Gleason, Abbott Lab., Oak Ridge, Tenn., private communication, 5-20-63
- Ce<sup>139</sup> (140±1)d M. L. Pool, N. L. Krisberg, Phys. Rev. 73, 1035 (1948)
- Ce<sup>141</sup> (33.1±0.2)d D. Walker, Proc. Phys. Soc. (London) A62, 799 (1949)
  - (32.5±0.2)d M. S. Freedman, D. W. Engelkemeir, Phys. Rev. 79, 897 (1950)
  - (32.51±0.02)d B. H. Kettelle, A. R. Brosi, Nuclear Data Sheets
    October, 1957
- Pm<sup>147</sup> (2.66±0.02)y R. P. Schuman, M. E. Jones, A. C. Mewherter, J. Inorg. Nuclear Chem. 3, 160 (1956)
  - (2.6/1±0.02)y W. F. Merritt, P. J. Campion, R. C. Hawkings, Can. J. Phys. 35, 16 (1957)
  - (2.7±0.1)y J. P. Cali, L. F. Lowe, Nucleonics 17, No. 10, 86 (1959)
  - (2.50±0.03)y E. I. Watt, et al, Nuclear Sci. and Eng. 11, 74
    (1961)
  - (2.67±0.06)y F. P. Roberts, E. J. Wheelwright, W. Y. Matsumoto, H. W.-77296 (1963)
- Hg<sup>203</sup> (47.9±0.2)d J. M. Cork, D. W. Martin, J. M. LeBlanc, C. E. Branyan, Phys. Rev. 85, 386 (1952)

- (46.91±0.14)d G. G. Eichholz, J. V. Krzyzewski, Can. J. Phys. 34, 1167 (1956)
- (47.1±0.2)d H. Thiry, Bull. Soc. Roy. Sci. Liege 26, 29 (1957)
- (47.2±0.7)d J. P. Cali, L. F. Lowe, Nucleonics 17, No. 10, 86 (1959)
- T1<sup>204</sup> (3.56±0.05)y W. F. Merritt, P. J. Campion, R. C. Hawkings, Can. J. Phys. 35, 16 (1957)
  - (4.11±0.13)y J. E. Edwards, J. Inorg. Nuclear Chem. 7, 336 (1958)
  - (3.57±0.04)y E. I. Wyatt, et al, Nuclear Sci. and Eng. 11, 74 (1961)
  - (3.80±0.02)y G. Harbottle, Nuclear Physics 41, 604 (1963)

\*For interpretations of the errors shown, refer to original publications.