

NIST Calibration Program
Calibration Services Users Guide
SP 250 Appendix
Fee Schedule 2012

Calibration Services:

Dimensional
Mechanical
Thermodynamic
Optical Radiation
Ionizing Radiation
Electromagnetic
Time and Frequency



National Institute of
Standards and Technology
U.S. Department of Commerce

Table of Contents

CHAPTER 1	1
POLICIES	1
A. Introduction	1
B. Types of Calibration Services	1
C. Other NIST Measurement Transfer Services	1
E. Fees	3
F. Reports of Calibration/Test Results	3
G. Traceability	3
H. NIST Policy on Reporting Measurement Uncertainty	4
I. NIST Policy Regarding Use of Metric (SI) Units	5
J. Reference to NIST in Advertisements	5
K. Disclaimer	5
L. Questions and Inquires	5
M. Contracts and Signed Statements	6
 CHAPTER 2	 7
ORDERING INSTRUCTIONS FOR DOMESTIC CUSTOMERS	7
A. Customer Inquires	7
B. Prearrangements and Scheduling	7
C. Purchase Orders	7
D. Remit to	8
E. Shipping, Insurance, and Risk of Loss	8
F. Turnaround Time	9
G. Customer Checklist	9
 CHAPTER 3	 11
SPECIAL INSTRUCTIONS FOR FOREIGN CUSTOMERS	11
A. Foreign Inquires	11
B. Criteria for Providing Service	11
C. Special Instructions	11
D. Shipping Charges	13
 CHAPTER 4	 14
DIMENSIONAL MEASUREMENTS	14
A. Length Measurements	14
B. Diameter and Roundness Measurements	16
C. Complex Dimensional Standards	17
E. Optical Reference Planes and Roundness Standards	19
F. Angular Measurements	20
G. Laser Measurements	20
H. Surface Texture	21

CHAPTER 5	22
MECHANICAL MEASUREMENTS	22
A. Hydrometers	22
B. Volume and Density	22
C. Flow Measurements	23
D. Flow Measurements at Cryogenic Temperatures	23
E. Air Speed Measurements	24
F. Mass Standards	25
G. Force Measurements	26
H. Vibration Measurements	27
I. Acoustic Measurements	28
CHAPTER 6	29
THERMODYNAMIC QUANTITIES	29
A. Pressure Measurements	29
B. Vacuum, Low Pressure and Leak Measurements	29
C. Laboratory and Industrial-Grade Thermometers	31
D. Thermocouples, Thermocouple Materials, Thermometer Indicators	32
E. Resistance Thermometry	34
F. Radiance Temperature Measurements	36
G. Humidity Measurements	37
H. Thermal Resistance Measurements	38
CHAPTER 7	39
OPTICAL RADIATION MEASUREMENTS	39
A. Photometric Measurements	39
B. Ozone Measurements	40
C. Optical Properties of Materials Measurements	40
D. Surface Color and Appearance	41
E. Spectroradiometric Measurements	41
F. Radiometric Standards in the Ultraviolet	43
G. Laser and Optoelectronic Components Used with Lasers	44
CHAPTER 8	46
IONIZING RADIATION MEASUREMENTS	46
A. Radioactivity Sources	46
B. Neutron Sources and Neutron Dosimetry	47
C. Dosimetry of X-Rays, Gamma-Rays, and Electrons	47
D. Dosimetry for High-Dose Applications	48
CHAPTER 9	50
ELECTROMAGNETIC MEASUREMENTS	50
A. Resistance Measurements	50
B. Impedance Measurements (Except Resistors)	52
C. Voltage Measurements	53
D. Precision Ratio Measurements	55

E.	Phase Meters and Standards and VOR Measurements	57
F.	Power and Energy Measurements, Low-Frequency	58
G.	RF, Microwave and Millimeter-Wave Measurements	59
H.	Electromagnetic Field Strength and Antenna Measurements	63
I.	Pulse Waveform Measurements	64
CHAPTER 10		65
TIME AND FREQUENCY MEASUREMENTS		65
A.	Broadcast and Measurement Services	65
B.	Calibration and Characterization of Oscillators and Amplifiers	66
C.	Test of PM/AM Noise Measurement Systems	66
CHAPTER 11		67
SEMINARS		67
ALPHABETICAL CROSS-INDEX		68

CHAPTER 1

POLICIES

A. Introduction

The calibration services of the National Institute of Standards and Technology (NIST) are designed to help the makers and users of precision instruments achieve the highest possible levels of measurement quality and productivity. The services listed in this Fee Schedule constitute the highest order of calibration services available in the United States. They directly link a customer's precision equipment or transfer standards to national and international measurement standards. These services are offered to public and private organizations and individuals alike.

For more specific information, the NIST Calibration Services Users Guide, SP 250, contains data on uncertainty and other technical references. Copies are available upon request or consult our website (see Section L of this chapter).

B. Types of Calibration Services

- Calibration Services
- Special Tests
- Measurement Assurance Programs (MAPs)

NIST provides Calibration Services using well-characterized, stable and predictable measurement processes. NIST calibrates instruments and devices that are metrologically suitable as reference or transfer standards.

Special Tests are so designated for one or more of the following reasons: (1) the specific type of calibration is seldom requested, thus precluding the maintenance of a large statistical base for characterizing the measurement process; (2) the test requested is unique; or (3) the service is still under development – meaning the measurement or calibration methods are still being perfected, or all the quality-control documentation has not been completed.

Measurement Assurance Programs are quality control programs for calibrating a customer's entire measurement system. In a typical MAP, a stable artifact or set of artifacts called transfer standards are first measured by NIST and then sent to a customer's laboratory for a series of measurements. The transfer standards are then returned to NIST for re-measurement, along with the participating laboratory's results. NIST reports its comparative findings to the customer and, when necessary, offers guidance on achieving and maintaining measurement quality. Successful use of a NIST MAP requires that the customer make periodic measurements of in-house check standards to estimate their measurement process uncertainty and to ensure that the measurement process remains in a state of statistical control. Unless a laboratory has a measurement quality assurance program to monitor its own measurement process parameters continuously, there is no value in participating in a MAP. In fact, NIST recommends that its customers establish and use a measurement quality assurance program to monitor their measurement parameters, whether or not they participate in a MAP.

C. Other NIST Measurement Transfer Services

National Voluntary Laboratory Accreditation Program (NVLAP)

NIST does not audit or regulate metrology laboratories as part of MAP or other calibration services. Calibration laboratories and testing facilities may be accredited by NIST under the National Voluntary Laboratory Accreditation Program (NVLAP). The basic procedures and general accreditation requirements of NVLAP are described in NIST Handbook 150. A participating laboratory may voluntarily take steps to improve or assess its measurement process. For further information about NVLAP, contact:

National Voluntary Laboratory Accreditation Program (NVLAP)
National Institute of Standards and Technology
100 Bureau Drive, Stop 2140
Gaithersburg, MD 20899-2140

Telephone: (301) 975-4016
Fax: (301) 926-2884
Email: NVLAP@nist.gov
Internet: www.nist.gov/nvlap

Standard Reference Materials® Group (SRM)

Calibration assistance and alternative paths for traceability are provided by NIST's Standard Reference Materials® Group. Chemical measurement instruments are not calibrated at NIST, but NIST provides suites of Standard Reference Materials® (SRMs) for the calibration of the instrument by the user. In addition, NIST provides SRMs for dimensional measurements, thermodynamic property and photometric measurements. For further information about SRMs, contact:

Standard Reference Materials® Group (SRM)
National Institute of Standards and Technology
100 Bureau Drive, Stop 2300
Gaithersburg, MD 20899-2300

Telephone: (301) 975-2200
Fax: (301) 926-4751
Email: srminfo@nist.gov
Internet: www.nist.gov/srm

Standard Reference Data Group (SRD)

Very few calibrations can be conducted without additional quantitative information related to measurement of physical or chemical properties. NIST develops and publishes evaluated data for technical and scientific applications called Standard Reference Data. For further information about SRD, contact:

Standard Reference Data Group (SRD)
National Institute of Standards and Technology
100 Bureau Drive, Stop 2300
Gaithersburg, MD 20899-2300

Telephone: (301) 975-2200
Fax: (301) 926-0416
Internet: www.nist.gov/srd

Weights and Measures Division (W&M)

The NIST Weights and Measures Division (W&M) provides measurement services to state and local governments responsible for marketplace transactions involving measurements. State weights and measures laboratories provide alternative sources for calibration services in mass, length, volume, and certain other measurement areas. For further information contact:

Weights and Measures Division (W&M)
National Institute of Standards and Technology
100 Bureau Drive, Stop 2600
Gaithersburg, MD 20899-2600

Telephone: (301) 975-4004
Fax: (301) 926-0647
Email: own@nist.gov
Internet: www.nist.gov/pml/wmd/

D. Criteria for Quality Assurance

All the measurement services listed in this document meet rigorous criteria for quality assurance. Calibration Services and MAPs satisfy the most demanding and explicit requirements in that they are carried out regularly under pre-established and well-defined conditions; the measurement processes involved are well-characterized, stable, and statistically controlled; and quality-control procedures are well-defined and strictly followed. Furthermore, each Calibration Service or MAP is planned and documented to permit continuity of service over time.

Quality

NIST has implemented a quality system for its measurement services. The NIST Quality System, www.nist.gov/qualitysystem/ (NIST QS), comprises policies and procedures that are documented in the NIST Quality Manual (NIST QM). NIST commits that the NIST QS be, to the extent allowed by statute and regulation, in conformity with the international standard **ISO/IEC 17025** and the relevant requirements of **ISO Guide 34** as they apply to the Standard Reference Materials (SRMs) and related services that NIST delivers. In general the scope of the NIST quality system for measurement services encompasses all services listed in the NIST Special Publication (SP) 250, NIST Calibration Services Users Guide and the NIST Special Publication (SP) 260, Standard Reference Materials Catalog. In particular, specific services covered by the NIST QS are those that are declared in conformity by the NIST Measurement Services Advisory Group (MSAG). For further details, consult the NIST Quality Manual for Measurement Services (NIST-QM--I).

E. Fees

NIST recovers the cost of providing calibration services by charging a fee for each calibration performed. The costs of services are published in the Fee Schedule, which is updated and published annually to reflect changes in prices and services. Even so, the cost of many services varies according to your exact calibration specifications; you must therefore provide the technical contact with an exact description of work before receiving a price quote.

NOTE: Fees for NIST services do not include shipping costs or insurance.

F. Reports of Calibration/Test Results

Reports on calibrations or other services are the property of the customer. Copies are supplied to other parties only as required by federal law or requested in writing by the customer. The results of calibrations and tests performed by NIST apply only to the specific instrument or standard at the time of test unless otherwise clearly stated.

G. Traceability

The primary purpose of the NIST Policy on Traceability is to state the NIST role with respect to traceability. The Policy presents the definition of measurement traceability used by NIST, and clarifies the roles of NIST and others in achieving traceability of measurement results for measurements both internal and external to NIST.

The NIST Policy on Traceability (www.nist.gov/traceability/) also addresses the role of NIST in providing its customers with the tools they need (a) to assist them in establishing traceability of their measurement results, and (b) to assess the claims of traceability made by others. This is achieved directly through the provision of NIST measurement-related products and services, through collaboration with relevant organizations, through development and dissemination of technical information on traceability, and through conducting coordinated outreach programs.

Many government regulations and commercial contracts require regulated organizations or contractors to verify that the measurements they have are “traceable” and to support the claim of traceability by keeping records that their own measuring equipment has been calibrated by laboratories or testing facilities whose measurements are part of this “unbroken chain”: The purpose of requiring traceability is to ensure that measurements are accurate representations of the specific quantity subject to measurement, within the uncertainty of the measurement.

NIST reports its calibration results with the measurement values accompanied by the uncertainties associated with the methods, operators, and environment at NIST. Users of these calibration services will make their own measurements with the calibrated instruments or artifacts. In addition to the uncertainty indicated by NIST, other uncertainties are inherent in the instrument, associated with the method or protocol in using the instrument, with the operator of the instrument, and with the physical environment (pressure, temperature,

humidity, etc.) in which the measurements are made. Thus, the measurements made with the calibrated instruments or artifacts by organizations outside of NIST have total uncertainty budgets associated with them, only one component of which is the uncertainty reported to them by NIST.

NIST often receives calls to verify the authenticity of a NIST Report of Test number appearing on another organization's report. Although NIST can verify the authenticity of its report numbers, having an authentic number does not provide complete assurance or evidence that the measurement value provided by another organization is traceable. Not only should there be an unbroken chain of comparisons, each provided measurement should be accompanied by a statement of uncertainty associated with the farthest link in the chain from NIST, that is, the last facility providing the measurement value. NIST does not have that information; only the facilities that provided the measurement values to the customer can provide the associated uncertainties and describe the traceability chain.

In summary, to adequately establish an audit trail for traceability, a proper calibration result should include: the assigned value, a stated uncertainty, identification of the standards used in the calibration, and the specification of any environmental conditions of the calibration where correction factors should be applied, if the standard or equipment were to be used under different environmental conditions.

NIST does not define nor enforce traceability except in its NVLAP laboratory accreditation program. Moreover, NIST is not legally required to comply with traceability requirements of other federal agencies; nor do we determine what must be done to comply with another party's contract or regulation calling for such traceability. However, NIST can and does provide technical advice on making measurements consistent with national standards.

Although NIST supports making the user aware of traceability and provides the user with details as to how traceability is established, NIST does not allow the prominent display of its name on proprietary products or in the advertising of them (See Section J of this chapter).

H. NIST Policy on Reporting Measurement Uncertainty

To ensure that NIST uncertainty statements are consistent across the organization and with international practice, NIST policy requires that all NIST measurements be accompanied by statements of uncertainty as discussed in NIST Technical Note 1297¹. That publication is based on the approach to expressing uncertainty in measurements recommended by the International Committee on Weights and Measures (CIPM)². That committee established general rules for evaluating and expressing uncertainty in measurements that are intended to be applicable to a broad spectrum of measurements. Copies of NIST TN 1297 are available upon request (see Section L) or on the web site: www.physics.nist.gov/Pubs/guidelines/contents.html.

The American National Standard for Expressing Uncertainty-U.S. Guide to the Expression of Uncertainty of Measurement (ANSI/NCSL Z540-2-1997) is available from the

NCSL International
2995 Wilderness Place, Suite 107
Boulder, CO 80301-5404
(303) 440-3339
www.ncsli.org/

NIST reports its calibration results with the measurement values accompanied by the uncertainties associated with the methods, operators, and environment at NIST. Users of these calibration services will make their own measurements with the calibrated instruments or artifacts. In addition to the uncertainty indicated by NIST, other uncertainties are inherent in the instrument, associated with the method or protocol in using the instrument, with the operator of the instrument, and with the physical environment (pressure, temperature, humidity, etc.) in which the measurements are made. Thus, the measurements made with the calibrated instruments or artifacts by organizations outside of NIST have total uncertainty budgets associated with them, only one component of which is the uncertainty reported to them by NIST.

I. NIST Policy Regarding Use of Metric (SI) Units

In accordance with the Metric Conversion Act of 1975 as amended by Section 5164 of the Omnibus Trade and Competitiveness Act of 1988 and as required by related provisions of the Code of Federal Regulations, the National Institute of Standards and Technology (NIST) uses the modern metric system of measurement units (International System of Units–SI) in all publications. When the field of application or the special needs of users of NIST publication require the use of non-SI units, the values of quantities are first stated in the SI units and the corresponding values expressed in non-SI units follow in parentheses. Copies of NIST SP 811³ are available upon request (see Section L) or on the web site: www.nist.gov/pml/pubs/

¹Taylor, B.N.; Kuyatt, C.E.; *Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Results*; NIST Technical Note 1297; U.S. Government Printing Office: Washington, DC (1994); available at <http://physics.nist.gov/Pubs/contents.html>.

²JCGM 100:2008; *Guide to the Expression of Uncertainty in Measurement*; (ISO GUM 1995 with Minor Corrections), Joint Committee for Guides in Metrology (JCGM) (2008); available at http://www.bipm.org/utls/common/documents/jcgm/JCGM_100_2008_E.pdf.

³Thompson, A.; Taylor, B.N.; *Guide for the Use of the International System of Units (SI)*; NIST Technical Note 811; U.S. Government Printing Office: Washington, DC (2008); available at <http://physics.nist.gov/Pubs/contents.html>.

J. Reference to NIST in Advertisements

The NIST measurement/test results or reports shall not be used to indicate or imply that NIST approves, recommends, or endorses the manufacturer, supplier, or user of any instruments or standards or that NIST in any way guarantees or predicts the future performance of items after calibration or test. No reference shall be made to NIST or to reports or results furnished by NIST in any advertising or sales promotions, which would indicate or imply that NIST approves, recommends, or endorses any proprietary product or proprietary material.

K. Disclaimer

Commercial products, materials, and instruments, are identified in our communications and documents for the sole purpose of adequately describing experimental or test procedures. In no event does such identification imply recommendation or endorsement by NIST of a particular product; nor does it imply that a named material or instrument is necessarily the best available for the purpose it serves.

L. Questions and Inquires

This Fee Schedule is intended to make the task of selecting and ordering an appropriate calibration service as quick and easy as possible. Nevertheless, when questions arise, you should contact NIST for immediate clarification.

Calibration Program
National Institute of Standards and Technology
100 Bureau Drive, Stop 2300
Gaithersburg, MD 20899-2300
Telephone: (301) 975-2200
Fax: (301) 869-3548
Email: calibrations@nist.gov
Internet: www.nist.gov/calibrations/

For technical questions concerning a specific service, directly contact the NIST staff member responsible for that calibration area.

M. Contracts and Signed Statements

As an agency of the United States Federal Government, Department of Commerce, the National Institute of Standards and Technology attests solely to the provisions described above. Receipt of orders by NIST does not imply acceptance of any provisions set forth in the order that are contrary to the policy, practice, or regulations of NIST or the U.S. Government. In general, NIST will not sign any affidavits, acknowledgement forms, or other documents that may be required by any domestic or foreign entity for policy governing procurement of goods and services.

CHAPTER 2

ORDERING INSTRUCTIONS FOR DOMESTIC CUSTOMERS

A. Customer Inquires

General customer inquiries for information or clarifications about the NIST calibration services may be directed as indicated in Section L of Chapter 1.

B. Prearrangements and Scheduling

Services should be arranged in advance, beginning with direct contact with a NIST technical staff member responsible for the desired service. Use the appropriate technical section of the Users Guide or Fee Schedule to determine whom to contact. This advance communication may answer your questions, clarify the policies and procedures briefly described here, and will permit you to schedule a tentative calibration date. Following the initial communication, you must complete and submit a purchase order and prepare to ship the item according to the procedures described below or agreed upon with the technical contact. If a calibration is scheduled far in advance, the item should not be shipped until shortly before the scheduled date; you must submit the purchase order (complete with the name and number of the desired service) before a firm calibration date can be assigned. When NIST receives your purchase order and assigns a firm service date, your order will be confirmed by the technical contact.

C. Purchase Orders

Before you ship an item for calibration, send a purchase order to the address listed in the appropriate technical section of the Users Guide or Fee Schedule. The purchase order must:

1. State both the name and number of the NIST service (listed in this Fee Schedule as the “Service ID Number”) being requested. **FAILURE TO INCLUDE THE SERVICE ORDER NUMBER WILL SERIOUSLY IMPEDE SCHEDULING AND SERVICE.**
2. Clearly identify the item(s) being sent for calibration, including any serial number(s) or model number(s).
3. Give the name, address, and telephone number of your company’s procurement officer, purchasing agent or other administrative/financial authority.
4. Give the name, address, and telephone number of your company’s technical contact, if different from above.
5. List separately the instructions and address for return shipment, insurance, mailing address for the calibration/test report, and billing address. (Federal or state agency requests for calibration services should be accompanied by a document authorizing that the cost of the service be billed to the agency).
6. Clearly state any special or necessary conditions of test, such as operating frequency or temperature.
7. Clearly state the customer identification number; i.e., customer’s employer identification number (EIN) for individuals; tax identification number (TIN) for organizations; or agency location code (ALC) for government customers.
8. If the calibration or test report is to be handled in a special manner, give instructions on the purchase order.

NOTE: Receipt of orders by NIST does not imply acceptance of any provisions set forth in the order that are contrary to the policy, practice, or regulations of NIST or the U.S. Government. In general, NIST will not

Page 7 of 75

sign any affidavits, acknowledgement forms, or other documents that may be required by company policy governing the procurement of goods and services.

D. Remit to

All **billing terms** are net **30 days** for domestic customers. Payment must be received or late fees will be accessed.

No discounts are allowed for early payment.

We **cannot accept a Letter of Credit** as a form of payment.

PAY.GOV

For NIST invoices, electronic payments can be submitted through Pay.gov by ACH, VISA, MasterCard, Discover, American Express or debit card. Go to www.pay.gov. Bypass the user id and password section; you do not need to be registered with Pay.gov to make a payment against our invoices. To locate the payment forms click on "by Agency Name" on the left hand side of the menu bar. Find and select the National Institute of Standards and Technology. Choose the appropriate NIST payment form that best fits your invoice. Complete all required fields and submit you payment.

Note: For ACH payments, please verify with your banking institution that your account is set up to have ACH payments processed.

Lockbox Information

NIST Lockbox accepts check payments for NIST. Please use the following address for all NIST payments:

NIST
P.O. Box 301505
Los Angeles, CA 90030-1505

Please remember that all checks must be drawn on a United States bank and made payable in US dollars. In addition, please continue to reference the NIST invoice/receivable number on the check stub.

Other Forms of Payment Accepted

In addition to checks, NIST also accepts VISA, MasterCard, Discover, and American Express. Customers can supply their credit card information and fax a copy of the invoice to Accounts Receivable at 310/975-8943 or mail the information to:

NIST
Mail Stop 1624
100 Bureau Drive
Gaithersburg, MD 20899-1624

E. Shipping, Insurance, and Risk of Loss

Ship the instrument or standard to the mailing address of the technical group providing the service. Please take note that the mailing address is not the same for every technical group.

Please adhere rigorously to the following procedures:

1. Ship only items in good repair. Apparatus in disrepair will not be calibrated. If defects are found, after calibration has begun, the procedure will be terminated, a report issued, and a charge levied for work completed.
2. Use strong, reusable packing materials and containers marked clearly and indelibly on the outside with the requestor's name, address and the following notation: **REUSABLE CONTAINER, DO NOT DESTROY.**

3. Follow any special shipping procedures given in the technical sections of the Calibration Services Users Guide, particularly those sections covering radiation and dosimetry measurements.
4. Insure the shipments to and from NIST and clearly state the method of return shipment. NIST will not assume liability for loss or damage unless such loss and damage result solely from the negligence of NIST personnel. If return shipment by parcel post is requested or is suitable, NIST will prepay the return shipment but will not insure it. When no shipping or insurance instructions are furnished, NIST will return the shipment by common carrier, collect and uninsured.
5. Shipments to NIST must be at FOB destinations (customer pays for shipping).
6. Return shipments are sent FOB origin (customer pays for shipping).

NOTE: Fees for NIST services do not include shipping cost or insurance.

F. Turnaround Time

Normal turnaround time for NIST calibration services varies greatly—usually from several weeks to several months depending on the type of service requested, and the service schedule. Some services are only scheduled once or twice a year with appointments made months in advance of the service date. To avoid unnecessary scheduling or administrative delays in the calibration process, always make arrangements with the technical contact for the service you wish to utilize prior to shipping your instrument or artifact to us.

G. Customer Checklist

Please refer to last page of this chapter for a Customer Checklist which is intended to assist you in developing the basic information required to process an order for calibration services at NIST.

Customer Checklist for Ordering NIST Calibration Services

Information Obtained from NIST Technical Contact	Comments
NIST Contact (name/telephone)	Provide this information on your purchase order (PO)
Is the service available?	Please make sure customer's technical contact discusses service with NIST technical contact before proceeding.
NIST Service Identification Number	Provide this information on your PO
Estimated cost of services	Provide this information on your PO
Estimated turnaround time	Many calibration services are batched. Find out when to send the instrument.
Special instructions	
Packaging instructions	
Shipping instructions	
Other Precautions	
Information Supplied by the Customer on Purchase Order	
Purchase order number	
Purchase order date	
Customer's tax identification number	
Customer's mailing address	
Customer's billing address	
Name, telephone number, fax number, email address of administrative or procurement contact point at customer's location	
Name, telephone number, fax number, email address of technical contact point at customer's location	
Ship-to address (including NIST technical contact name)	
Return address (for shipment back to customer)	
NIST Service Identification Number	
Estimated cost	
Shipping terms (no FOB destination on return shipment)	
Special instructions from customer's technical contact	

CHAPTER 3

SPECIAL INSTRUCTIONS FOR FOREIGN CUSTOMERS

A. Foreign Inquires

Foreign customers should address all inquiries to:

Calibration Program
National Institute of Standards and Technology
100 Bureau Drive, Stop 2300
Gaithersburg, MD 20899-2300
United States of America
Telephone: (301) 975-2200
Fax: (301) 869-3548
Email: calibrations@nist.gov
Internet: www.nist.gov/calibrations/

NOTE: Please clearly indicate your **city** and **country** on all correspondence so that we may promptly respond to your request.

B. Criteria for Providing Service

Under certain circumstances, NIST is authorized to provide measurement service, including calibration services, for organizations or individuals located outside the United States. However, the Calibration Program must review each request for calibration services to determine if services are available to the requestor's organization in the requestor's country. Foreign customers must provide the following information, in writing, to the Calibration Program (see address above):

1. Identification of the item(s) to be calibrated, including serial and model numbers.
2. A detailed description of the measurements that are needed, or indicate the service identification number.
3. A description of any special requirement/circumstance that might affect the decision to provide the service. For example, will adjustments have to be made to the instrument, or will the time period be restricted in which the device is available for calibration?
4. A complete name and address of the requestor's organization.

C. Special Instructions

If the request for calibration service is accepted by NIST, the requesting organization will be notified of the cost of service and will be given the contact information for the NIST technical unit that will perform the measurements. The requesting organization must then complete the following steps:

1. Contact the NIST technical staff that will perform the service to determine the time schedule.
2. Send a purchase order to the Calibration Program. Provide complete addresses, including country, for returning the instrument and for mailing the calibration or test report.
3. NIST policy requires prepayment for all NIST calibration services requested by non-U.S. organizations. Before proceeding with any service(s), we will need a check, money order or a bank wire transfer. The prepayment must be for the full amount and be drawn on a U.S. bank. The prepayment methods are as follows:

No discounts are allowed for early payment.

We **cannot accept a Letter of Credit** as a form of payment.

PAY.GOV

For NIST invoices, electronic payments can be submitted through Pay.gov by ACH, VISA, MasterCard, Discover, American Express or debt card. Go to www.pay.gov. Bypass the user id and password section; you do not need to be registered with Pay.gov to make a payment against our invoices. To locate the payment forms click on “by Agency Name” on the left hand side of the menu bar. Find and select the National Institute of Standards and Technology. Choose the appropriate NIST payment form that best fits your invoice. Complete all required fields and submit your payment.

Note: For ACH payments, please verify with your banking institution that your account is set up to have ACH payments processed.

Lockbox Information

NIST Lockbox accepts check payments for NIST. Please use the following address for all NIST payments:

NIST
P.O. Box 301505
Los Angeles, CA 90030-1505

Please remember that all checks must be drawn on a United States bank and made payable in US dollars. In addition, please continue to reference the NIST invoice/receivable number on the check stub.

Other Forms of Payment Accepted

In addition to checks, NIST also accepts VISA, MasterCard, Discover, and American Express. Customers can supply their credit card information and fax a copy of the invoice to Accounts Receivable at 310/975-8943 or mail the information to:

NIST
Mail Stop 1624
100 Bureau Drive
Gaithersburg, MD 20899-1624

Wire Payments

Payments may also be sent by wire using the US Department of Treasury FEDWIRE system and it can be done so to the following bank:

Treas NYC (Account is with the Federal Reserve Bank of New York)
U.S. Dept. of Treasury
33 Liberty Street
New York, NY 10045
Phone: 001-202-874-7132

In Payment Details field, CL329930001
ABA# 021030004
Account # 13060001
Account Name: TREAS NYC/CTR/BNF=/NIST/AC-13060001

Reference “Calibrations” to enable us to identify your payment. In addition, please be sure to pay any fees assessed for your bank wire transfers; otherwise, they will deduct it from your prepayment wire.

We cannot accept wire payment make through the Swift system only FEDWIRE. Therefore, we do not have a Swift code.

PLEASE NOTE: Our account number and name are of critical importance and must be referenced in order for NIST to be properly credited with your payment. It must appear in the precise manner shown to allow for the automated processing and classification of the funds transfer message. In addition, please refer to the NIST invoice number, your purchase order number, your country, and any other pertinent information that would help us identify you payment.

This transfer of funds can only be accomplished by your company going through a U.S. correspondent bank or by having your country's central bank send a swift telecommunication system message to the Federal Reserve Bank. **Be sure to cover any processing fees your bank may charge you.** Questions on bank wiring can be directed to the NIST Accounts Receivable Office at 301/975-3880, email: billing@nist.gov, or fax at 301/975-8943.

4. Before shipping the instrument or standard to the appropriate NIST technical unit, you must arrange with a customs broker for entry of the instrument into the U.S. with transportation to and from the port of entry to NIST prepaid. Air freight is most satisfactory. Entry bond is required for instruments not manufactured in the U.S. If arrangements are made with a broker in the country of origin, that broker should, in turn, have a U.S. customs broker in or near the port of entry to arrange for the entry of the instrument and its transportation to NIST. Direct arrangements can be made with customs brokers located in the Washington, DC/Baltimore, Maryland, metropolitan area or in the Denver, Colorado, area, as appropriate. These brokers must arrange for transportation to the port of exit after testing/calibration is completed.

D. Shipping Charges

The calibration costs quoted **do not** include shipping, insurance, or the services of a customs broker. You must arrange and pay for these services separately. For your information, NIST currently uses the following customs brokers:

Gaithersburg, Maryland

Laing International
P.O. Box 16144
Washington, DC 20041
Phone: (703) 471-9279
Fax: (703) 471-8436

Boulder, Colorado

FedEx Trade Networks
4725 Paris Street, Suite 200
Denver, CO 80239
Phone: (303) 371-9550
Fax: (303) 373-0850

You are **not required** to use these customs brokers, but may select a broker of your choice.

CHAPTER 4

DIMENSIONAL MEASUREMENTS

A. Length Measurements

A.1 Gage Blocks

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Eric Stanfield (Long blocks)	(301) 975-4882	eric.stanfield@nist.gov	NIST
Beverly Connelly (Short blocks)	(301) 975-2485	beverly.connelly@nist.gov	100 Bureau Drive, Stop 8211
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

A.1 Gage Blocks		
Service ID Number	Description of Services	Fee (\$)
10010C	Gage Blocks: Set Up Charge, per order	187
10011C	Mechanical Comparisons, per Block (100 mm and shorter)	115
10012C	Mechanical Comparisons, per Block (over 100 mm)	275
10013C	Interferometry, per Block (100 mm and shorter), Maximum 25 Blocks per Order	323
10014C	Interferometry, per Block (over 100 mm)	At Cost
10015C	Non-standard size Gage Blocks	At Cost

Fees are subject to change without notice.

A.2 Line Standards

<u>Technical Contact:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
William B. Penzes	(301) 975-3477	wpenzes@nist.gov	NIST
Thomas W. LeBrun	(301) 975-4256	thomas.lebrun@nist.gov	100 Bureau Drive, Stop 8212
			Gaithersburg, MD 20899-8212

Please contact the technical staff before shipping instruments or standards to the address listed above.

A.2 Line Standards		
Service ID Number	Description of Service	Fee (\$)
10020C	Line Standards: Scales, < 1 m (40 inches), 4 Passes	9294
10021C	Line Standards: Scales, < 1 m (40 inches), 8 Passes	14247
10022C	Line Standards: Stage Micrometer, Per Scale, 30 Intervals, 2 Passes	1578
10023C	Line Standards: Stage Micrometer, Per Scale, 30 Intervals, 4 Passes	1995

10024C	Line Standards: End Standards, < 1 m	9557
10025C	Line Standards: Grid Plates, Less than 60 Intervals, 1 D Linear Calibration	15823

Fees are subject to change without notice.

A.3 Metal Tapes/Scales and Long Length Artifacts

<u>Technical Contact:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Chris Blackburn	(301) 975-6413	chris.blackburn@nist.gov	NIST
Daniel S. Sawyer	(301) 975-5863	daniel.sawyer@nist.gov	100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

A.3 Metal Tapes/Scales and Long Length Artifacts		
Service ID Number	Description of Services	Fee (\$)
10030C	Metal Tapes: Surveying, Oil Gaging, and General Purpose; Metal Scales	At Cost
10040S	Special Tests of Long Length Artifacts	At Cost

A.4 Step Gages

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
John Stoup	(301) 975-3476	john.stoup@nist.gov	NIST
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

A.4 Step Gages		
Service ID Number	Description of Services	Fee (\$)
11060S	Special Tests of Step Gages	At Cost

A.5 Other Length Standards

Technical Contacts:

John Stoup
Theodore Doiron

Telephone:

(301) 975-3476
(301) 975-3472

Email:

john.stoup@nist.gov
theodore.doiron@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

A.5 Other Length Standards		
Service ID Number	Description of Services	Fee (\$)
10050S	Special Tests of Length Standards	At Cost

B. Diameter and Roundness Measurements

Technical Contacts:

Eric S. Stanfield
Theodore Doiron

Telephone:

(301) 975-4882
(301) 975-3472

Email:

eric.stanfield@nist.gov
theodore.doiron@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
11010S	Special Tests of Cylindrical Diameter Standards (i.e. Plug and Pin Gages): Set Up Charge, per order	191
11011S	Mechanical comparison, per Gage (25 mm and smaller)	115
11012S	Interferometry, per Gage (50 mm and smaller)	262
11013S	Per Gage (over 50 mm)	At Cost
11014S	Roundness trace, per trace	216
11020C	Measuring Wires for Threads and Gears: Set Up Charge, per order	191
11021C	Single Wire, per wire	117
13020S	Special Tests of Roundness (Sphere and Hemisphere Types) Reversal Method: Radial Deviations from Best Fit Least-Squares Circle at 360 positions	1351
13030S	Special Tests of Roundness Calibration Specimens	At Cost
11030S	Special Tests of Spherical Diameter Standards; Balls: Set Up Charge, per order (applies to mechanical comparison and interferometry)	191
11031S	Mechanical Comparison (51 mm or smaller), Average Diameter, per ball, Expanded Uncertainty, $U \sim \pm 89$ nm to 115 nm	111
11032S	Mechanical Comparison (over 51 mm), Average Diameter, per ball	At Cost
11033S	Interferometry (25 mm or smaller) Average Diameter, per ball, Expanded Uncertainty, $U \sim \pm 30$ nm	563

11034S	Ball Out-of-Roundness: Least-Squares Out-of-Roundness and Polar Plots, price per trace (Typically three orthogonal traces for spheres and five traces for CMM calibration spheres) price per trace	108
Special Tests of Internal Diameter Standards: Ring Gages		
11040S	Plain Ring Gages, per ring	899
11050S	Special Tests of Diameter	At Cost

Fees are subject to change without notice.

C. Complex Dimensional Standards

C.1 API Threaded Plug and Ring Gages

Technical Contacts:

Dennis Everett
(12010C–12070S)
Eric Stanfield
(11050S)
John Stoup
(12060S)
Theodore Doiron

Telephone:

(301) 975-5272
(301) 975-4882
(301) 975-3476
(301) 975-3472

Email:

dennis.everett@nist.gov
eric.stanfield@nist.gov
john.stoup@nist.gov
theodore.doiron@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

C.1 API Threaded Plug and Ring Gages		
Service ID Number	Description of Services	Fee (\$)
12010C	Spec 5, 1.005 inches to 7 5/8 inches	2313
12011C	Spec 5, 8 5/8 inches to 20 inches	3610
12012C	Buttress Casing, 4 1/2 inches to 9 5/8 inches	2759
12013C	Buttress Casing, 10 inches to 13 3/8 inches	3354
12014C	Buttress Casing, 16 inches to 20 inches	3617
12015C	Line Pipe, 1/8 inch to 6 inches (New)	2317
12016C	Line Pipe, 8 inches to 20 inches (New)	3081
12017C	Extreme Line Casing, 5 inches to 7 inches (New)	3867
12018C	Extreme Line Casing, 5 inches to 7 inches (Used)	1450
12019C	Extreme Line Casing, 7 5/8 inches to 10 inches (New)	4468
12021C	Extreme Line Casing, 7 5/8 inches to 10 inches (Used)	1842
12022C	Spec 7 (Rotary), NC 23 - NC 61 (New)	3008
12023C	Spec 7 (Rotary), NC 70 (New)	3187
12024C	Spec 7 (Rotary), 1 inch to 4 1/2 inches, Reg. (New)	3011
12025C	Spec 7 (Rotary), 5 1/2 inches to 8 5/8 inches, Reg. (New)	3263

12026C	Spec 7 (Rotary), Any Type (Used)	1342
12027C	Spec 11B (Sucker Rods) P1, P2 Pin Go P7, P8 Pin Go B1, B2 Box Go (NEW)	1584/per set
12028C	Spec 11B (Sucker Rods) P1, P2 Pin Go P7, P8 Pin Go B1, B2 Box Go (USED)	793/per set
12029C	Spec 11B (Sucker Rods) P3, P4 Pin Cone B3, B4 Box Cone (NEW)	1866/per set
12031C	Spec 11B (Sucker Rods) P3, P4 Pin Cone B3, B4 Box Cone (USED)	720/per set
12032C	Spec 11B (Sucker Rods) P5, P6 Pin Cone B5, B6 Box Cone (NEW)	1217/per set
12033C	Spec 11B (Sucker Rods) P5, P6 Pin B5, B6 Box Cone (USED)	638/per set
12050S	Special Tests of Threaded Plug and Ring Gages	At Cost
12060S, 11050S	Special Tests of Two– and Three–Dimensional Gages	At Cost
12070S	Special Complex Dimensional Test, by Prearrangement	At Cost

Fees are subject to change without notice.

C.2 Sieves

Technical Contacts:

Theodore Doiron

Telephone:

(301) 975-3472

Email:

theodore.doiron@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

C.2 Sieves		
Service ID Number	Description of Services	Fee (\$)
10060S	Special Tests of Sieves	239

Fees are subject to change without notice.

C.3 Algorithms Testing and Evaluation Program for Coordinate Measuring Systems

Technical Contact:

Craig M. Shakarji

Telephone:

(301) 975-3545

Email:

shakarji@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8211

Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

C.3 Algorithms Testing and Evaluation Program for Coordinate Measuring Systems		
Service ID Number	Description of Services	Fee (\$)
10070S	Special Test of CMS Software: NIST-generated data sets (basic service)	2046
10071S	Special Test of CMS Software: NIST-generated data sets (per geometry evaluated)	At Cost
10072S	Special Test of CMS Software: NIST-generated data sets, standard level (per geometry evaluated)	907
10080S	Special Test of CMS Software: Customer-generated data sets (basic service)	At Cost
10081S	Special Test of CMS Software: Customer-generated data sets (per geometry evaluated)	At Cost
10082S	Special Test of CMS Software: Customer-generated data sets, standard level (per geometry evaluated)	At Cost

Fees are subject to change without notice.

E. Optical Reference Planes and Roundness Standards

Technical Contacts:

Eric S. Stanfield

Theodore Doiron

Telephone:

(301) 975-4882

(301) 975-3472

Email:

eric.stanfield@nist.gov

theodore.doiron@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8211

Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
13010S	Special Tests of Optical Reference Planes (Flats): Optical Flat, ≤ 152 mm (6"), Per Surface	1611
13011S	Special Tests of Optical Reference Planes (Flats): Optical Flat, 152 mm to 203 mm (8")	2128
13012S	Special Tests of Optical Reference Planes (Flats): Optical Flat, 203 mm to 304 mm	2801
13013S	Special Tests of Optical Reference Planes (Flats): Optical Flat, ≥ 304 mm (12")	3529
13014S	Special Tests of Optical Reference Planes (Flats): Three Flat Calibration	At Cost

Fees are subject to change without notice.

F. Angular Measurements

Technical Contacts:

Bryon S. Faust
Theodore Doiron

Telephone:

(301) 975-4351
(301) 975-3472

Email:

bryon.faust@nist.gov
theodore.doiron@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
14010C	Angle Gage Blocks: Set Up Charge, per order	193
14011C	Angle Gage Blocks, per block	189
14020S	Special Tests of Optical Polygons	At Cost
14030S	Special Tests of Rotary and Indexing Tables: Every 30°	2691
14031S	Special Tests of Rotary and Indexing Tables: (30°, 5°, 1°) Calibration	5279
14040S	Special Tests of Optical Wedges: Fixed-Angle Wedge	906
14041S	Special Tests of Optical Wedges: Variable-Angle Wedge	At Cost
14050S	Special Angular Measurements, by Prearrangement	At Cost

Fees are subject to change without notice.

G. Laser Measurements

Technical Contact:

Jack Stone

Telephone:

(301) 975-5638

Email:

jack.stone@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8211
Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
14510S	Laser Frequency/Wavelength, Full Calibration	2937
14511S	Quick Check of Frequency/Wavelength at Laboratory Conditions	1557

Fees are subject to change without notice.

H. Surface Texture

Technical Contact:

T. Brian Renegar

Telephone:

(301) 975-4274

Email:

brenegar@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8212
Gaithersburg, MD 20899-8212

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
15010C	Roughness Calibration Specimens	1721
15030C	Step Height Measurements	1721
15040S	Surface Roughness and Topography Special Tests	At Cost

Fees are subject to change without notice.

CHAPTER 5

MECHANICAL MEASUREMENTS

A. Hydrometers

Technical Contacts:

Sherry Sheckels
John D. Wright

Telephone:

(301) 975-5940
(301) 975-5937

Email:

sherry.sheckels@nist.gov
john.wright@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8361
Gaithersburg, MD 20899-8361

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
16010C	Reference Standard Hydrometers	1403
16020S	Hydrometers Special Tests	At Cost

Fees are subject to change without notice.

B. Volume and Density

Technical Contacts:

Sherry Sheckels
John D. Wright

Telephone:

(301) 975-5940
(301) 975-5937

Email:

sherry.sheckels@nist.gov
john.wright@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8361
Gaithersburg, MD 20899-8361

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
17010C	Volume Standards < 380 L	2160
17020C	Volume Standards > 380 L, 2 points	3147
17030C	Volume Standards > 380 L, 5 points	5322
17040S	Volume Special Tests	At Cost

Fees are subject to change without notice.

C. Flow Measurements

Technical Contacts:

Gina Kline
(Gas Flow)
John D. Wright
(Gas Flow)
Iosif Shinder
(Water Flow)
Aaron Johnson
(Gas Flow and Hydrocarbon Flow)
Sherry Sheckels
(Hydrocarbon Flow)

Telephone:

(301) 975-4813
(301) 975-5937
(301) 975-5943
(301) 975-5954
(301) 975-5940

Email

gina.kline@nist.gov
john.wright@nist.gov
iosif.shinder@nist.gov
aaron.johnson@nist.gov
sherry.sheckels@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8361
Gaithersburg, MD 20899-8361

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
18010C	Gas Flow Meters	5593
18015C	Natural Gas Flow Calibration	At Cost
18020C	Water Flow Meters	5475
18030C	Hydrocarbon Liquid Flow Meters	5115
18040C	Transfer Standards	At Cost
18050S	Gas Flow Special Tests	At Cost
18060S	Water Flow Special Tests	At Cost
18070S	Hydrocarbon Liquid Flow Special Tests	At Cost

Fees are subject to change without notice.

See 30063S Special Tests for Low-Gas-Flow Instrumentation

D. Flow Measurements at Cryogenic Temperatures

Technical Contact:

Michael Lewis
Fax: (303) 497-5224

Telephone:

(303) 497-3458

Email

mlewis@boulder.nist.gov

Mailing Address:

NIST
325 Broadway, MC 838.09
Boulder, CO 80305-3328

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
18800S	Special Tests of Cryogenic Liquid Flow	At Cost

E. Air Speed Measurements

Technical Contacts:

J. Michael Hall
Iosif Shinder

Telephone:

(301) 975-5947
(301) 975-5943

Email:

j.hall@nist.gov
iosif.shinder@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8361
Gaithersburg, MD 20899-8361

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
19010C	High Air Speed Instruments 1.3 m/s to 67 m/s (3 mph to 150 mph)	3217
19020C	Low Air Speed Instruments 0.3 m/s to 10.2 m/s (15 fpm to 2 000 fpm)	3217
19030S	High Air Speed Special Tests	At Cost
19040S	Low Air Speed Special Tests	At Cost

Fees are subject to change without notice.

F. Mass Standards

Technical Contacts:

Vincent Lee
Zeina J. Jabbour

Telephone:

(301) 975-6453
(301) 975-4468

Email:

vincent.lee@nist.gov
zeina.jabbour@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8221
Gaithersburg, MD 20899-8221

Administrative and Logistics:

Jeanne Bruins (301) 975-6624 jeanne.bruins@nist.gov
Fax: (301) 417-0514

IMPORTANT NOTES TO OUR CUSTOMERS:

1. Please contact the technical staff for correct Fee and appropriate Service ID Number for your equipment.
2. Please do not send purchase orders and equipment to NIST without scheduling a calibration.
3. Calibrations for variations of complete standard weight sets are available. These may require fewer (or more) than the number of measurement series required for the calibration of a complete standard weight set. These variations will affect pricing of the service. Contact the technical staff for details.
4. If you request a calibration estimate (which includes cost and turnaround time estimates and start date of calibration), please note that we need to receive a confirmation from you to reserve the calibration start date. If no confirmation is received within 30 days, the reservation will be cancelled and the start date given to the next customer.

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
22010C	Complete Standard Weight Set (1 mg to 100 g) by weighing design (see note 3 above)	17449
22020C	Complete Standard Weight Set (1 mg to 1 kg) by weighing design (see note 3 above)	20004
22030C	Complete Standard Weight Set (2 kg to 30 kg) by weighing design (see note 3 above)	8679
22040C	Single Weights (1 mg to 1 kg) (see note 3 above)	2133
22060C	Single Weights (2 kg to 30 kg) (see note 3 above)	2781
22080C	Single Weights (> 30 kg (>60 lb) to 1200 kg, 2 double substitution weighings)	At Cost
22100C	Single Weights (> 1200 kg to 30 000 kg)	At Cost
22110C	Single Weights (> 30 kg to 1200 kg, calibrated in a weighing design)	At Cost
22130C	Single Weights for Dead Weight Pressure Testers 5.9 kg to 22.7 kg (13 lb to 50 lb)	1470
22140C	Single Weights for Dead Weight Pressure Testers > 22.7 kg (> 50 lb)	At Cost
22150C	Single Weights for Dead Weight Pressure Testers < 5.9 kg (< 13 lb)	1151
22170S	Special Mass Measurement Services	At Cost

Fees are subject to change without notice.

G. Force Measurements

Technical Contacts:

Rick L. Seifarth
Samuel L. Ho
Kevin L. Chesnutwood

Telephone:

(301) 975-6652
(301) 975-6648
(301) 975-6653

Email:

ricky.seifarth@nist.gov
samuel.ho@nist.gov
kchesnut@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8222
Gaithersburg, MD 20899-8222

Administrative and Logistics:

Jeanne Bruins (301) 975-6624 jeanne.bruins@nist.gov
Fax: (301) 417-0514

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
23010C	Force Transducers to 112 540 N (25 300 lbf) 1 mode	3799
23020C	Extra observation	75
23030C	Additional bridges	1029
23040C	Force Transducers to 112 540 N (25 300 lbf) 2 modes	6300
23050C	Extra observation	75
23060C	Additional bridges	1035
23070C	Force Transducers 112 540 N to 498 201 N (25 300 lbf to 112 000 lbf) 1 mode	4367
23080C	Extra observation	75
23090C	Additional bridges	1175
23100C	Force Transducers 112 540 N to 498 201 N (25 300 lbf to 112 000 lbf) 2 modes	8579
23110C	Extra observation	223
23120C	Additional bridges	2365
23130C	Force Transducers 498 205 N to 1 334 467 N (112 000 lbf to 300 000 lbf) 1 mode	8908
23140C	Extra observation	223
23150C	Additional bridges	1469
23160C	Force Transducers 498 205 N to 1 334 467 N (112 000 lbf to 300 000 lbf) 2 modes	14239
23170C	Extra observation	309
23180C	Additional bridges	2658
23190C	Force Transducers 1 334 471 N to 4 448 222 N (300 00 lbf to 1 000 000 lbf) 1 mode	10663
23200C	Extra observation	223
23210C	Additional bridges	2071

23220C	Force Transducers 1 334 471 N to 4 448 222 N (300 00 lbf to 1 000 000 lbf) 2 modes	16927
23230C	Extra observation	294
23240C	Additional bridges	3693
23250C	Force Transducers over 4 448 222 N (1 000 000 lbf) compression only	At Cost
23260S	Special Tests of Force Transducers	At Cost

Fees are subject to change without notice.

H. Vibration Measurements

Technical Contacts:

David J. Evans

Telephone:

(301) 975-6637

Email:

david.evans@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8220
Gaithersburg, MD 20899-8220

Administrative and Logistics:

Terri Kroft

(301) 975-2058

terri.kroft@nist.gov

Fax: (301) 990-3851

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Freq. Range	Peak Accel.	Fee (\$)
24010C	Transducer Sensitivity	2 Hz to 160 Hz	0.2 g _n to 1 g _n	3508
24020C	Transducer Sensitivity	10 Hz to 3500 Hz	2 g _n to 10 g _n	6137
24030C	Transducer Sensitivity	10 Hz to 10 kHz	2 g _n to 10 g _n	8768
24040S	Shock Measurement	250 Hz to 10 kHz	20 g _n to 10 000 g _n	At Cost
24050S	Transducer Sensitivity	3 kHz to 20 kHz	4 g _n to 200 g _n	At Cost
24060S	Special Vibration Tests, by Prearrangement			At Cost

Fees are subject to change without notice.

I. Acoustic Measurements

Technical Contacts:

Victor Nedzelnitsky
Randall P. Wagner
David J. Evans

Telephone:

(301) 975-6638
(301) 975-6619
(301) 975-6637

Email:

vnedzelnitsky@nist.gov
randall.wagner@nist.gov
david.evans@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8221
Gaithersburg, MD 20899-8221

Administrative and Logistics:

Terri Kroft (301) 975-2058 terri.kroft@nist.gov
Fax: (301) 990-3851

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
25010C	Pressure Response: WE Type 640AA microphones or equivalent (e.g., Tokyo Riko Type ECL MR103; Bruel & Kjaer Type 4160, Bruel & Kjaer Types 4144 or 4132 with DB0111 adapter), 50 Hz to 10 000 Hz	6887
25020C	Pressure Response: WE Type 640AA microphones or equivalent (e.g., Tokyo Riko Type ECL MR103; Bruel & Kjaer Type 4160; Bruel & Kjaer Types 4144 or 4132 with DB0111 adapter), 50 Hz to 20 000 Hz	8295
25030C	Pressure Response: Tokyo Riko Type ECL MR112, Bruel & Kjaer Type 4134, or equivalent half-inch microphones, 50 Hz to 10 000 Hz	7983
25040C	Pressure Response: Tokyo Riko Type EC MR112, Bruel & Kjaer Type 4134, or equivalent half-inch microphones, 50 Hz to 20 000 Hz	10047
25050C	Free-Field Response: Tokyo Riko Type ECL MR112, Bruel & Kjaer Types 4133, 4134, 4165, 4166, 4180, or equivalent half-inch microphones, 2500 Hz to 20 000 Hz	7560
25060S	Special Tests of Acoustic Devices	At Cost
25070S	Special Tests of Audiometers/Earphones	6402

Fees are subject to change without notice.

CHAPTER 6

THERMODYNAMIC QUANTITIES

A. Pressure Measurements

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Douglas A. Olson (All Services)	(301) 975-2956	dolson@nist.gov	NIST
R. Gregory Driver (Pneumatic gages) (29010C, 29030C, 29035C, 29040S)	(301) 975-4832	rdriver@nist.gov	100 Bureau Drive, Stop 8364 Gaithersburg, MD 20899-8364

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
29010C	Deadweight Piston Gages	7535
29020C	Controlled Clearance Piston Gages	At Cost
29030C	Pressure Gages and Transducers	At Cost
29035C	Non-mercurial Barometers and Manometers	At Cost
29040S	Special Tests of Pressure Gages	At Cost

Fees are subject to change without notice.

B. Vacuum, Low Pressure and Leak Measurements

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Jay Hendricks (30010C–30025C, 30040S)	(301) 975-4836	jay.hendricks@nist.gov	NIST
James A. Fedchak (30029C–30032S, 30034C–30038C, 30050S)	(301) 975-8962	james.fedchak@nist.gov	100 Bureau Drive, Stop 8364 Gaithersburg, MD 20899-8364
Dana R. Defibaugh (30060S–30062C)	(301) 975-2471	dana.defibaugh@nist.gov	
Robert F. Berg (30063S)	(301) 975-2466	robert.berg@nist.gov	

Please contact the technical staff before shipping instruments or standards to the address listed above.

NOTE: 1 Torr = 133.322 Pa

Service ID Number	Description of Services	Fee (\$)
30010C	One Low-Pressure Transducer Absolute or Differential Relative to Vacuum	5227
30011C	Additional Transducer (Cost per Unit)	4953
30020C	One Differential Low-Pressure Transducer Relative to near Atmospheric Pressure	5797
30021C	Additional Transducers (Cost per Unit)	5250
30025C	Piston Gauges versus an Ultrasonic Interferometer Manometer	At Cost

30029C	Spinning Rotor Gages, below 0.1 Pa, Nitrogen Gas with NIST Controller	5030
30030C	Spinning Rotor Gages, below 0.1 Pa, Nitrogen Gas Customer Controller with IEEE-488	5030
30031C	Spinning Rotor Gages, below 0.1 Pa, Additional Gas	6088
30032S	Special Test of Spinning Rotor Gages, Transition Range (above 0.1 Pa)	At Cost
30034C	Ionization Gages, 10^{-4} Pa to 10^{-1} Pa, Nitrogen Gas	5745
30035C	Ionization Gages, 10^{-5} Pa to 10^{-1} Pa, Nitrogen Gas	7011
30036C	Ionization Gages, 10^{-7} Pa to 10^{-1} Pa, Nitrogen Gas	7953
30037C	Ionization Gages, Additional Filament or Gas for Above Tests	At Cost
30038C	Ionization Gages, NIST Supplied Gage Tube for Above Tests	303
30040S	Special Tests of Low-Pressure Gages	At Cost
30050S	Special Tests of Vacuum Gages	At Cost
30060S	Special Tests of Leak Artifacts (10^{-13} mol/s to 10^{-6} mol/s)	At Cost
30061C	Helium Leaks, Primary Calibration (10^{-13} mol/s to 10^{-6} mol/s)	6673
30062C	Helium Leaks, Comparison Calibration (10^{-13} mol/s to 10^{-9} mol/s)	5214
30063S	Special Tests of Low-Gas-Flow Instruments	At Cost

Fees are subject to change without notice.

NOTE: Due to the time and effort required preparing vacuum instrumentation for calibration it is particularly important that they be known to be in proper operating condition when they are submitted to NIST. Equipment will be inspected upon receipt and the customer notified of any obvious damage. If the schedule permits, we will cooperate with the customer's efforts to repair or replace damaged equipment so that the calibration of their equipment can proceed. However, concealed damage or operational deficiencies most likely will not be detected before the instrument is operating on the vacuum system or the calibration has started; in such cases, **if the equipment cannot be calibrated, we will charge 20 % of the regular calibration fee for low-pressure transducers and 30 % of the regular fee for spinning rotor and ionization gages.**

C. Laboratory and Industrial-Grade Thermometers

Technical Contact:

C. Dawn Cross

Telephone:

(301) 975-4822

Email:

dawn.cross@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8363
Gaithersburg, MD 20899-8363

Please contact the technical staff before shipping instruments or standards to the address listed above.

NOTE: NIST no longer calibrates mercury in glass thermometers as of March 1, 2011. Fahrenheit ranges are not direct conversions of the Celsius ranges.

Service ID Number	Description of Services	Fee (\$)
31010C	Organic Liquid in Glass Thermometers (0 °C to 200 °C) (32 °F to 392 °F)	325/pt
31040C	Organic Liquid in Glass Thermometers (−1 °C to −110 °C) (31 °F to −166 °F)	441/pt
31050C	Organic Liquid in Glass Thermometers (Liquid N ₂) (−196 °C or −321 °F)	325/pt
31100C	Quantity Tests of Liquid-In-Glass Thermometers	At Cost
31110S	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (0 °C to 150 °C) (32 °F to 300 °F)	325/pt
31120S	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (151 °C to 315 °C) (301 °F to 600 °F)	441/pt
31130S	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (316 °C to 550 °C) (601 °F to 1022 °F)	441/pt
31140S	Special Tests of Industrial Platinum Resistance Thermometer, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (−1 °C to −110 °C) (31 °F to −166 °F)	441/pt
31150S	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (Liquid N ₂) (−196 °C or −321 °F)	325/pt
31190S	Additional copy of Table from Results of 31110S–31150S at a Later Date	278
31200S	Preliminary Examination of Ineligible Thermometer	117
31250S	Additional Copy of Report	101
31260S	Special Thermometry Services, by Prearrangement	At Cost

Fees are subject to change without notice.

D. Thermocouples, Thermocouple Materials, Thermometer Indicators

Technical Contacts:

Karen Garrity
(32010C–32101C, 32150S)
C. Dawn Cross
(32110C–32147C)

Telephone:

(301) 975-4818
(301) 975-4822

Email:

kgarrity@nist.gov
dawn.cross@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8363
Gaithersburg, MD 20899-8363

Please contact the technical staff before shipping instruments or standards to the address listed above.

Comparison Calibrations, Temperature Measured with Thermocouple (TC)						
Service ID Number	TC Type	Temp Range °C	Points	Min. Length (mm)	Temp. (°C)	Fee (\$)
32010C	S	0 to 1450	1 °C or 1 °F Interv. Table	700	0 to 1100 1450	1228
32020C	R	0 to 1450	1 °C or 1 °F Interv. Table	700	0 to 1100 1450	1228
32030C	B	0 to 1750	1 °C or 1 °F Interv. Table	1000	0 to 800 800 to 1100 1450 1750	1789
32031C	B	800 to 1750	1 °C or 1 °F Interv. Table	1000	800 to 1100 1450 1750	1228
32040C	E	0 to 1000	4 to 15	700	0 to 1000	1228
32041C	J	0 to 760	4 to 15	700	0 to 760	1228
32042C	K	0 to 1100	4 to 15	700	0 to 1100	1228
32043C	N	0 to 1100	4 to 15	700	0 to 1100	1228
32044C	T	0 to 400	4 to 15	700	0 to 400	1228
32050C	Comparison calibration, two point minimum, per point, for all items above					537/pt
32060C	Each additional table of results at 1 °C or 1 °F intervals, for type S, R, or B at later date					331
32061C	Each additional table of results at 1 °C or 1 °F intervals, for type S, R, or B at time of test					205
32070C	Thermocouple materials tested against Pt Thermoelectric standard, 4 to 15 points, 700 mm minimum lengths					1228

Calibration at Metal Freezing Points, Minimum TC Wire Diameter 0.4 mm, Freezing Point Determination at Au, Ag, Al, and Zn						
Service ID Number	TC Type	Temp Range °C	Points	Min. Length (mm)	Temp. (°C)	Fee (\$)
32090C	S or R	0 to 1450	Table 1 °C or 1 °F Interv. and equations to generate table	1000	at freezing points 0 to 1100 1450	2726
32091C	Type S or T, freezing point determination, per point, two point minimum					880
Calibration of Digital Thermometer Indicator or Portable Potentiometer						
32100C	Indicator or Potentiometer, first dial or range					916
32101C	Indicator or Potentiometer, each additional dial or range					511
Comparison Calibration of Thermocouples or Thermocouple Materials Tested against Pt Thermoelectric Standard, Temperature Measured with Standard Platinum Resistance Thermometer, Minimum TC Wire Length 1.0 m, 2 Point Minimum						
32110C	Range −110 °C to 315 °C and Liquid N ₂ (−196 °C) or −166 °F to 600 °F and Liquid N ₂ (−321 °F), Expanded Uncertainty 0.4 °C					565/pt
32120C	316 °C to 550 °C or 601 °F to 1022 °F, Expanded Uncertainty 0.5 °C					565/pt
Table at one degree intervals for Type T thermocouple for any of the following options: (The cost of the table will be in addition to the calibration per point covered under fee schedule services numbered 32110C–32120C).						
32141C	Option 1: Table from −196 °C to + 300°C (−321 °F to +572 °F), calibration points at (−196, −110, 250, +100, +200, +300) °C					586
32142C	Option 2: Table from −196 °C to +100 °C (−321 °F to +212 °F), calibration points at (−196, −110, 250, +50, +100) °C					586
32143C	Option 3: Table from -110 °C to +300 °C (−166 °F to +572 °F), calibration points at (-110, 250, +100, +200, +300) °C					586
32144C	Option 4: Table from −110 °C to +100 °C (−166 °F to +212 °F), calibration points at (−110, 250, +50, +100) °C					586
32145C	Option 5: Table from 0 °C to 300 °C (32 °F to +572 °F), calibration points at (+100, +200, +300) °C					586
32146C	Option 6: Table from −110 °C to 0 °C (−166 °F to +32 °F), calibration points at (−110, 250) °C					586
32147C	Option 7: Table from −196 °C to 0 °C (−321 °F to +32 °F), calibration points at (−196, −110, 250) °C					586
32150S	Special Tests of Thermocouples and Thermocouple Materials					At Cost

Fees are subject to change without notice.

NOTE: Due to the extra time involved in calibrating sheathed thermocouples, a surcharge of 20 % of the cost of calibrating bare-wire thermocouples will be added to the relevant fees listed above.

E. Resistance Thermometry

Technical Contacts:

Weston L. Tew
(0.65 K to 84 K)
Gregory F. Strouse
(83 K to 962 °C)

Telephone:

(301) 975-4811
(301) 975-4803

Email:

wtew@nist.gov
gstrouse@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8363
Gaithersburg, MD 20899-8363

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
33010C	Capsule SPRT (13.8 K to 30 °C) e-H ₂ to Ga	11151
33020C	Capsule SPRT (13.8 K to 157 °C) e-H ₂ to In	11447
33030C	Capsule SPRT (13.8 K to 232 °C) e-H ₂ to Sn	11742
33031C	Capsule SPRT (24.5 K to 30 °C) Ne to Ga	8295
33032C	Capsule SPRT (24.5 K to 157 °C) Ne to In	8589
33033C	Capsule SPRT (24.5 K to 232 °C) Ne to Sn	8883
33040C	Capsule SPRT(54 K to 30 °C) O ₂ to Ga	7429
33050C	Capsule SPRT (54 K to 157 °C) O ₂ to In	7723
33060S	Capsule SPRT (54 K to 232 °C) O ₂ to Sn	8018
33065S	Capsule SPRT (83 K to 0.01 °C) Ar to TPW	At Cost
33070C	Capsule SPRT (83 K to 30 °C) Ar to Ga	3239
33080C	Capsule SPRT (83 K to 157 °C) Ar to In	3976
33090C	Capsule SPRT (83 K to 232 °C) Ar to Sn	4713
33100C	Capsule SPRT (0 °C to 30 °C) TPW to Ga	1316
33110C	Capsule SPRT (0 °C to 157 °C) TPW to In	1907
33120C	Capsule SPRT (0 °C to 232 °C) TPW to Sn	2644
33130C	Capsule SPRT (234 K to 30 °C) Hg to Ga	3604
33140C	Rhodium-Iron or Platinum-Cobalt Resistance Thermometers (0.65 K to 24.6 K)	12273
33141C	Rhodium-Iron or Platinum-Cobalt Resistance Thermometers (0.65 K to 83.8 K)	15077
33142C	n-Type Germanium Resistance Thermometers (0.65 K to 24.6 K)	12011
33150C	Long Stem SPRT (83 K to 0.01 °C) Ar to TPW	2973
33160C	Long Stem SPRT (83 K to 30 °C) Ar to Ga	3416
33170C	Long Stem SPRT (83 K to 157 °C) Ar to In	3637
33180C	Long Stem SPRT (83 K to 232 °C) Ar to Sn	4006

33190C	Long Stem SPRT (83 K to 420 °C) Ar to Zn	4595
33200C	Long Stem SPRT (83 K to 661 °C) Ar to Al	5849
33210C	Long Stem SPRT (234 K to 30 °C) Hg to Ga	2529
33220C	Long Stem SPRT (234 K to 157 °C) Hg to In	3266
33230C	Long Stem SPRT (234 K to 232 °C) Hg to Sn	3635
33240C	Long Stem SPRT (234 K to 420 °C) Hg to Zn	4151
33250C	Long Stem SPRT (234 K to 661 °C) Hg to Al	4742
33260C	Long Stem SPRT (0 °C to 30 °C) TPW to Ga	1273
33270C	Long Stem SPRT (0 °C to 157 °C) TPW to In	1937
33280C	Long Stem SPRT (0 °C to 232 °C) TPW to Sn	2527
33290C	Long Stem SPRT (0 °C to 420 °C) TPW to Zn	3043
33300C	Long Stem SPRT (0 °C to 661 °C) TPW to Al	3633
33310C	Long Stem SPRT (0 °C to 962 °C) TPW to Ag	7026
33320C	Additional Copy of Table from Results of 33010C–33310C at Time of Test	68
33330C	Additional Copy of Table from Results of 33010C–33310C at a Later Date	433
33340C	Minimum Charge for Unsuitable Thermometer	904
33350S	Special Tests of Resistance Thermometers	At Cost
33355S	Special Tests of Cryogenic Resistance Thermometers	At Cost
33360S	Special Tests of Thermometric Fixed-Point Devices	At Cost
33370M	Measurement Assurance Program for Temperature 83 K to 420 °C (Ar to Zn)	16641
33380M	Measurement Assurance Program for Temperature 83 K to 661 °C (Ar to Al)	19985

Fees are subject to change without notice.

F. Radiance Temperature Measurements

Technical Contact:

Charles E. Gibson

Telephone:

(301) 975-2329

Email:

cgibson@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8441
Gaithersburg, MD 20899-8441

Fax: (301) 869-5700

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
Calibration reports are issued giving the radiance temperature of the blackbody at 655.48 nm versus the scale reading, output current, or output voltage		
35010C	Radiance Temperature Standard, Disappearing Filament Optical Pyrometer (800 °C to 2400 °C, 4 to 12 points, 1 range)	9524
35020C	Radiance Temperature Standard, Disappearing Filament Optical Pyrometers (each additional range up to 4200 °C, only available with 35010C)	6879
35040C	Radiance Temperature Standard, Disappearing Filament Optical Pyrometer (800 °C to 4200 °C, 1 range, 3 or fewer points)	4762
Calibration reports are issued giving the radiance temperature of the lamp at 655.48 nm versus the lamp current		
35050C	Radiance Temperature Standard, Tungsten Strip Lamp (800 °C to 2300 °C, 6 to 16 points)	13228
35051C	Recalibration of Tungsten Strip Lamp (800 °C to 2300 °C, 6 to 16 points)	11111
35060C	Radiance Temperature Standard, Tungsten Strip Lamp (800 °C to 2300 °C, 5 or fewer points)	8466
35061C	Recalibration of Tungsten Strip Lamp (800 °C to 2300 °C, 5 or fewer points)	6349
Calibration reports are issued giving the radiance temperature of the reference blackbody at 655.48 nm, 900 nm or 1000 nm versus the display reading, output current, or output voltage		
35070S	Special Tests of Radiation Thermometers (800 °C to 2700 °C)	At Cost
35071C	Radiance Temperature Standard, Radiation Thermometer (800 °C to 2700 °C, 6 to 20 points)	10053
35072C	Radiance Temperature Standard, Radiation Thermometer (800 °C to 2700 °C, 5 or fewer points)	5291
Calibration reports are issued giving the thermodynamic temperature of the reference blackbody versus the radiation thermometer display reading, output current, or output voltage.		
35080S	Special Tests of Radiation Thermometers (15 °C to 900 °C)	At Cost
35081C	Radiance Temperature Standard, Radiation Thermometer (15 °C to 70 °C, 3 points)	5291
35082C	Radiance Temperature Standard, Radiation Thermometer (70 °C to 170 °C, 3 points)	5291

35083C	Radiance Temperature Standard, Radiation Thermometer (400 °C to 700 °C, 3 points)	5291
35084C	Radiance Temperature Standard, Radiation Thermometer (700 °C to 900 °C, 3 points)	5291
Calibration reports are issued giving the thermodynamic temperature of the reference blackbody versus the test blackbody source display reading.		
35090S	Special Tests of Blackbody Sources (15 °C to 900 °C)	At Cost
Calibration reports are issued giving heat flux at the sensor surface versus the output voltage.		
35100S	Special Tests of Radiative Heat Flux Sensors	At Cost
35101C	Radiative Heat Flux Sensors (1 W/cm ² to 5 W/cm ² , 9 points, Gardon and Schmidt-Boelter type sensors)	4233
35102C	Additional Radiative Heat Flux Sensor (same model as 35101C)	3175

Fees are subject to change without notice.

Calibration Schedule: Requests for calibration services are scheduled after receipt of a purchase order.

G. Humidity Measurements

Technical Contacts:

Peter H. Huang

Joseph T. Hodges

Gregory E. Scace

Telephone:

(301) 975-2621

(301) 975-2626

(301) 975-2605

(301) 975-2626

Email

phuang@nist.gov

jhodges@nist.gov

gregory.scace@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8363

Gaithersburg, MD 20899-8363

Fax: (301) 548-0206

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
36010C	Dew-Point Hygrometers (+25 °C to –15 °C)	4341
36020C	Dew-Point Hygrometers (–70 °C to –15 °C)	9144
36030C	Electric Hygrometers	At Cost
36040C	Electrolytic Hygrometers	At Cost
36050C	Aspirated Hygrometers	At Cost
36060C	Pneumatic Bridge Hygrometers	At Cost
36070S	Special Tests of Humidity	At Cost

Fees are subject to change without notice.

H. Thermal Resistance Measurements

Technical Contact:
Robert Zarr

Telephone:
(301) 975-6436

Email:
robert.zarr@nist.gov

Mailing Address:
NIST
100 Bureau Drive, Stop 8632
Gaithersburg, MD 20899-8632
Fax: (301) 975-5433

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Material	Specimen Thickness (mm)	Mean Temp. (K)	Temp. Difference (K)	Relative Expanded Uncertainty $k = 2$ (%)	Fee (\$)
36110C	Fibrous glass blanket	25	297	22 or 28	1.0	3099
36120C	Fibrous glass blanket	75	297	22 or 28	1.5	3099
36130C	Fibrous glass blanket	150	297	22 or 28	2.5	3099
36140C	Fibrous glass blanket	225	297	22 or 28	3.0	3099
36150C	Quantity Tests of Fibrous glass blanket		297	22 or 28		At Cost
36199S	Special Tests of Thermal Insulation		280 to 330	22 or 28		At Cost

Fees are subject to change without notice.

CHAPTER 7

OPTICAL RADIATION MEASUREMENTS

A. Photometric Measurements

Technical Contact:

Cameron Miller

Telephone:

(301) 975-4713

Email:

c.miller@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8442
Gaithersburg, MD 20899-8442
Fax: (301) 840-8551

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
37010C	Luminous Intensity and Color Temperature Standard Lamps	5095
37020S	Special Tests for luminous Intensity and Color Temperature of Submitted Lamps	At Cost
37030C	Color Temperature Standard Lamps	4036
37040C	Each Additional Color Temperature for 37030C	793
37050S	Special Tests for Color Temperature of Submitted Lamps	At Cost
37060S	Special Tests for Total Luminous Flux of Submitted Incandescent Lamps and Florescent Lamps	At Cost
37070C	Opal Glass Luminance Coefficient Standards	4041
37080S	Special Tests for Submitted Luminance Sources and Transmitting Diffusers	At Cost
37090S	Special Tests for Photometers, Illuminance Meters and Luminance Meters	At Cost
37100S	Special Photometric Tests	At Cost
37110S	Special Tests for Submitted Flashing-Light Photometers	At Cost
37120S	Special Tests for Color Measuring Instruments for Displays	At Cost
37130S	Special Tests for Luminous Intensity and Luminous Flux of LEDs	At Cost

Fees are subject to change without notice.

B. Ozone Measurements

Technical Contacts:

James Norris

Telephone:

(301) 975-3936

Email:

james.norris@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8393
Gaithersburg, MD 20899-8393

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
37510C	Ozone Instrument Calibrations	2006
37515S	Additional Special Tests for Ozone Instruments	At Cost
37520C	NIST Standard Reference Photometer (NIST SRP)	73960
37525S	NIST Standard Reference Photometer Maintenance	At Cost
37530C	Validation of NIST Standard Reference Photometer (NIST SRP)	4749
37535S	Additional Special Tests for Validation of NIST Standard Reference Photometer (NIST SRP)	At Cost

Fees are subject to change without notice.

C. Optical Properties of Materials Measurements

Technical Contacts:

David W. Allen

Telephone:

(301) 975-3680

Email:

david.allen@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8442
Gaithersburg, MD 20899-8442
Fax: (301) 840-8551

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
38010C	Spectral Transmittance Filters (Cobalt Blue Glass)	3477
38020C	Spectral Transmittance Filters (Copper Green Glass)	3477
38030C	Spectral Transmittance Filters (Carbon Yellow Glass)	3477
38040C	Spectral Transmittance Filters (Selenium Orange Glass)	3477
38060S	Special Tests of Spectral Reflectance (250 nm to 2500 nm)	At Cost
38061S	Special Tests of Spectral Transmittance (250 nm to 2500 nm)	At Cost
38075S	Special Tests Infrared Reflectance, Transmittance, and Emittance of Materials	At Cost

Fees are subject to change without notice.

D. Surface Color and Appearance

Technical Contacts:

Maria E. Nadal
(38090S and 38091S)
Martin Wilson
(38100C–38130C)

Telephone:

(301) 975-4632

(301) 975-2356

Email:

maria.nadal@nist.gov

martin.wilson@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8442
Gaithersburg, MD 20899-8442
Fax: (301) 840-8551

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
38090S	Specular Gloss	At Cost
38091S	Special Test of 0°/45° Surface Color	At Cost
38100C	X-Ray Film Step Tablet Transmission Density Standard (Replacement for SRM 1001)	1059
38110C	Recalibration of an X-Ray Film Step Tablet Transmission Density Standard	1535
38120C	Photographic Film Step Tablet Transmission Density Standard (Replacement for SRM 1008)	1296
38130C	Recalibration of a Photographic Film Step Tablet Transmission Density Standard	1747

Fees are subject to change without notice.

E. Spectroradiometric Measurements

E.1 Spectroradiometric Source Measurements

Technical Contacts:

Charles E. Gibson
(39010C–39060S)
Jeanne M. Houston
(39071C–39081S)
Thomas C. Larason
(39080S, 39081S, 39100S)
George Eppeldauer
(39090S)

Telephone:

(301) 975-2329

(301) 975-2327

(301) 975-2338

Email:

cgibson@nist.gov

jeanne.houston@nist.gov

(301) 975-2334

geppeldauer@nist.gov

Mailing/Shipping Address:

NIST
100 Bureau Drive, Stop 8441
Gaithersburg, MD 20899-8441
Fax: (301) 869-5700
tlarason@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

E.1 Spectroradiometric Source Measurements		
Service ID Number	Description of Services	Fee (\$)
NIST calibrates and issues a type 30A/T24/13 tungsten strip lamp with a mogul bi-post base.		
39010C	Spectral Radiance Standard, Tungsten Strip Lamp (225 nm to 2400 nm) (other spectral ranges are available under no. 39060S)	18094
NIST calibrates customer supplied integrating sphere sources and maps the source aperture.		
39020C	Spectral Radiance Standard, Integrating Sphere Source (300 nm to 1000 nm in 25 nm steps)	10384

39021C	Spectral Radiance Standard, Integrating Sphere Source (300 nm to 2400 nm in 25 nm steps)	14592
NIST calibrates and issues an 1000 W, tungsten quartz-halogen lamp mounted in a medium bi-post base. The calibrations are performed at 50 cm.		
39030C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 450 nm)	13547
39031C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 450 nm)	9655
39032C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (350 nm to 800 nm)	13547
39033C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (350 nm to 800 nm)	9655
39040C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 1600 nm)	16758
39041C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 1600 nm)	13160
39045C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 2400 nm)	19580
39046C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 2400 nm)	16119
NIST calibrates and issues a 30 W deuterium arc lamp mounted in a medium bi-post base.		
39050C	Spectral Irradiance Standard, 30W Deuterium Arc Lamp (200 nm to 400 nm)	17119
39051C	Recalibration of 30 W Deuterium Arc Lamp (200 nm to 400 nm)	12829
39060S	Special Tests of Radiometric Sources	At Cost
E.2 Spectroradiometric Detector Measurements		
39071C	UV Silicon Photodiodes	5718
39072C	Recalibration of UV Silicon Photodiodes	4526
39073C	Visible to NIR Silicon Photodiodes	5811
39074C	Recalibration of Visible to NIR Silicon Photodiodes	4526
39075S	Special Tests of NIR Photodiodes	At Cost
39077C	UV to Near-Infrared Silicon Photodiodes (Hamamatsu S2281)	6942
39078C	Recalibration of UV to Near-Infrared Silicon Photodiodes (Hamamatsu S1337–1010BQ or S2281)	5658
39080S	Special Tests of Radiometric Detectors	At Cost
39081S	Special Tests of Photodetector Responsivity Spatial Uniformity	At Cost
39090S	Special Tests of IR Detectors	At Cost
39100S	Special Tests of Irradiance Detectors	At Cost
39200S	Special Tests of Aperture Area	At Cost

Fees are subject to change without notice.

F. Radiometric Standards in the Ultraviolet

Technical Contact:

Robert E. Vest

Telephone:

(301) 975-3992

Email:

rvest@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8411
Gaithersburg, MD 20899-8411

Charles S. Tarrio

(301) 975-3737

ctarrio@nist.gov

NIST

Steven Grantham

(301) 975-5528

grantham@nist.gov

100 Bureau Drive, Stop 8410

Thomas B. Lucatorto

(301) 975-3734

tlucatorto@nist.gov

Gaithersburg, MD 20899-8410

Please contact the technical staff before shipping instruments or standards to the address listed above.

Standard Detectors in the Far Ultraviolet		
Service ID Number	Description of Services	Fee (\$)
40510C	Detector Standard, Windowless Photodiode (5 nm to 122 nm)	4936
40511C	Recalibration of Detector Standard (5 nm to 122 nm)	4491
40520C	Detector Standard, Windowless Photodiode (18 nm to 122 nm)	3548
40521C	Recalibration of Detector Standard (18 nm to 122 nm)	3103
40530C	Detector Standard, Windowless Photodiode (52 nm to 122 nm)	2160
40531C	Recalibration of Detector Standard (52 nm to 122 nm)	1715
40540C	Uncalibrated Windowless Photodiode	911
40560C	Detector Standard, Windowless Photodiode (116 nm to 254 nm)	12733
40561C	Recalibration of Detector Standard (116 nm to 254 nm)	1715
40599S	Special Tests on Detectors from the Ultraviolet (254 nm) to the Soft X-Ray Region (5 nm)	At Cost
40600C	Testing the Contamination Potential of Extreme Ultraviolet (EUV) Photoresists	At Cost
406001S	Special Tests of Extreme Ultraviolet (EUV) Photoresists	At Cost

Fees are subject to change without notice.

G. Laser and Optoelectronic Components Used with Lasers

Technical Contacts:

John H. Lehman
(CW Laser Radiometry)

Paul D. Hale
(High Speed Measurements)

Christopher L. Cromer
(Pulsed-Laser Radiometry)

Timothy Drapela
(Optical Fiber and Component Measurements - other than Fiber Power)

Telephone:

(303) 497-3654

(303) 497-5367

(303) 497-5620

(303) 497-5858

Email:

lehman@boulder.nist.gov

hale@boulder.nist.gov

cromer@boulder.nist.gov

drapela@boulder.nist.gov

Mailing Address:

NIST
325 Broadway, MC 815.01
Boulder, CO 80305-3328

Administrative and Logistics:

John Lomax

(303) 497-3842

john.lomax@boulder.nist.gov

FAX: (303) 497-4286

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
42110C	Laser Power and Energy Meter (or Detector) Calibrations at a Single Standard Wavelength and Power (See Table 4)	
	CW Laser Power below 2 Watts	4807
	Pulsed Laser Energy (Q-switched YAG) at 1064 nm	4987
	CW Laser Power at 1064 nm above 2 Watts and 10.6 μ m	6129
	Pulsed Laser Energy (Excimer) at 248 nm and 193 nm	5825
42111C	Same as 42110C, Additional Standard Wavelengths or Powers (See Table 4)	
	CW Laser Power below 2 Watts	2403
	Pulsed Laser Energy (Q-switched YAG) at 1064 nm	3606
	CW Laser Power at 1064 nm above 2 Watts and 10.6 μ m above 1 Watt	4746
	Pulsed Laser Energy (Excimer) at 248 nm and 193 nm	4382
42120M	Laser Power and Energy Measurement Assurance Program (MAP)	At Cost
42130C	Optical Fiber Power Meter (or Detectors Used with Lasers) Calibrations at a Single Standard Wavelength and Connector Type (See Table 5)	3305
42131C	Same as 42130C, Additional Standard Wavelengths or Connector Types (See Table 5)	1322
42140M	Optical Fiber Power Meter Measurement Assurance Program (MAP)	At Cost
42150M	Low-Level Laser Measurement Assurance Program (MAP)	At Cost
42151C	Low-Level Laser Radiometer Calibration	At Cost
42155C	Calibration Service of Optoelectronic Frequency Response for Combined Photodiode/RF Power Sensor Transfer Standards	At Cost
42160S	Special Test for Frequency Response Measurements of Detectors Used with Lasers	At Cost

42161S	Special Test for Impulse Response Measurements of Detectors Used with Lasers	At Cost
42162S	Special Test for High Accuracy Laser and Optical Fiber Power Measurements	At Cost
42164C	Spectral Responsivity Measurements of Laser and Optical Fiber Power Meters (or Detectors Used with Lasers)	3125
42165S	Special Test for Spatial Uniformity of Laser and Optical Fiber Power Meters and Detectors Used with Lasers	At Cost
42166C	Calibration for Linearity Measurements of Optical Fiber Power Meters (or Detectors Used with Lasers)	At Cost
42167S	Special Test for Linearity Measurements of High-Power Laser Power Meters (or Detectors Used with Lasers)	At Cost
42170S	Special Test for General Laser Measurements, by Prearrangement	At Cost
42180S	Special Test for General Optical Fiber Power Measurements, by Prearrangement	At Cost
42190S	Special Test for Optical Fiber and Fiber Component Measurements (other than Fiber Power), by Prearrangement	At Cost
42210C	Spectral Responsivity Measurements with Curve Fitting of Laser and Optical Meters (or Detectors used with Lasers)	4085
42220C	Calibration Service for Instruments that Measure Laser Beam Diameter	At Cost

Fees are subject to change without notice.

CHAPTER 8

IONIZING RADIATION MEASUREMENTS

A. Radioactivity Sources

<u>Technical Contacts:</u> Lisa R. Karam (All Services) M.P. Unterweger (43030C, 43040C, 43070S, 43090S) Jeffrey T. Cessna (43010C, 43020C, 43060C, 43070S) Lynne King (43030C, 43040C, 43070S, 43090S)	<u>Telephone:</u> (301) 975-5561 (301) 975-5536 (301) 975-5539 (301) 975-5544	<u>Email:</u> lisa.karam@nist.gov munterweger@nist.gov jcessna@nist.gov lynne.king@nist.gov	<u>Mailing Address:</u> NIST 100 Bureau Drive, Stop 8462 Gaithersburg, MD 20899-8462 Attn: Jeffrey Cessna
--	--	--	--

Administrative and Logistics:
 Jeffrey Cessna (301) 975-5539 jcessna@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
43010C	Gamma-Ray-Emitting Radionuclides in Solution (Half Lives Greater than 15 Days)	3287
43020C	Gamma-Ray-Emitting Radionuclides in Solution (Half Lives Less than 15 Days)	5312
43030C	Alpha- and Beta-Particle-Emitting Solid Sources, NIST 2 $\pi\alpha/\beta$ Proportional Counter	2111
43040C	Beta-Particle-Emitting Solid Sources (Activity), NIST 2 $\pi\alpha/\beta$ Proportional Counter	3044
43050C	Mixed Alpha-Emitting Solid Sources, NIST 2 $\pi\alpha/\beta$ Proportional Counter in Conjunction with a Solid State Detector	3243
43060S	Special Tests of Beta-Particle-Emitting Solution Sources, Liquid Scintillation Counting	6023
43070S	Special Tests of Beta-Particle-Emitting Solution Sources, Other Techniques	At Cost
43090S	Special Tests of Alpha-Particle-Emitting Solid Sources	At Cost

Fees are subject to change without notice.

B. Neutron Sources and Neutron Dosimetry

Technical Contacts:

M. Scott Dewey
(All Services Except 44060C)
Alan K. Thompson
(44060C, 44100S)

Telephone:

(301) 975-4843
(301) 975-4666

Email:

mdewey@nist.gov
alan.thompson@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8461
Gaithersburg, MD 20899-8461

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
44010C	Radioactive Neutron Sources Emission Rates (10^5 s^{-1} to 10^9 s^{-1})	6202
44020C	Radioactive Neutron Sources Emission Rates (10^8 s^{-1} to 10^{10} s^{-1})	6202
44060C	Personnel Protection Instrumentation, Californium Source Bare and Moderated	At Cost
44070C	Activation Detector Dosimetry, Thermal Neutrons	At Cost
44080C	Activation Detector Dosimetry, Californium Fission Neutrons	At Cost
44090C	Activation Detector Dosimetry, ^{235}U Cavity Fission Sources	At Cost
44100S	Special Tests of Neutron Sources and Dosimeters	At Cost

Fees are subject to change without notice.

C. Dosimetry of X-Rays, Gamma-Rays, and Electrons

C.1 X-Ray and Gamma-Ray Measuring Instruments

Technical Contacts:

Michelle O'Brien
(46010C-46050S)
Ronaldo Minniti
(46010C-46110C)
Michael G. Mitch
(46010C-47040S)

Telephone:

(301) 975-2014
(301) 975-5586
(301) 975-5491

Email:

michelle.obrien@nist.gov
ronaldo.minniti@nist.gov
michael.mitch@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8460
Gaithersburg, MD 20899-8460
Fax: (301) 869-7682

Please contact the technical staff before shipping instruments or standards to the address listed above.

C.1 X-Ray and Gamma-Ray Measuring Instruments		
Service ID Number	Description of Services	Fee (\$)
Air-Kerma (Exposure)		
46010C	Radiation Detectors—Calibration in ^{60}Co and ^{137}Cs Gamma-Ray Beams, per Detector, per Set-Up, per Beam Code	2001
46011C	Radiation Detectors—Calibration in X-Ray Beams (see Tables 6, 7 and 8), per Detector, per Set-Up, per Beam Code	1915
46020C	Passive Dosimeters—Irradiation of Up to Six, One Beam Quality at One Set-up	2239
46021C	Up to Six Additional Dosimeters at Same Set-up and Beam Quality	1387

46030S	Special Tests of High-Gain Electrometers - Charge Sensitivity, One Set of Switch Positions, with 46010C/46011C, by Prearrangement	1441
46040S	Special Tests of kV Measuring Devices	At Cost
46050S	Special Tests of X-Ray and Gamma-Ray Measuring Instruments	At Cost
Absorbed Dose to Water From ⁶⁰Co Beam		
46110C	Radiation Detectors - Calibration in a ⁶⁰ Co Gamma-Ray Beam	2467
C.2 Sealed Gamma-Ray Sources or Beta-Particle Sources, and Measuring Instruments		
47010C	Gamma-Ray Sources Similar to NIST Standards - ⁶⁰ Co to ¹³⁷ Cs, Having Air-Kerma Strengths 10 μ Gy m ² /h to 1500 μ Gy m ² /h; and ¹⁹² Ir Sources of the Same Type Used to Calibrate Reentrant Chamber, Having Air-Kerma Strengths 0.1 μ Gy m ² /h to 30 μ Gy m ² /h	3745
47011C	Each Additional Gamma-Ray Source of Same Radionuclide	3600
47020C	¹²⁵ I or ¹⁰³ Pd Sources: Seeds Having Air-Kerma Strengths 0.5 μ Gy m ² /h to 100 μ Gy m ² /h	2824
47021C	Each Additional ¹²⁵ I or ¹⁰³ Pd Source of Same Radionuclide/Design Submitted with Above	2736
47030C	Beta-Particle Sources Calibrated for Surface Dose Rate	1155
47035C	Beta-Particle Sources Calibrated for Radiation Protection	937
47036C	Ionization Chamber Calibrated with Beta-Particle Sources for Radiation Protection	937
47040S	Special Tests of Gamma-Ray and Beta-Particle Sources	At Cost

Fees are subject to change without notice.

D. Dosimetry for High-Dose Applications

D.1 Dosimetry of High-Energy Electron Beams

Technical Contacts:

Marc D. Desrosiers

Michael G. Mitch

Telephone:

(301) 975-5639

(301) 975-5491

Email:

marc.desrosiers@nist.gov

michael.mitch@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8460

Gaithersburg, MD 20899-8460

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
D.1 Dosimetry of High-Energy Electron Beams		
48010M	Dose Interpretation of NIST-Packaged Dosimeters Irradiated by Customer - Two Dosimeters	1353
48011M	Each Additional Dosimeter	618
48020S	Special Tests of Electron-Beam Dosimeters	At Cost

D.2 Dosimetry of Photon Beams		
49010C	First Irradiation of a Customer Supplied Dosimeter with ⁶⁰ Co Gamma-Rays	1240
49011C	Each Additional Irradiation at Ambient (20 °C to 30 °C) Temperatures	134
49015C	Setup for Each Non-Ambient Irradiation Temperature (–77 °C to +19 °C and +31 °C to +70 °C)	400
49016C	Each Additional Irradiation at Non-Ambient Temperature Under 49015C	193
49020C	Dose Measurement Session of 1 NIST Transfer Dosimeter and Certificate	1322
49021C	Additional Measurement Session of 1 NIST Transfer Dosimeter, Same Certificate with 49020C	635
49022C	Additional Measurement of 1 NIST Transfer Dosimeter, Same Session	134
49030C	Dose Measurement Session of 1 Dosimeter and 90 Day Summary Certificate	1113
49031C	Additional Measurement Session of 1 Dosimeter, Same Certificate with 49030C	335
49032C	Additional Measurement of 1 Dosimeter, Same Session	53
49050S	Special Measurement Services for Dosimeter Response and Dose Distributions	At Cost

Fees are subject to change without notice.

CHAPTER 9

ELECTROMAGNETIC MEASUREMENTS

A. Resistance Measurements

A.1 DC Resistance Standards and Measurements

Technical Contacts:

George R. Jones
Randolph E. Elmquist

Telephone:

(301) 975-4225
(301) 975-6591

Email:

george.jones@nist.gov
relmquist@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Calibration fees are the most critical element in funding the metrology services that we provide, and represent the direct cost of providing calibration services for dc resistors and shunts. These services often reach beyond traceability to include detailed consultation. Currently our fees also must recover some of the rapidly increasing costs of providing year-round, readily accessible services and maintaining state-of-the-art traceability through the quantum Hall effect standard. Customers of our most critical calibration services, NIST Service ID numbers 51130C and 51131C, have benefited the most from our efforts to reduce turn-around time through automation, and to provide the world's best level of uncertainty, while keeping these test fees at a reasonable level. In fiscal year 2009, these fees will increase substantially. This necessary fee increase will enable continued support of the most fundamental metrology needs of the users of these services.

Service ID Number	Description of Services	Fee (\$)
51100S	Special Resistance Measurements Services, by Prearrangement	At Cost
51110M	Measurement Assurance Program for Resistance	At Cost
51130C	Standard Resistor, Thomas-Type, 1 Ω	3858
51131C	Standard Resistor, Evanohm Wirewound High Precision, 10 k Ω	3734
51132C	Standard Resistor, Four-Terminal 0.0001 Ω	2819
51133C	Standard Resistor, Four-Terminal 0.001 Ω	2392
51134C	Standard Resistor, Four-Terminal 0.01 Ω	2392
51135C	Standard Resistor, Four-Terminal 0.1 Ω	1771
51136C	Standard Resistor, Four-Terminal 1 Ω	1771
51137C	Standard Resistor, Four-Terminal 10 Ω	1771
51138C	Standard Resistor, Four-Terminal 100 Ω	1771
51139C	Standard Resistor, Four-Terminal 1 k Ω	1771
51140C	Standard Resistor, 10 k Ω	2349
51141C	Standard Resistor, 100 k Ω	2349
51142C	Standard Resistor, 1 M Ω	2644

51143C	Standard Resistor, 10 MΩ	3193
51144C	Additional Voltage, 10 MΩ	2661
51145C	Standard Resistor, 100 MΩ	3217
51146C	Additional Voltage, 100 MΩ	2661
51147C	Standard Resistor, 1 GΩ	3217
51148C	Additional Voltage, 1 GΩ	2661
51149C	Standard Resistor, 10 GΩ	4062
51150C	Additional Voltage, 10 GΩ	3501
51151C	Standard Resistor, 100 GΩ	4053
51152C	Additional Voltage, 100 GΩ	3492
51153C	Standard Resistor, 1 TΩ	4264
51154C	Additional Voltage, 1 TΩ	3691
51160C	Standard Resistor for Current Measurements (Shunts) with all determinations at 300 A or Below, One Range, One Current Level	3841
51161C	Standard Resistor for Current Measurements (Shunts), with At Least One Determination Above 300 A (maximum current 2000 A), One Range, One Current Level	5534
51162C	Standard Resistor for Current Measurements (Shunts), Additional Range of a Multi-Range Resistor	2351
51163C	Standard Resistor for Current Measurements (Shunts), Additional Determination at Another Current Level	2351

Fees are subject to change without notice.

A.2 High-Voltage Standard Resistors

Technical Contacts:

Gerald J. FitzPatrick

Telephone:

(301) 975-8922

Email:

gfitzpatrick@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
51210C	High-Voltage Standard Resistors	At Cost

B. Impedance Measurements (Except Resistors)

B.1 Low-Frequency Capacitance and Inductance Measurements and Standards

Technical Contacts:

Andrew D. Koffman

Telephone:

(301) 975-4518

Email:

akoffman@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8170

Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
52100S	Special Four Terminal-Pair (4TP) Capacitance and Dissipation Factor Characterization	At Cost
52110S	Special LF Capacitance Measurements, by Prearrangements	At Cost
52120S	Special Measurement Assurance Program for Standard Capacitors (100 pF and 1000 pF, at a Frequency of 1000 Hz)	At Cost
52130C	Fixed, Fused-Silica Dielectric Standard Capacitors (1, 10, and 100) pF, at a Frequency of (100, 400, or 1000) Hz	3983
52131C	Additional Measurement at One of the Above Frequencies	402
52140C	Fixed Three-Terminal, High-Precision Nitrogen Dielectric Standard Capacitors with Coaxial Connectors, Small Uncertainty, (10, 100 and 1000) pF, at a Frequency of (100, 400, or 1000) Hz	2537
52141C	Additional Measurement at One of the Above Frequencies	386
52150C	Physical Tests for Three-Terminal Standard Capacitors with Coaxial Connectors, Large Uncertainty (0.001 pF to 10 000 pF) at a Frequency of (100, 400, or 1000) Hz	2474
52160C	Fixed Three-Terminal Standard Capacitors with Coaxial Connectors, Large Uncertainty (0.001 pF to 10 000 pF) at a Frequency of (100, 400, or 1000) Hz	1671
52161C	Additional Measurement at One of the Above Frequencies	386
52170C	Two- or Three- Terminal Mica Dielectric Standard Capacitors with Binding Post Connectors (0.001 μ F to 1 μ F), at a Frequency of (66, 100, 400, 1000 or 10 000) Hz	1655
52171C	Additional Measurement at One of the Above Frequencies	1542
52176C	Two-Terminal Standard Capacitors with Precision High Frequency (HF) Coaxial Connectors (0.001 pF to 10 000 pF), at a Frequency of 1000 Hz	At Cost
52180C	Fixed Standard Inductors (0.00005 H to 10 H), at a Frequency of (100, 400, 1000, or 10 000) Hz	1655
52181C	Additional Measurement at One of the Above Frequencies	1574
52190S	Special LF Inductance Measurements, by Prearrangement	At Cost

Fees are subject to change without notice.

B.2 Power-Frequency Capacitors

Technical Contacts:

Gerald J. FitzPatrick

Telephone:

(301) 975-8922

Email:

gfitzpatrick@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
52400C	Power-Frequency Capacitors	At Cost

C. Voltage Measurements

C.1 DC Voltage Measurements and Standards

Technical Contacts:

June E. Sims

Yi-Hua Tang

Telephone:

(301) 975-4238

(301) 975-4691

Email:

june.sims@nist.gov

ytang@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
53110S	Special DC Voltage Measurements, by Prearrangement	At Cost
53130C	First Saturated Standard Cell in a Group	5600
53131C	Each Additional Cell	3757
53140C	Platinum Resistance Thermometer Temperature Determination for Standard Cell Calibration	1300
53150C	Unsaturated Standard Cells	3143
53160C	Tests of Solid-State Voltage Reference Standard (1 Output, 1 V to 10 V)	2474
53161C	Each Additional Output	1580
53180S	Special Handling (Equipment Pickup or Delivery)	291
53190S	Special Handling (Cleaning, Minor Repair, Return Service Charge)	586

Fees are subject to change without notice.

C.2 AC Voltage Measurements

Technical Contacts:

Bryan C. Waltrip

Telephone:

(301) 975-2438

Email:

bwaltrip@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
53200S	Special Tests of High-Accuracy Digital Multimeters, Multifunction Calibrators, by Prearrangement	At Cost
53201S	Special Tests of Low-Voltage AC-DC Transfer Standards, by Prearrangement	At Cost
53202S	Special 25-Point Test of Digital Multimeters (DMMs), by Prearrangement	4352
53203S	Each Additional DMM Test Point for 53202S	At Cost

Fees are subject to change without notice.

C.3 AC-DC Thermal Voltage and Current Converters (to 1 MHz)

Technical Contacts:

Joseph R. Kinard

Thomas E. Lipe

Telephone:

(301) 975-4250

(301) 975-4251

Email:

jkinard@nist.gov

tlipe@nist.gov

Mailing Address:

NIST
Building 220, Room B146
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
53310S	Special AC-DC Measurement Services, by Prearrangement	At Cost
53350C	Set-up Charge (No Test Points Included) for a Standard or Standards Set for AC-DC Difference (Voltage or Current)	2854
53351C	First Point for Each Applied Voltage or Current	1172
53352C	Additional Points for Each Applied Voltage and Current Level (Additional Frequency/Voltage or Frequency/Current Points)	83

Fees are subject to change without notice.

D. Precision Ratio Measurements

D.1 Inductive Dividers

Technical Contact:

Scott Shields

Telephone:

(301) 975-4232

Email:

scott.shields@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54110S	Special Ratio Measurements and Tests of Inductive Voltage Dividers, by Prearrangement	At Cost
54120C	Inductive Voltage Dividers – (Single Frequency, Voltage to be Specified, Each Setting of 3 Most Significant Dials)	5544
54121C	Additional Frequency Points	5544
54130C	Inductive Voltage Dividers – (Single Frequency, Voltage to be Specified, Each Setting of Most Significant Dial Only)	3483
54131C	Additional Frequency Points	3483

Fees are subject to change without notice.

D.2 Resistive Dividers

Technical Contacts:

Gerald J. FitzPatrick

Telephone:

(301) 975-8922

Email:

gfitzpatrick@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54210C	Resistor and Resistive Dividers, Total Resistance or Voltage Ratio, Two Direct Voltage Levels Between 10 kV and 150 kV	4055
54211S	Special Tests of Resistor and Resistive Dividers at Direct Voltage Levels, by Prearrangement	At Cost
54213S	Special Tests of Resistor and Resistive Dividers at 60 Hz, by Prearrangement	At Cost

Fees are subject to change without notice.

D.3 Capacitive Dividers

Technical Contacts:

Gerald J. FitzPatrick

Telephone:

(301) 975-8922

Email:

gfitzpatrick@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8170

Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54310S	Special Test of Capacitive Dividers at 60 Hz, by Prearrangement	At Cost

D.4 Voltage and Current Transformers

Technical Contacts:

Gerald J. FitzPatrick

Thomas L. Nelson

Telephone:

(301) 975-8922

(301) 975-2986

Email:

gfitzpatrick@nist.gov

tnelson@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8170

Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54510C	Voltage Transformer, Ratio & Phase Angle, at 60 Hz on 1 Range, 1 Secondary Voltage, 1 Burden Primary Vrms $\leq$ 150 kV	At Cost
54520C	Current Transformer, Ratio & Phase Angle, 1 Range at 1 Frequency, 1 Burden, Secondary Currents (0.5, 1, 2, 3, 4, 5) A, Primary Current Not Over 12 000 A	5060
54521C	Current Transformer, Ratio & Phase Angle, 1 Secondary Current, Additional Combination of Range, Frequency, and Burden, Primary Current Not Over 12 000 A	483
54522C	Current Transformer, Ratio & Phase at Each Additional Secondary Current, Same Combination of Range, Frequency, and Burden as 54520C or 54521C	386
54600S	Special Tests of Dividers and Transformers, by Prearrangement	At Cost

Fees are subject to change without notice.

E. Phase Meters and Standards and VOR Measurements

Technical Contacts:

Bryan C. Waltrip

Telephone:

(301) 975-2438

Email:

bwaltrip@nist.gov

Mailing Address:

NIST

100 Bureau Drive, Stop 8170

Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
55110S	Special Tests of Phase Standards and Related Instruments, by Prearrangement	At Cost
55120C	Phase Meters – One Combination of Input Voltages (0.5 V to 120 V) at One Frequency (2 Hz to 100 kHz) – the Input Voltage Ratio Shall Not Exceed 10	2939
55121C	Phase Meters – Each Additional Combination of Input Voltages (0.5 V to 120 V) at the Same or at a Different Frequency (2 Hz to 100 kHz) – the Input Voltage Ratio Shall Not Exceed 10	947
55130C	Phase Meters – One Additional Combination of One Input Voltage (0.5 V to 120 V) and One Input Current (1 A to 5 A) at One Frequency (2 Hz to 4 kHz)	3951
55131C	Phase Meters – Each Additional Combination of One Input Voltage (0.5 V to 120 V) and One Input Current (0.5 A to 5 A)	1076
55140C	Phase Meters – One Input Voltage (120 V to 240 V) and Another Input Voltage (120 V to 240 V) at One Frequency (2 Hz to 5 kHz)	3951
55141C	Phase Meters – Each Additional Combination of One Input Voltage (120 V to 240 V) and Another Input Voltage (120 V to 240 V) at the Same or at a Different Frequency (2 Hz to 5 kHz)	1076

Fees are subject to change without notice.

F. Power and Energy Measurements, Low-Frequency

Technical Contacts:

Thomas L. Nelson
Gerald J. FitzPatrick

Telephone:

(301) 975-2986
(301) 975-8922

Email:

tnelson@nist.gov
gfitzpatrick@nist.gov

Mailing Address:

NIST
100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
56110S	Special Test of AC-DC Wattmeters, by Prearrangement	At Cost
56200C	Watt, Watthour, Var, Varhour Meter, Initial Two Determinations of Same Meter at 60 Hz	4671
56201C	Each Additional Determination, Same Meter at 50 Hz	282
56202C	Initial Two Determinations of One or Two Meters Run Simultaneously with the First (56200C)	4271
56210M	Measurement Assurance Program for Watthour Meters	6091
56220S	Special Tests of Watthour Meter with Pulse Output; 120 Volts, 5 Amperes, 60 Hz at 0.5 Lag, Unity and 0.5 Lead Power Factors	1981
56230S	Special Test of Phasor Measurement Units, PMUs	At Cost

Fees are subject to change without notice.

G. RF, Microwave and Millimeter-Wave Measurements

G.1 Thermistor Detectors

Technical Contacts:

Ronald A. Ginley
Thomas P. Crowley

Telephone:

(303) 497-3634
(303) 497-4133

Email:

rginley@boulder.nist.gov
crowley@boulder.nist.gov

Mailing Address:

NIST
325 Broadway, MC 818.01
Boulder, CO 80305-3328

Administrative and Logistics:

Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov
Fax: (303) 497-3970

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
The following tests are for 50 Ω thermistor and thermoelectric detectors with coaxial connectors.		
61100S	Measurement setup charge (applies to all coaxial power measurements—one setup charge for multiple detectors with the same connectors and frequencies ¹)	3051
61110S	Coaxial Detectors in the Frequency Range from 0.1 MHz to 10 MHz	3573
61120S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type ² . Up to 20 Frequency Points	3878
61121S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type ² . From 20 to 40 Frequency Points	4235
61122S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type ² . From 40 to 120 Frequency Points	4593
61123S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type ² . More than 120 Frequency Points	5309
61137C	NIST Model CN Coaxial Detectors at 21 Frequencies within the Frequency Range of 50 MHz to 18 GHz	9076
61138C	NIST Model CN Coaxial Detectors at Single Customer Selected Frequency within the Frequency Range of 50 MHz to 18 GHz	57
The following tests are for thermistor detectors with waveguide flanges.		
61140S	Measurement setup charge (applies to all waveguide power measurements EXCEPT WR15—one charge for multiple detectors with the same connectors and frequencies ¹)	5914
61141S	Measurement setup charge (applies to all WR15 waveguide power measurements—one charge for multiple detectors with the same connectors and frequencies ¹)	4576
61142S	Rectangular Waveguide Detectors with WR90 Flanges ²	3727
61143S	Rectangular Waveguide Detectors with WR62 Flanges ²	3727
61144S	Rectangular Waveguide Detectors with WR42 Flanges ²	3727
61145S	Rectangular Waveguide Detectors with WR28 Flanges ²	4261

61146S	Rectangular Waveguide Detectors with WR22 Flanges ²	4767
61147S	Rectangular Waveguide Detectors with WR15 Flanges ²	7304
61148S	Rectangular Waveguide Detectors with WR10 Flanges ²	7304
Miscellaneous Tests		
61190S	Special Microwave and RF Power Measurement Services, by Prearrangement	At Cost

Fees are subject to change without notice.

¹ Only one setup charge is necessary for multiple detectors sent in at the same time with the same connector type and measurement frequencies.

² Measurement Frequencies

G.2 Scattering Parameters of Passive One and Two-Port Devices

Technical Contacts:

Ronald A. Ginley

Telephone:

(303) 497-3634

Email:

rginley@boulder.nist.gov

Mailing Address:

NIST
325 Broadway, MC 818.01
Boulder, CO 80305-3328

Administrative and Logistics:

Puanani L. DeLara

(303) 497-3753

calibration@boulder.nist.gov

Fax: (303) 497-3970

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
61290S	Special Microwave and RF Scattering-Parameter Measurement Services, by Prearrangement	At Cost

Fees are subject to change without notice.

G.3 Thermal Noise Measurements

Technical Contacts:

David Walker
James Randa

Telephone:

(303) 497-5490
(303) 497-3150

Email:

dwalker@boulder.nist.gov
randa@boulder.nist.gov

Mailing Address:

NIST
325 Broadway, MC 818.01
Boulder, CO 80305-3328

Administrative and Logistics:

Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov
Fax: (303) 497-3970

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Freq.	Connector Type	Device Requirements/Service	Fee (\$)
61410S	30 MHz 60 MHz	Coaxial N Precision (PIN) GPC 3.5 (PIN) GPC 7 14 mm	Temperature < 15 000 K (ENR < 17 dB) VSWR < 1.2	
				Set Up Charge, per order 3760
				Per Frequency 6183
61420S	1.0 GHz to 12.4 GHz Continuous Frequencies	Coaxial 14 mm (1 to 4 GHz) GPC 7 N Precision (PIN) GPC 3.5 (PIN) GPC 2.4 (PIN) (8 GHz to 12.4 GHz)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
				Set Up Charge, per order 6294
				Per Frequency 773
61425S	12.4 GHz to 18.0 GHz Continuous Frequencies	Coaxial GPC 7 N Precision (PIN) GPC 3.5 (PIN) GPC 2.4 (PIN)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
				Set Up Charge, per order 8577
				Per Frequency 4969
61430S	18.0 GHz to 26 GHz Continuous Frequencies	Coaxial GPC 3.5 (PIN) GPC 2.4 (PIN)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
				Set Up Charge, per order 8375
				Per Frequency 4804

61435S	26.5 GHz to 40 GHz Continuous Frequencies	Coaxial GPC 2.4 (PIN)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			12518
	Per Frequency			6572
61450S	8.2 GHz to 12.4 GHz Continuous Frequencies	Waveguide WR 90	Temperature <15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			7103
	Per Frequency			773
61455S	12.4 GHz to 18.0 GHz Continuous Frequencies	Waveguide WR 62	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			8577
	Per Frequency			4710
61460S	18.0 GHz to 26.0 GHz Continuous Frequencies	Waveguide WR 42	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			8577
	Per Frequency			4710
61465S	26.5 GHz to 40.0 GHz Continuous Frequencies	Waveguide WR 28	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			9386
	Per Frequency			4710
61470S	33.0 GHz to 50.0 GHz Continuous Frequencies	Waveguide WR 22	Temperature <15 000 K (ENR < 17 dB) Reflection Coefficient <0.2	
	Set Up Charge, per order			8577
	Per Frequency			4710
61475S	50.0 GHz to 65.0 GHz Continuous Frequencies	Waveguide WR 15	Temperature < 15 000 K (ENR , 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			11579
	Per Frequency			7600
61495S	Special Noise Temperature Measurements, by Prearrangement			At Cost

Fees are subject to change without notice.

H. Electromagnetic Field Strength and Antenna Measurements

H.1 Microwave Antenna Parameter Measurements

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Perry F. Wilson (63100S–63400S)	(303) 497-3406	pfw@boulder.nist.gov	NIST 325 Broadway, MC 818.02 Boulder, CO 80305-3328
Jeff Guerrieri (63100S)	(303) 497-3863	jeff.guerrieri@nist.gov	
Michael H. Francis (63200S)	(303) 497-5873	mfrancis@boulder.nist.gov	

Administrative and Logistics:
Puanani L. Delara (303) 497-3753 calibration@boulder.nist.gov
Fax: (303) 497-3970

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
63100S	Gain and Polarization Calibrations of Standard Antennas Using Extrapolation Range	At Cost
63200S	Measurement of Pattern, Gain, and Polarization of Arbitrary Antennas Using Near-Field Scanning Techniques	At Cost
63400S	Special Consulting, Advisory, and Other Services	At Cost

H.2 Field Strength Parameter Measurements

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Dennis G. Camell	(303) 497-3214	camell@boulder.nist.gov	NIST
Perry F. Wilson	(303) 497-3406	pfw@boulder.nist.gov	325 Broadway, MC 818.02 Boulder, CO 80305-3328

Administrative and Logistics:
Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov
Fax: (303) 497-3970

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
64100S	Special Test Services for Antenna/Field Strength/Masurement, Using the Transverse Electromagnetic (TEM) Cell Method (10 kHz to 300 MHz)	At Cost
64300S	Special Test Services for Antenna/Field Strength/Reflectivity Measurements, Utilizing the Anechoic Chamber and Standard Field Method	At Cost

I. Pulse Waveform Measurements

Technical Contacts:

Paul Hale
(65100S, 65200S, 65400S)

Telephone:

(303) 497-5367

Email:

hale@boulder.nist.gov

Mailing Address:

NIST
325 Broadway, MC 815.01
Boulder, CO 80305-3328

David I. Bergman

(301) 975-4464

dbergman@nist.gov

(65250S, 65500S, 65501S)

NIST

100 Bureau Drive, Stop 8170
Gaithersburg, MD 20899-8170

Administrative and Logistics (65100S, 65200S and 65400S):

John Lomax

(303) 497-3842

john.lomax@nist.gov

Fax:

(303) 497-4286

Administrative and Logistics (65250S, 65500S and 65501S):

Denise D. Prather

(301) 975-4221

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
65100S	Impulse Spectrum Amplitude (50 Ω)	At Cost
65200S	Fast Repetitive Pulse Transition Parameters (50 Ω)	At Cost
65250S	Repetitive Pulse Waveform Measurements, Including Settling Parameters	At Cost
65400S	Pulse Time Delay Interval	At Cost
65500S	Peak-to-Peak Detector Calibration at One Frequency Selected from Those Given in Table 9.23 at 1.2 V	At Cost
65501S	Additional Frequency for Peak-to-Peak Detector in 65500S	At Cost

CHAPTER 10

TIME AND FREQUENCY MEASUREMENTS

A. Broadcast and Measurement Services

<u>Technical Contacts:</u>	<u>Telephone:</u>	<u>Email:</u>	<u>Mailing Address:</u>
Michael A. Lombardi (Frequency)	(303) 497-3212	lombardi@boulder.nist.gov	NIST
Marc A. Weiss (Time)	(303) 497-3261	mweiss@boulder.nist.gov	325 Broadway, MC 847.40
John Lowe	(303) 497-5453	lowe@boulder.nist.gov	Boulder, CO 80305-3328
Stefania Romisch	(303) 497-3446	stefania.romisch@nist.gov	

Administrative and Logistics:

Trudi Peppler	(303) 497-3338	tpeppler@boulder.nist.gov
Fax:	(303) 497-6461	

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
Broadcast Services (WWW, WWVH, WWVB, GOES, ACTS, and NTS)		
76100C	Frequency Measurement and Analysis Service (FMAS), Frequency Delivered to User's Site	Initial One-Time Fee: 1500 Monthly Charge: 500
76101C	Time Measurement and Analysis Service (TMAS)	Initial One-Time Fee: 1500 Monthly Charge: 750
76110S	Global Time Service, Frequency and Time delivered to User's Site	15000 per year
76120S	Characterization of Global Positioning System (GPS) Satellite Receivers	At Cost

B. Calibration and Characterization of Oscillators and Amplifiers

Technical Contacts:

David Howe
Stefania Romisch

Telephone:

(303) 497-3277
(303) 497-3446

Email:

dhowe@boulder.nist.gov
stefania.romisch@nist.gov

Mailing Address:

NIST
325 Broadway, MC 847
Boulder, CO 80305-3328

Administrative and Logistics:

Trudi Peppler (303) 497-3338 tpeppler@boulder.nist.gov
Fax: (303) 497-6461

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
77100C	Oscillator Frequency Calibration	At Cost
77110C	Characterization of Atomic Frequency Standards	At Cost
77120C	Characterization of Oscillators: Time Domain	At Cost
77130C	Characterization of Oscillators and Amplifiers: Phase Noise in the Frequency Domain	At Cost
77131C	Characterization of Oscillators and Amplifiers: Amplitude Noise in the Frequency Domain	At Cost

C. Test of PM/AM Noise Measurement Systems

Technical Contact:

David Howe

Telephone:

(303) 497-3277

Email:

dhowe@boulder.nist.gov

Mailing Address:

NIST
325 Broadway, MC 847.30
Boulder, CO 80305-3328

Administrative and Logistics:

Trudi Peppler (303) 497-3338 tpeppler@boulder.nist.gov
Fax: (303) 497-6461

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
77135C	Tests of RF PM/AM Noise Measurement Systems: On-Site Tests	At Cost
77136C	Tests of Microwave PM/AM Noise Measurement Systems: On-Site Tests	At Cost
77140S	Special Time/Frequency Measurements: Oscillators and Other Components	At Cost

CHAPTER 11

SEMINARS

The following announcements concern notification of changes in services and information about future NIST Measurement Seminars. General policy questions regarding NIST measurement services should be referred to the Calibration Program.

NIST MEASUREMENT SEMINARS

NIST holds seminars and workshops that provide advice and assistance on measurements and calibrations. This affords laboratories outside NIST an opportunity to learn how to make measurements consistent with national standards which NIST maintains. Participation is open to a limited number of people who have the appropriate education, work experience, and current profession in measurement and standards laboratory activities.

Each seminar lasts from one to five days and is devoted to lectures, group discussions, and laboratory demonstrations. A course may be cancelled if registration is insufficient. However, in the past, requests for enrollment have nearly always exceeded the numbers that could be accommodated.

Acceptance letters will be mailed no later than 4 weeks prior to the scheduled date of the course. Detailed information on schedules and housing will be included. Those accepted will be expected to study the assigned reading material before coming to the course and should be prepared to discuss their own experiences with related problems.

See the Weights and Measures Program web site www.nist.gov/pml/wmd/index.cfm for the National Conference on Weights and Measures (NCWM) Calendar of Events for other training not listed here.

NIST offers conferences and workshops throughout the year. To see the latest listing go to www.nist.gov for upcoming NIST Conferences and Events.

ALPHABETICAL CROSS-INDEX

Item

Service ID Numbers

A

Absolute pressure transducers	30010C-30011C
Accelerometers	24010C-24060S
Ac-dc thermal converters (to 1MHz).....	53350C-53352C
Ac-dc watt-hour or var-hour meters.....	56110S-56210M
Ac voltage, high accuracy	53200S-53203S
Acoustic devices	25060S
Acoustic measurements	25010C-25070S
Activation detector dosimetry	44070C-44090C
Air navigation aids	55210S-55230S
Air-speed indicators.....	19010C-19040S
Alpha-particle-emitting solid sources.....	43030C-43050C
American Petroleum Institute gages.....	12010C
Anechoic chambers	25010C-25070S
Anemometers.....	19010C-19040S
Angle gage blocks	14010C
Angular measurements	14010C-14050S
Antenna parameter measurements, microwave	63100S-63400S
Attenuators, rf and microwave	61290S
Audio-frequency phase meter.....	55120C-55141C

B

Ball plates	11050S
Balls.....	11030S
Barometers.....	29035C, 30010C-30011C
Bell provers	18010C
Beta-particle applications	47030C-47040S
Beta-particle emitting sources	43060S, 43070S,
.....	47030C-47040S
Blackbody sources.....	35090S
Bolometer units, rf and microwave	61110S-61138S

C

Capacitance and inductance measurements, low frequency	52100S-52181C
Capacitive voltage dividers	54310S
Capacitors, dielectric	52130C
Capacitors, low frequency	52110S-52171C
Capacitors, power frequency	52400C
Coaxial thermistor detectors.....	61110S-61153S
Color measuring instruments.....	37120S
Color temperature.....	37010C-37050S
Complex dimensional standards.....	12010C-12040S
Coordinate measuring machines.....	11050S, 12040S,
.....	15010C-15040C
-software algorithms	10070S-10082S
-socketed ball bars	SRMs (p. 5)

-probe performance spheres.....	SRMs (p. 5)
Cryogenic flow measurements	18800S
Cryogenic resistance thermometers.....	33355S
Current and voltage transformers	54510C-54600S

D

Dc resistance measurements	51100S-51163C
Dc voltage measurements	53110S-53190S
Deadweight piston gages	29010C
Density measurements, liquids	17040S
Detector standards, windowed photodiode.....	40560C-40561C
Detector standards, windowless photodiode.....	40510C
Detectors, IR.....	39080S
Detectors, near ultraviolet to soft x-ray region.....	40599S
Detectors, radiometric	39080S
Detectors, spectroradiometric	39071C-39090S
Detectors, used with lasers	42110C-42180S
Deuterium lamps	39050C
Dew-point hygrometer.....	36010C-36020C
Diameter measurements	11010S-11060S
Differential pressure transducers	30020C-30021C
Digital multimeters, low frequency	53200S-53203S
Dimensional metrology	10010C-14050S
Dividers, inductive	54110S-54131C
Dividers, resistive	54210C-54213S
Dosimeters, electron beam	48010M-48020S
Dosimeters, high dose	49010C-49050S
Dosimeters, neutron.....	44100S
Dosimeters, radiochromic.....	49010C-49032C
Dosimeters, x-ray, gamma-ray, and electron.....	46010C-48020S
Dosimetry, neutron	44010C-44100S

E

Earphones	25070S
Electromagnetic field-strength parameter measurements.....	64100S-64300S
Electrometers.....	46030S
Electron beam dosimetry	48010M-48020S
End standards	10050S
Energy and power measurements, low frequency	56110S-56210M

F

Ferrous-ferric dosimeters.....	48010M-48011M
Fiber optic power meters	42130C-42180S
Field strength measurements, electromagnetic.....	64100S-64300S
Filament lamps, ribbon.....	35050C-35060C,
.....	39010C-39030C
Filters, spectral transmittance	38010C-38040C
Fixed-point devices, thermometric	33360S
Flashing-light photometer	37110S
Flats, optical reference.....	13010S
Flow measurements, cryogenic	18800S
Flowrate meters, liquid and gas.....	18010C-18070S
Flux standards, luminous	37060S
Force transducers.....	23010C-23260S
Frequency and time measurement services	76100C-76110S
Frequency domain	77131C

G

Gage blocks	10010C
Gages, API.....	12010C
Gages, ionization	30034C-30038C
Gages, low pressure.....	30040S
Gages, molecular drag	30029C-30031C
Gages, piston	29010C-29020C
Gages, plug.....	11010S
Gages, plug and ring.....	12020S
Gages, pressure.....	29010C-29040S
Gages, ring.....	11040S
Gages, step.....	11060S
Gages, two dimensional.....	12030S
Gages, vacuum	30010C-30050S
Gamma-ray dosimeters.....	46010C-46021C
Gamma-ray emitting sources.....	43010C-43020C,
.....	47010C-47011C
Gas flowmeters.....	18010C, 18050S
Gear measuring wires	11020C
Germanium resistance thermometers	33142C
Global time service.....	76110S
Global positioning system satellite receivers.....	76120S
Grid plates	11050S

H

Heat flux sensors	35100S-35102C
Helium permeation leaks	30060S-30062S
High dose dosimetry.....	49010C-49050S
High-vacuum gages.....	30029C-30038C
High-voltage resistors.....	51210C
Humidity measurements	36010C-36070S
Hydrocarbon liquid flow meters.....	18030C, 18070S
Hydrometers	16010C-16020S
Hygrometers	36010C-36070S

I

Illuminance meters	37090S
Impedance measurements.....	52110S
Impulse spectrum amplitude.....	65100S
Impulse response of coaxial networks.....	65300S
Incandescent lamps.....	37060S
Indexing tables	14030S
Inductance and capacitance measurements, low frequency.....	52110S-52181C
Inductive voltage dividers	54110S-54131C
Industrial grade thermometers	31010C-37020S
Intensity, luminous	37010C-37020S
Interferometry.....	10010C
Internal diameter standards.....	11040S
Ionization chambers.....	47036C
Ionization gages.....	30034C-30038C
Irradiance detectors	39100S
Irradiance sources.....	39040C-39050C

L

Laboratory thermometers	31010C-31150S
Lamps, deuterium arc	39050C
Lamps, incandescent.....	37060S
Lamps, quartz halogen.....	39040C-39045C
Lamps, ribbon filament	35050C-35060C
.....	39010C-39030C
Laser frequency/wavelength.....	14510S
Laser power and energy measurements	42110C-42180S
Leak artifacts	30060S-30062S
Length and diameter	11050S
Length measurements.....	10010C-10060S
Length standards.....	10050S
Light emitting diodes (LEDs).....	37130S
Line standards.....	10020C
Linearity of optical fiber power meters	42166C-42167S
Liquid flow meters	18020C, 18060S
Load cells	23010C-23260S
Luminous flux	37060S
Luminous intensity	37010C-37020S
Luminous intensity of LEDs.....	37130S

M

Mammography x-ray measuring instruments	46010C-46050S
Manometers	29035C
Mass measurements.....	22010C-22170S

MEASUREMENT ASSURANCE PROGRAMS (MAPs)

Dc resistance.....	51110M
Dose interpretation of ferrous-ferric dosimeters.....	48010M-48011M
Laser power and energy.....	42120M, 42140M, 42150M
Platinum resistance thermometry	33370M-33380M
Watthour meters	56210M
Meteorological airspeed instrumentation	19030S
Meters, laser power and energy	42110C, 42170S

Meters, optical fiber power.....	42130C, 42140M, 42190S
Meters, phase.....	55110S-55141C
Microphones, pressure and free-field response	25010C-25050C
Micropotentiometers, low voltage	53201S
Micropotentiometers, rf.....	53350S-53352S
Microwave antenna parameter measurements	63100S-63400S
Molecular drag gages	30029C-30031C

N

Neutron dosimeters.....	44100S
Neutron sources	44010C-44020C
Noise temperature measurements, coaxial and waveguide.....	61410S-61495S
Non-mercurial barometers and manometers.....	29035C

O

Oil gaging and surveying tapes	10030C
Opal glass luminance standards.....	37070C
Optical fiber power meters	42130C, 42140M, 42180S
Optical flats	13010S
Optical polygons.....	14020S
Optical pyrometers	35010C-35040C
Optical reference planes	13010S
Optoelectronic Frequency Response	42155C
Organic-liquid-in-glass thermometers	31010C-31150S
Oscillator characterization.....	77100C-77140S
Ozone	37510C-37535S

P

Penetrameters, x-ray	46040S
Personnel protection instrumentation	44060C
Phase measurements.....	55110S-55141C
Phasor measure units PMU	56230S
Photodiode, spectral response.....	39070C
Photodiode, ultraviolet to near-infrared.....	39077C
Photodiodes, windowed and windowless	40510C-40560C
Photographic step tablets	38120C-38130C
Photometers	37090S, 37250C
Photometric tests	37100S
Photometry	37010C-37110S
Photon Beams.....	49010C-49050S
Pickup sensitivity	24010C-24030C, 24050C
Piston gages, controlled clearance.....	29020C
Piston gages, dead weight.....	29010C
Piston gauges versus UIM	30025C
Pitot-static tubes	19010C
Platinum resistance thermometers	33010C-33310C
Plug and ring gages	12010C-12020C
Plug gages.....	11010S
PM/AM noise measurement systems	77135C-77136S
Pneumatic bridge hygrometers	36060C
Polygons, optical	14020S
Power and energy measurements, low frequency.....	56110S-56210M
Power meters, optical fiber.....	42130C-42140M, 42180S

Power meters, thermoelectric	61110S-61155S
Pressure gages and transducers.....	29030C
Pressure gages, low absolute	30010C-30011C
Pressure gages, low differential.....	30020C-30021C
Pressure gages, special tests	29040S
Pressure measurements.....	29010C-29040S,
.....	30010C-30062C
Proving rings	23010C-23260S
Pulse waveform measurements	65100S-65400S
Pyrometer indicators.....	32100C
Pyrometers, optical	35010C-35040C
Pyrometers, radiation.....	35070S-35072C

Q

Quartz halogen lamps.....	39040C-39045C
---------------------------	---------------

R

Radiance standard sources.....	39010C-39030C
Radiance thermometry.....	35010C-35084C
Radiant energy detectors	39070C
Radiation detectors	46010C-46011C
Radiation pyrometers.....	35070S
Radiation thermometry.....	35010C-35084C
Radioactive sources, alpha emitting	43030C-43050C, 43090S
Radioactive sources, beta emitting	43060S-43070S
Radioactive sources, gamma emitting	43010C-43020C
Radioactive sources, neutron emitting.....	44010C-44020C
Radiochrometric dosimeters	49020C-49030C
Radiometric detectors.....	39080S
Radiometric measurements.....	39010C-39080S,
.....	40510C-40599S
Radiometric sources	39060S
Radionuclides	43010S-43090S
Resistance measurements, dc	51100S-51163C
Resistance thermometers	33010C-33310C
Resistive voltage dividers.....	54210C-54213S
Resistors, high-precision standard, dc	51130C-51154C
Resistors, high voltage.....	51210C
Resistors, megohm	51142C-51154C
Resistors for current measurements.....	51160C-51163C
Ring gages.....	11040S
R-meters	46010C-46011C
Rods, surveying leveling	10040S
Rotary and indexing tables	14030S
Roughness calibration standards	15010C-15040S
Roundness measurements.....	13020S-13030S

S

Saturated standard cells	53130C-53131C
Shock measurements	24040S
Sieves, special tests	10060S also SRMs (p. 5)
Spectral irradiance	39040C-39050C,
Spectral irradiance, lamps	39040C-39050C
Spectral radiance	39010C-39030C
Spectral radiance, lamps	39010C-39030C
Spectral reflectance	38060S
Spectral response, lasers	42164C
Spectral response, photodiode	39081S
Spectral transmittance filters	38010C-38040C, 38061S
.....	Also SRMs (p. 5)
Spectroradiometric detectors	39071C-39090S
Spectroradiometric sources	39010C-39060S
Specular gloss	38090S
Spherical diameter standards, balls	11030S
SRM 1001	38100C-38110C
SRM 1008	38120C-38130C
Stage micrometer	10020C
Standard Reference Photometer	37520C-37535S
Standard voltage cells	53130C-53150C
Step gages, length	11060S
Step height measurements, surface	15030C
Step tablet density, photographic	38120C-38130C
Sucker rods	12010C
Surface color	38091S
Surface roughness standards	15040S
Surveying and oil gaging tapes	10030C
Surveying leveling rods	10040S

T

Tapes	10030C
Thermal voltage converters (to 1 MHz)	53350C-53352C
Thermal resistance	36110C-36140S
Thermistor mounts	61110S-61155S
Thermocouples and thermocouple materials	32010C-32150S
Thermometers, cryogenic type	33140C-33141C
Thermometers, germanium resistance	33142C
Thermometers, laboratory	31010C-31260S
Thermometers, platinum resistance	33010C-33310C
Thermometer, rhodium-iron resistance	33140C-33141C
Thermometric fixed-point devices	33360S also SRMs (p. 5)
Thermometry, radiance	35010C-35070S
Thread measuring wires	11020C
Threaded plug and ring gages	12020S
Time and frequency measurement services	76100C-76120C
Topography	15040S
Transducer sensitivity	24010C-24030C, 24050C
Transducers, low pressure	30010C-30021C
Transformers, voltage and current	54510C-54600S
Transmittance filters, spectral	38010C-38040C
Transmitting diffusers	37080S
Tungsten lamps	39010C-39046C

Tungsten strip lamps.....	35050C-35061C
Two-dimensional gages.....	12030S

U

Ultraviolet detectors	40510C-406001S
Unsaturated standard cells.....	53150C

V

Vacuum gages	30029C-30038C, 30050S
Vacuum measurements.....	30010C-30050S
Var, varhour meters.....	56200C-56202C
Very-high-frequency omnidirectional measurements.....	55210C-55230S
Vibration and shock measurements.....	24010C-24060S
Voltage, ac.....	53201S
Voltage, dc.....	53110S-53190S
Voltage, rf dc.....	53350S-53352S
Voltage and current transformers	54510C-54600S
Voltage dividers, capacitive	54310S
Voltage dividers, inductive.....	54110S-54131C
Voltage dividers, resistive	54210C-54213S
Voltage reference standards, solid state.....	53160C-53161C
Voltmeters, high accuracy, ac.....	53200S
Volume standards	17010C-17040S
VOR measurements.....	55110S

W

Water flow meters	18020C, 18060S
Watt, watthour meters	56110S-56210M
Wattmeters, high power.....	61160S, 61190S
Wattmeters, high power.....	61160S, 61190S
Waveform measurements, pulse.....	65100S-65400S
Waveguide thermistor detectors	61144S-61155S
Wedges	14040S
Weights (mass standards)	22010C-22170S
Wires for thread and gear measurements.....	11020C

X

X-ray and photographic step tablets	38100C-38130C
X-ray dosimeters	46010C-46050S
X-ray penetrameters	46040S