# NIST Calibration Program Calibration Services Users Guide SP 250 Appendix Fee Schedule – January 13, 2017

## **Calibration Services:**

Dimensional Mechanical Thermodynamic Optical Radiation Ionizing Radiation Electromagnetic Time and Frequency

### 

National Institute of Standards and Technology U.S. Department of Commerce

## **Table of Contents**

CHA	APTER 1	1
POLI	CIES	1
A.	Introduction	1
В.	ProForma Invoice	1
C.	Types of Calibration Services	1
D.	Criteria for Quality Assurance	2
Calib out re well- strict	e measurement services listed in this document meet rigorous criteria for quality assurance. ration Services and MAPs satisfy the most demanding and explicit requirements in that they are carri egularly under pre-established and well-defined conditions; the measurement processes involved are characterized, stable, and statistically controlled; and quality-control procedures are well-defined and ly followed. Furthermore, each Calibration Service or MAP is planned and documented to permit nuity of service over time. Quality	e
	has implemented a quality system for its measurement services. The NIST Quality System,	2
www Quali regul ISO G delive	r.nist.gov/qualitysystem/ (NIST QS) comprises policies and procedures that are documented in the NI ity Manual (NIST QM). NIST commits that the NIST QS be, to the extent allowed by statute and ation, in conformity with the international standard ISO/IEC 17025 and the relevant requirements of Guide 34 as they apply to the Standard Reference Materials® (SRMs) and related services that NIST ers. In general the scope of the NIST quality system for measurement services encompasses all servic I in the NIST Special Publication (SP) 250, NIST Calibration Services Users Guide and the NIST Special	
	cation (SP) 260, Standard Reference Materials Catalog.	2
Fees	2	
F.	Reports of Calibration/Test Results	2
G.	Traceability	2
Н.	Reporting Measurement Uncertainty	3
١.	Use of Metric (SI) Units	3
J.	Reference to NIST in Advertisements	3
К.	Disclaimer	4
L.	Questions and Inquires	4
M.	Contracts and Signed Statements	4
CHA	APTER 2	5
ORDI	ERING INSTRUCTIONS FOR DOMESTIC CUSTOMERS	5
A.	Customer Inquires	5
В.	Prearrangements and Scheduling	5
C.	Purchase Orders	5
D.	Remit to	6
E.	Shipping, Insurance, and Risk of Loss	7
F.	Turnaround Time	7
G.	Customer Checklist	7
CHA	APTER 3	9
SPEC	IAL INSTRUCTIONS FOR FOREIGN CUSTOMERS	9

Α.	Foreign Inquires	9
В.	Criteria for Providing Service	9
C.	Special Instructions	9
D.	Shipping Charges	11
CHA	APTER 4	12
DIMI	ENSIONAL MEASUREMENTS	12
Α.	Length Measurements	12
В.	Diameter and Roundness Measurements	14
C.	Complex Dimensional Standards	15
E.	Optical Reference Planes and Roundness Standards	17
F.	Angular Measurements	18
G.	Laser Measurements	18
Н.	Surface Texture	19
١.	Nanostructures	19
<b>CH</b> A	APTER 5	20

MEC	CHANICAL MEASUREMENTS	20
Α.	Hydrometers	20
В.	Volume and Density	20
C.	Flow Measurements	21
D.	Flow Measurements at Cryogenic Temperatures	21
E.	Air Speed Measurements	22
F.	Mass Standards	22
G.	Force Measurements	23
Н.	Vibration Measurements	24
١.	Acoustic Measurements	25

### **CHAPTER 6**

26

THERMODYNAMIC QUANTITIES		26
Α.	Pressure Measurements	26
В.	Vacuum, Low Pressure and Leak Measurements	26
C.	Laboratory and Industrial-Grade Thermometers	28
D.	Thermocouples, Thermocouple Materials, Thermometer Indicators	29
Ε.	Resistance Thermometry	30
F.	Radiance Temperature Measurements	32
G.	Humidity Measurements	33
Н.	Thermal Resistance Measurements	33

## **CHAPTER 7**

35

OPTIC	AL RADIATION MEASUREMENTS	35
Α.	Photometric Measurements	35
В.	Ozone Measurements	36
C.	Optical Properties of Materials Measurements	36
D.	Surface Color and Appearance	37
E.	Spectroradiometric Measurements	37
F.	Radiometric Standards in the Ultraviolet	39

G.	Laser and Optoelectronic Components Used with Lasers	40
CHA	APTER 8	42
IONI	ZING RADIATION MEASUREMENTS	42
Α.	Radioactivity Sources	42
В.	Neutron Sources and Neutron Dosimetry	43
C.	Dosimetry of X-Rays, Gamma-Rays, and Electrons	43
D.	Dosimetry for High-Dose Applications	44
CHA	APTER 9	46
ELEC	TROMAGNETIC MEASUREMENTS	46
Α.	Resistance Measurements	46
В.	Impedance Measurements (Except Resistors)	48
C.	Voltage Measurements	50
D.	Precision Ratio Measurements	52
Ε.	Phase Meters and Standards and VOR Measurements	54
F.	Power and Energy Measurements, Low-Frequency	55
G.	RF, Microwave and Millimeter-Wave Measurements	56
Η.	Electromagnetic Field Strength and Antenna Measurements	60
Ι.	High-speed Repetitive Waveform Measurements	61
J.	Pulse Waveform Measurements	61
CHA	APTER 10	62
TIME	AND FREQUENCY MEASUREMENTS	62
Α.	Broadcast and Measurement Services	62
В.	Calibration and Characterization of Oscillators and Amplifiers	63
C.	Test of PM/AM Noise Measurement Systems	63
CHA	APTER 11	64
SEMI	INARS	64

## CHAPTER 1 POLICIES

### A. Introduction

The calibration services of the National Institute of Standards and Technology (NIST) are designed to help the makers and users of precision instruments achieve the highest possible levels of measurement quality and productivity. The services listed in this Fee Schedule constitute the highest order of calibration services available in the United States. They directly link a customer's precision equipment or transfer standards to national and international measurement standards. These services are offered to public and private organizations and individuals alike.

For more specific information, the NIST Calibration Services Users Guide, SP 250, contains data on uncertainty and other technical references. Copies are available upon request or consult our website (see Section L of this chapter).

### **B. ProForma Invoice**

Please be advised that for non-U.S. government agencies, starting 01 January 2013, a new legal document (Calibration Service Pro Forma Invoice) containing the NIST calibration service terms and conditions are required for all calibration services. This document is a Calibration Cooperative Research and Development Agreement (C-CRADA) between your company and NIST. In general, this C-CRADA protects your calibration information as well as providing you with a firm price quote, explaining invoicing information, and information on the NIST quality system and traceability. In addition to the legal terms and conditions, the Calibration Service Pro Forma Invoice is used in two primary ways: 1) to create a firm price quote prior to submission of a company purchase order or 2) to create a firm price quote after receipt of a company purchase order. In either case, a signed copy of the Calibration Service Pro Forma Invoice Pro Forma Invoice by the authorized company representative is required by NIST. The terms and conditions of the Calibration Service Pro Forma Invoice of a company is purchase order.

For U.S. government agencies, an agreement is required in lieu of the Calibration Service Pro Forma Invoice. Please contact Nancy Selepak (nancy.selepak@nist.gov) for assistance.

### C. Types of Calibration Services

- Calibration Services
- Special Tests
- Measurement Assurance Programs (MAPs)

NIST provides Calibration Services using well-characterized, stable and predictable measurement processes. NIST calibrates instruments and devices that are metrologically suitable as reference or transfer standards.

**Special Tests** are so designated for one or more of the following reasons: (1) the specific type of calibration is seldom requested, thus precluding the maintenance of a large statistical base for characterizing the measurement process; (2) the test requested is unique; or (3) the service is still under development – meaning the measurement or calibration methods are still being perfected, or all the quality-control documentation has not been completed.

**Measurement Assurance Programs** are quality control programs for calibrating a customer's entire measurement system. In a typical MAP, a stable artifact or set of artifacts called transfer standards are first measured by NIST and then sent to a customer's laboratory for a series of measurements. The transfer standards are then returned to NIST for re-measurement, along with the participating laboratory's results.

NIST reports its comparative findings to the customer and, when necessary, offers guidance on achieving and maintaining measurement quality. Successful use of a NIST MAP requires that the customer make periodic measurements of in-house check standards to estimate their measurement process uncertainty and to ensure that the measurement process remains in a state of statistical control. Unless a laboratory has a measurement quality assurance program to monitor its own measurement process parameters continuously, there is no value in participating in a MAP. In fact, NIST recommends that its customers establish and use a measurement quality assurance program to monitor their measurement parameters, whether or not they participate in a MAP.

### **D.** Criteria for Quality Assurance

All the measurement services listed in this document meet rigorous criteria for quality assurance. Calibration Services and MAPs satisfy the most demanding and explicit requirements in that they are carried out regularly under pre-established and well-defined conditions; the measurement processes involved are well-characterized, stable, and statistically controlled; and quality-control procedures are well-defined and strictly followed. Furthermore, each Calibration Service or MAP is planned and documented to permit continuity of service over time.

### E. Quality

NIST has implemented a quality system for its measurement services. The NIST Quality System, www.nist.gov/qualitysystem/ (NIST QS) comprises policies and procedures that are documented in the NIST Quality Manual (NIST QM). NIST commits that the NIST QS be, to the extent allowed by statute and regulation, in conformity with the international standard ISO/IEC 17025 and the relevant requirements of ISO Guide 34 as they apply to the Standard Reference Materials® (SRMs) and related services that NIST delivers. In general the scope of the NIST quality system for measurement services encompasses all services listed in the NIST Special Publication (SP) 250, NIST Calibration Services Users Guide and the NIST Special Publication (SP) 260, Standard Reference Materials Catalog.

### Fees

NIST recovers the cost of providing calibration services by charging a fee for each calibration performed. The costs of services are published in the Fee Schedule, which is updated and published annually to reflect changes in prices and services. Even so, the cost of many services varies according to your exact calibration specifications; you must therefore provide the technical contact with an exact description of work before receiving a price quote.

### NOTE: Fees for NIST services do not include shipping costs or insurance.

### F. Reports of Calibration/Test Results

Reports on calibrations or other services are the property of the customer. Copies are supplied to other parties only as required by federal law or requested in writing by the customer. The results of calibrations and tests performed by NIST apply only to the specific instrument or standard at the time of test unless otherwise clearly stated.

### G. Traceability

The primary purpose of the NIST Policy on Traceability is to state the NIST role with respect to traceability. The Policy presents the definition of measurement traceability used by NIST, and clarifies the roles of NIST

and others in achieving traceability of measurement results for measurements both internal and external to NIST.

The NIST Policy on Traceability also addresses the role of NIST in providing its customers with the tools they need (a) to assist them in establishing traceability of their measurement results, and (b) to assess the claims of traceability made by others. This is achieved directly through the provision of NIST measurement-related products and services, through collaboration with relevant organizations, through development and dissemination of technical information on traceability, and through conducting coordinated outreach programs.

Merely having an instrument or artifact calibrated at NIST is not enough to make the measurement result traceable to reference standards developed and maintained by NIST. To establish traceability to such reference standards, there must be an unbroken chain of comparisons and each provided measurement must be accompanied by a statement of uncertainty. The measurement system by which values are transferred must be clearly understood and under control. The dates and details of each link in the chain must also be provided.

Although NIST supports making the user aware of traceability and provides the user with details as to how traceability is established, NIST does not allow the prominent display of its name on proprietary products or in the advertising of them (See Section J of this chapter).

### H. Reporting Measurement Uncertainty

To ensure that NIST uncertainty statements are consistent across the organization and with international practice, NIST policy requires that all NIST measurements be accompanied by statements of uncertainty as discussed in NIST Technical Note 1297<sup>1</sup>.

NIST reports its calibration results, with the measurement values accompanied by the uncertainties associated with the methods, operators, and environment at NIST. Users of these calibration services will make their own measurements with the calibrated instruments or artifacts. In addition to the uncertainty indicated by NIST, other uncertainties are inherent in the instrument, associated with the method or protocol in using the instrument, with the operator of the instrument, and with the physical environment (pressure, temperature, humidity, etc.) in which the measurements are made. Thus, the measurements made with the calibrated instruments or artifacts by organizations outside of NIST have total uncertainty budgets associated with them, only one component of which is the uncertainty reported to them by NIST.

### I. Use of Metric (SI) Units

In accordance with the Metric Conversion Act of 1975 as amended by Section 5164 of the Omnibus Trade and Competitiveness Act of 1988 and as required by related provisions of the Code of Federal Regulations, the National Institute of Standards and Technology (NIST) uses the modern metric system of measurement units (International System of Units–SI) in all publications. When the field of application or the special needs of users of NIST publication require the use of non-SI units, the values of quantities are first stated in the SI units and the corresponding values expressed in non-SI units follow in parentheses. Copies of NIST SP 811<sup>3</sup> are available upon request (see Section L) or on the web site: www.nist.gov/pml/pubs/

### J. Reference to NIST in Advertisements

The NIST measurement/test results or reports shall not be used to indicate or imply that NIST approves, recommends, or endorses the manufacturer, supplier, or user of any instruments or standards or that NIST in any way guarantees or predicts the future performance of items after calibration or test. No reference shall be made to NIST or to reports or results furnished by NIST in any advertising or sales promotions, which would indicate or imply that NIST approves, recommends, or endorses any proprietary product or proprietary material.

### K. Disclaimer

Commercial products, materials, and instruments, are identified in our communications and documents for the sole purpose of adequately describing experimental or test procedures. In no event does such identification imply recommendation or endorsement by NIST of a particular product; nor does it imply that a named material or instrument is necessarily the best available for the purpose it serves.

### L. Questions and Inquires

The NIST Calibration Services website is intended to make the task of selecting and ordering an appropriate calibration service as quick and easy as possible. Nevertheless, when questions arise you should contact NIST for immediate clarification.

General inquiries about the NIST calibration services, assistance in determining the availability of services, and requests for complimentary copies of the Guide for the International System of Units (SP 811), and Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Results (TN 1297) are to be addressed to:

PML Calibration Services National Institute of Standards and Technology 100 Bureau Drive, Stop 8363 Gaithersburg, MD 20899-8363 United States of America Telephone: (301) 975-2200 Fax: (301) 975-2950 Email: calibrations@nist.gov Internet: www.nist.gov/calibrations/

For technical questions concerning a specific service, directly contact the NIST staff member responsible for that calibration area.

### **M.** Contracts and Signed Statements

As an agency of the United States Federal Government, Department of Commerce, the National Institute of Standards and Technology attests solely to the provisions described above. Receipt of orders by NIST does not imply acceptance of any provisions set forth in the order that are contrary to the policy, practice, or regulations of NIST or the U.S. Government. In general, NIST will not sign any affidavits, acknowledgement forms, or other documents that may be required by any domestic or foreign entity for policy governing procurement of goods and services.

### N. Use of NIST Instrumentation at a User's Facility

The delivery of certain measurement services requires that NIST equipment be loaned to the customer for onsite measurements and/or calibrations. The customer agrees to be responsible for the equipment once it leaves NIST until it is returned to NIST's possession. The User will obtain appropriate liability insurance, including property damage insurance, and will be required to present evidence of insurance coverage for the equipment in an amount not less than \$100,000, or alternatively, not less than the amount specified by NIST in the documentation accompanying the equipment.

### **CHAPTER 2** ORDERING INSTRUCTIONS FOR DOMESTIC CUSTOMERS

### A. Customer Inquires

General customer inquiries for information or clarifications about the NIST calibration services should be directed as follows:

PML Calibration Services National Institute of Standards and Technology 100 Bureau Drive, Stop 8363 Gaithersburg, MD 20899-8363 301-975-2200 phone 301-975-2950 fax calibrations@nist.gov

### **B.** Prearrangements and Scheduling

Services should be arranged in advance, beginning with direct contact with a NIST technical staff member responsible for the desired service. Use the appropriate technical section of the Users Guide or Fee Schedule to determine whom to contact. This advance communication may answer your questions, clarify the policies and procedures briefly described here, and will permit you to schedule a tentative calibration date. Following the initial communication, you must complete and submit a purchase order and prepare to ship the item according to the procedures described below or agreed upon with the technical contact. If a calibration is scheduled far in advance, the item should not be shipped until shortly before the scheduled date; you must submit the purchase order (complete with the name and number of the desired service) before a firm calibration date can be assigned. When NIST receives your purchase order and assigns a firm service date, your order will be confirmed by the technical contact.

### C. Purchase Orders

Before you ship an item for calibration, send a purchase order to the address listed in the appropriate technical section. The purchase order must:

- 1. State both the name and number of the NIST service (listed in this Fee Schedule as the "Service ID Number") being requested. FAILURE TO INCLUDE THE SERVICE ORDER NUMBER WILL SERIOUSLY IMPEDE SCHEDULING AND SERVICE.
- 2. Clearly identify the item(s) being sent for calibration, including any serial number(s) or model number(s).
- 3. Give the name, address, and telephone number of your company's procurement officer, purchasing agent or other administrative/financial authority.
- 4. Give the name, address, and telephone number of your company's technical contact, if different from above.
- 5. List separately the instructions and address for return shipment, insurance, mailing address for the calibration/test report, and billing address. (Federal or state agency requests for calibration services should be accompanied by a document authorizing that the cost of the service be billed to the agency).
- 6. Clearly state any special or necessary conditions of test, such as operating frequency or temperature.

- 7. Clearly state the customer identification number; i.e., customer's employer identification number (EIN) for individuals; tax identification number (TIN) for organizations; or agency location code (ALC) for government customers.
- 8. If the calibration or test report is to be handled in a special manner, give instructions on the purchase order.

**NOTE:** Receipt of orders by NIST does not imply acceptance of any provisions set forth in the order that are contrary to the policy, practice, or regulations of NIST or the U.S. Government. In general, NIST will not sign any affidavits, acknowledgement forms, or other documents that may be required by company policy governing the procurement of goods and services.

### **D.** Remit to

Payment Terms: Net 30 days

No discounts are allowed for early payment.

### PAY.GOV

For NIST invoices, electronic payments can be submitted through Pay.gov by ACH, VISA, MasterCard, Discover, American Express or debit card. Go to www.pay.gov. Bypass the user id and password section; you do not need to be registered with Pay.gov to make a payment against our invoices. To locate the payment forms click on "by Agency Name" on the left hand side of the menu bar. Find and select the National Institute of Standards and Technology. Choose the appropriate NIST payment form that best fits your invoice. Complete all required fields and submit you payment.

## Note: For ACH payments, please verify with your banking institution that your account is set up to have ACH payments processed.

#### **Remit to address:**

NIST Lockbox accepts check payments for NIST. Please use the following address for all NIST payments:

NIST P.O. Box 301505 Los Angeles, CA 90030-1505

Please remember that all checks must be drawn on a United States bank and made payable in US dollars. In addition, please continue to reference the NIST invoice/receivable number on the check stub.

### **Other Forms of Payment**

In addition to checks, NIST also accepts VISA, MasterCard, Discover, and American Express. Customers can supply their credit card information and fax a copy of the invoice to Accounts Receivable at 310/975-8943 or mail the information to:

NIST Mail Stop 1624 100 Bureau Drive Gaithersburg, MD 20899-1624

#### NIST Federal Identification Number: 530-20-5706

#### NIST DUNS Number: 929956050

W-9 Mail to: NIST Accounts Receivable Stop 1624 Gathersburg, MD 20899-1624

### E. Shipping, Insurance, and Risk of Loss

Ship the instrument or standard to the mailing address of the technical group providing the service. Please take note that the mailing address is not the same for every technical group.

#### Please adhere rigorously to the following procedures:

- 1. Ship only items in good repair. Apparatus in disrepair will not be calibrated. If defects are found, after calibration has begun, the procedure will be terminated, a report issued, and a charge levied for work completed.
- 2. Use strong, reusable packing materials and containers marked clearly and indelibly on the outside with the requestor's name, address and the following notation: **REUSABLE CONTAINER, DO NOT DESTROY.**
- 3. Follow any special shipping procedures given in the technical sections of the Calibration Services Users Guide, particularly those sections covering radiation and dosimetry measurements.
- 4. Insure the shipments to and from NIST and clearly state the method of return shipment. NIST will not assume liability for loss or damage unless such loss and damage result solely from the negligence of NIST personnel. If return shipment by parcel post is requested or is suitable, NIST will prepay the return shipment but will not insure it. When no shipping or insurance instructions are furnished, NIST will return the shipment by common carrier, collect and uninsured.
- 5. Shipments to NIST must be at FOB destinations (customer pays for shipping).
- 6. Return shipments are sent FOB origin (customer pays for shipping).

### NOTE: Fees for NIST services do not include shipping cost or insurance.

### F. Turnaround Time

Normal turnaround time for NIST calibration services varies greatly–usually from several weeks to several months depending on the type of service requested, and the service schedule. Some services are only scheduled once or twice a year with appointments made months in advance of the service date. To avoid unnecessary scheduling or administrative delays in the calibration process, always make arrangements with the technical contact for the service you wish to utilize prior to shipping your instrument or artifact to us.

### G. Customer Checklist

Please refer to last page of this chapter for a Customer Checklist which is intended to assist you in developing the basic information required to process an order for calibration services at NIST.

## Customer Checklist for Ordering NIST Calibration Services

Information Obtained from NIST Technical Contact	Comments
NIST Contact (name/telephone)	Provide this information on your purchase order (PO)
Is the service available?	Please make sure customer's technical contact discusses service with NIST technical contact before proceeding.
NIST Service Identification Number	Provide this information on your PO
Estimated cost of services	Provide this information on your PO
Estimated turnaround time	Many calibration services are batched. Find out when to send the instrument.
Special instructions	
Packaging instructions	
Shipping instructions	
Other Precautions	
Information Supplied by the Customer on Purchase Order	
Purchase order number	
Purchase order date	
Customer's tax identification number	
Customer's mailing address	
Customer's billing address	
Name, telephone number, fax number, email address of administrative or procurement contact point at customer's location	
Name, telephone number, fax number, email address of technical contact point at customer's location	
Ship-to address (including NIST technical contact name)	
Return address (for shipment back to customer)	
NIST Service Identification Number	
Estimated cost	
Shipping terms (no FOB destination on return shipment)	
Special instructions from customer's technical contact	

### **CHAPTER 3** SPECIAL INSTRUCTIONS FOR FOREIGN CUSTOMERS

### A. Foreign Inquires

Foreign customers should address all inquiries to:

PML Calibration Services National Institute of Standards and Technology 100 Bureau Drive, Stop 8363 Gaithersburg, MD 20899-8363 United States of America Telephone: (301) 975-2200 Fax: (301) 975-2950 Email: calibrations@nist.gov Internet: www.nist.gov/calibrations/

**NOTE:** Please clearly indicate your **city** and **country** on all correspondence so that we may promptly respond to your request.

### **B.** Criteria for Providing Service

Under certain circumstances, NIST is authorized to provide measurement service, including calibration services, for organizations or individuals located outside the United States. However, the Calibration Program must review each request for calibration services to determine if services are available to the requestor's organization in the requestor's country. Foreign customers must provide the following information, in writing, to the Calibration Program (see address above):

- 1. Identification of the item(s) to be calibrated, including serial and model numbers.
- 2. A detailed description of the measurements that are needed, or indicate the service identification number.
- 3. A description of any special requirement/circumstance that might affect the decision to provide the service. For example, will adjustments have to be made to the instrument, or will the time period be restricted in which the device is available for calibration?
- 4. A complete name and address of the requestor's organization.

### C. Special Instructions

If the request for calibration service is accepted by NIST, the requesting organization will be notified of the cost of service and will be given the contact information for the NIST technical unit that will perform the measurements. The requesting organization must then complete the following steps:

- 1. Contact the NIST technical staff that will perform the service to determine the time schedule.
- 2. Send a purchase order to the Calibration Program. Provide complete addresses, including country, for returning the instrument and for mailing the calibration or test report.
- 3. NIST policy requires prepayment for all NIST calibration services requested by non-U.S. organizations. Before proceeding with any service(s), we will need a check, money order or a bank wire transfer. The prepayment must be for the full amount and be drawn on a U.S. bank. The prepayment methods are as follows:

#### **Money Orders & Prepayment Checks**

All foreign checks must be drawn on a United States Bank and made payable in US Dollars. All foreign checks must be mailed to the Receivables officer for deposit. In addition, please reference the NIST invoice/receivable number on the check stub. Checks made payable to the National Institute of Standards and Technology (NIST) should be mailed to:

NIST Mail Stop 1624 100 Bureau Drive Gaithersburg, MD 20899-1624

#### Prepayment by credit card

Please contact NIST Accounts Receivable Office at 301-975-3880, by email: billing@nist.gov, or by Fax: 301-975-8943.

#### **Bank Wire Transfers**

Payments may also be sent by wire using the US Department of Treasury FEDWIRE system and it can be done so to the following bank:

Treas NYC (Account is with the Federal Reserve Bank of New York) U.S. Dept. of Treasury 33 Liberty Street New York, NY 10045 Phone: 001-202-874-7132

In Payment Details field, CL329930001 ABA# 021030004 Account # 13060001 Account Name: TREAS NYC/CTR/BNF=/NIST/AC-13060001

Reference "Calibrations" to enable us to identify your payment. In addition, please be sure to pay any fees assessed for your bank wire transfers; otherwise, they will deduct it from your prepayment wire.

## We cannot accept wire payment make through the Swift system only FEDWIRE. Therefore, we do not have a Swift code.

**PLEASE NOTE:** Our account number and name are of critical importance and must be referenced in order for NIST to be properly credited with your payment. It must appear in the precise manner shown to allow for the automated processing and classification of the funds transfer message. In addition, please refer to the NIST invoice number, your purchase order number, your country, and any other pertinent information that would help us identify you payment.

The transfer of funds can only be accomplished by your company going through a U.S. correspondent bank or by having your country's central bank send a swift telecommunication system message to the Federal Reserve Bank. **Be sure to cover any processing fees your bank may charge you.** Questions on bank wiring can be directed to the NIST Accounts Receivable Office at 301-975-3880, email: billing@nist.gov, or fax at 301-975-8943.

### **D.** Shipping Charges

The calibration costs quoted *do not* include shipping, insurance, or the services of a customs broker. You must arrange and pay for these services separately. For your information, NIST currently uses the following customs brokers:

Gaithersburg, Maryland	Boulder, Colorado
Laing International	FedEx Trade Networks
P.O. Box 16144	4725 Paris Street, Suite 200
Washington, DC 20041	Denver, CO 80239
Phone: (703) 471-9279	Phone: (303) 371-9550
Fax: (703) 471-8436	Fax: (303) 373-0850

You are **not required** to use these customs brokers, but may select a broker of your choice.

### CHAPTER 4 DIMENSIONAL MEASUREMENTS

### A. Length Measurements

A.1 Gage Blocks

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Eric Stanfield	(301) 975-4882	eric.stanfield@nist.gov	NIST
(Long blocks)			100 Bureau Drive, Stop 8211
Beverly Connelly	(301) 975-2485	beverly.connelly@nist.gov	Gaithersburg, MD 20899-8211
(Short blocks)			
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	

Please contact the technical staff before shipping instruments or standards to the address listed above.

A.1 Gage Blocks			
Service ID Number	Description of Services	Fee (\$)	
10010C	Gage Blocks: Set Up Charge, per order	216	
10011C	Mechanical Comparisons, per Block (100 mm and shorter)	128	
10012C	Mechanical Comparisons, per Block (over 100 mm)	307	
10013C	Interferometry, per Block (100 mm and shorter), Maximum 25 Blocks per Order	351	
10014S	Interferometry, per Block (over 100 mm)	At Cost	
10015S	Non-standard size Gage Blocks	At Cost	

Fees are subject to change without notice.

### A.2 Line Standards

<b>Technical Contact:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Addre
Ted Doiron	(301) 975-3472	dorion@nist.gov	NIST
			100 Purson Dri

Mailing Address: NIST 100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211

### Please contact the technical staff before shipping instruments or standards to the address listed above.

A.2 Line Standards				
Service ID Number	Description of Service	Fee (\$)		
10020C	Line Standards: Scales, < 1 m (40 inches), 4 Passes	9942		
10021C	Line Standards: Scales, < 1 m (40 inches), 8 Passes	15230		
10022C	Line Standards: Stage Micrometer, Per Scale, 30 Intervals, 2 Passes	1657		
10023C	Line Standards: Stage Micrometer, Per Scale, 30 Intervals, 4 Passes	2071		

Fee Schedule 2017

10024C	Line Standards: End Standards, < 1 m	10149
10025C	Line Standards: Grid Plates, Less than 60 Intervals, 1 D Linear Calibration	16693
<b>F</b> 1		

### A.3 Metal Tapes/Scales and Long Length Artifacts

<b>Technical Contact:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Chris Blackburn	(301) 975-6413	chris.blackburn@nist.gov	NIST
Daniel S. Sawyer	(301) 975-5863	daniel.sawyer@nist.gov	100 Bureau Drive, Stop 8211
			Gaithersburg, MD 20899-8211

### Please contact the technical staff before shipping instruments or standards to the address listed above.

A.3 Metal Tapes/Scales and Long Length Artifacts				
Service ID Number	Description of Services	Fee (\$)		
10030S	Metal Tapes: Surveying, Oil Gaging, and General Purpose; Metal Scales	At Cost		
10040S	Special Tests of Long Length Artifacts	At Cost		

### **B.** Diameter and Roundness Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Eric S. Stanfield	(301) 975-4882	eric.stanfield@nist.gov	NIST
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	100 Bureau Drive, Stop 8211
			Gaithersburg, MD 20899-8211

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
11010C	Cylindrical Diameter Standards (i.e. Plug and Pin Gages): Set Up Charge, per order	208
11011C	Mechanical comparison, per Gage (25 mm and smaller)	126
11012C	Interferometry, per Gage (50 mm and smaller)	281
11013S	Per Gage (over 50 mm)	At Cost
11014C	Roundness trace, per trace	231
11020C	Measuring Wires for Threads and Gears: Set Up Charge, per order	216
11021C	Single Wire, per wire	126
13020C	Special Tests of Roundness (Sphere and Hemisphere Types) Reversal Method: Radial Deviations from Best Fit Least–Squares Circle at 360 positions	1408
13030S	Special Tests of Roundness Calibration Specimens	At Cost
11030C	Spherical Diameter Standards; Balls: Set Up Charge, per order (applies to mechanical comparison and interferometry)	216
11031C	Mechanical Comparison (51 mm or smaller), Average Diameter, per ball, Expanded Uncertainty, U $\sim \pm 89$ nm to 115 nm	122
11032S	Mechanical Comparison (over 51 mm), Average Diameter, per ball	At Cost
11033C	Interferometry (25 mm or smaller) Average Diameter, per ball, Expanded Uncertainty, U $\sim \pm 30$ nm	600
11034C	Ball Out-of-Roundness: Least-Squares Out-of-Roundness and Polar Plots, price per trace (Typically three orthogonal traces for spheres and five traces for CMM calibration spheres) price per trace	114
	Special Tests of Internal Diameter Standards: Ring Gages	
11040C	Plain Ring Gages, per ring	964
11050S	Special Tests of Diameter	At Cost

## C. Complex Dimensional Standards

### C.1 API Threaded Plug and Ring Gages

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Dennis Everett	(301) 975-5272	dennis.everett@nist.gov	NIST
(12010C-12070S)			100 Bureau Drive, Stop 8211
Eric Stanfield	(301) 975-4882	eric.stanfield@nist.gov	Gaithersburg, MD 20899-8211
(11050S)			
John Stoup	(301) 975-3476	john.stoup@nist.gov	
(12060S)			
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	
(12010C–12070S) Eric Stanfield (11050S) John Stoup (12060S)	(301) 975-4882 (301) 975-3476	eric.stanfield@nist.gov john.stoup@nist.gov	100 Bureau Drive, Stop 8211

### Please contact the technical staff before shipping instruments or standards to the address listed above.

	C.1 API Threaded Plug and Ring Gages			
Service ID Number	Description of Services	Fee (\$)		
12010C	Spec 5, 1.005 inches to 7 5/8 inches	2524		
12011C	Spec 5, 8 5/8 inches to 20 inches	3815		
12012C	Buttress Casing, 4 1/2 inches to 9 5/8 inches	2973		
12013C	Buttress Casing, 10 inches to 13 3/8 inches	3563		
12014C	Buttress Casing, 16 inches to 20 inches	3844		
12015C	Line Pipe, 1/8 inch to 6 inches (New)	2488		
12016C	Line Pipe, 8 inches to 20 inches (New)	3290		
12017C	Extreme Line Casing, 5 inches to 7 inches (New)	4126		
12018C	Extreme Line Casing, 5 inches to 7 inches (Used)	1566		
12019C	Extreme Line Casing, 7 5/8 inches to 10 inches (New)	4686		
12021C	Extreme Line Casing, 7 5/8 inches to 10 inches (Used)	1977		
12022C	Spec 7 (Rotary), NC 23 - NC 61 (New)	3187		
12023C	Spec 7 (Rotary), NC 70 (New)	3367		
12024C	Spec 7 (Rotary), 1 inch to 4 1/2 inches, Reg. (New)	3187		
12025C	Spec 7 (Rotary), 5 1/2 inches to 8 5/8 inches, Reg. (New)	3491		
12026C	Spec 7 (Rotary), Any Type (Used)	1473		
12027C	Spec 11B (Sucker Rods) P1, P2 Pin Go P7, P8 Pin Go B1, B2 Box Go (NEW)	1658/per set		

Fee Schedule 2017

12028C	Spec 11B (Sucker Rods) P1, P2 Pin Go P7, P8 Pin Go B1, B2 Box Go (USED)	851/per set
12029C	Spec 11B (Sucker Rods) P3, P4 Pin Cone B3, B4 Box Cone (NEW)	1990/per set
12031C	Spec 11B (Sucker Rods) P3, P4 Pin Cone B3, B4 Box Cone (USED)	773/per set
12032C	Spec 11B (Sucker Rods) P5, P6 Pin Cone B5, B6 Box Cone (NEW)	1321/per set
12033C	Spec 11B (Sucker Rods) P5, P6 Pin B5, B6 Box Cone (USED)	685/per set
12050S	Special Tests of Threaded Plug and Ring Gages	At Cost
12060S, 11050S	Special Tests of Two- and Three-Dimensional Gages	At Cost
12070S	Special Complex Dimensional Test, by Prearrangement	At Cost

### C.2 Sieves

<u><b>Technical Contacts:</b></u>	<u>Telephone:</u>	Email:	<u>Mailing Address:</u>
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	NIST
	(301) 773 3472	incodore.donone inst.gov	100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211

Please contact the technical staff before shipping instruments or standards to the address listed above..

### C.3 Algorithms Testing and Evaluation Program for Coordinate Measuring Systems

**Technical Contact: Telephone:** Email: **Mailing Address:** Craig M. Shakarji (301) 975-3545 shakarji@nist.gov NIST

100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211

#### Please contact the technical staff before shipping instruments or standards to the address listed above.

C.3 Algorithms Testing and Evaluation Program for Coordinate Measuring Systems			
Service ID Number	Description of Services Fee (S		
10070C	CMS Software: NIST-generated data sets (basic service)	2091	
10071S	Special Test of CMS Software: NIST-generated data sets (per geometry evaluated)	At Cost	
10072C	CMS Software: NIST-generated data sets, standard level (per geometry evaluated)	903	
10080S	Special Test of CMS Software: Customer-generated data sets (basic service)	At Cost	
10081S	Special Test of CMS Software: Customer-generated data sets (per geometry evaluated)	At Cost	
10082S	Special Test of CMS Software: Customer-generated data sets, standard level (per geometry evaluated)	At Cost	

Fees are subject to change without notice.

### E. Optical Reference Planes and Roundness Standards

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Eric S. Stanfield	(301) 975-4882	eric.stanfield@nist.gov	NIST
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	100 Bureau Drive, Stop 8211
			Gaithersburg, MD 20899-8211

#### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
13010C	Optical Reference Planes (Flats): Optical Flat, ≤152 mm (6"), Per Surface	1776
13011C	Optical Reference Planes (Flats): Optical Flat, 152 mm to 203 mm (8")	2317
13012C	Optical Reference Planes (Flats): Optical Flat, 203 mm to 304 mm	3039
13013C	Optical Reference Planes (Flats): Optical Flat, $\geq$ 304 mm (12")	3799
13014S	Optical Reference Planes (Flats): Three Flat Calibration	At Cost

### F. Angular Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Bryon S. Faust	(301) 975-4351	bryon.faust@nist.gov	NIST
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	100 Bureau Drive, Stop 8211
			Gaithersburg, MD 20899-8211

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
14010C	Angle Gage Blocks: Set Up Charge, per order	216
14011C	Angle Gage Blocks, per block	203
14020C	Optical Polygons	240/per face
14030C	Rotary and Indexing Tables: Every 30°	2880
14031C	Rotary and Indexing Tables: (30°, 5°, 1°) Calibration	5745
14040C	Optical Wedges: Fixed-Angle Wedge	990
14041S	Optical Wedges: Variable-Angle Wedge	At Cost
14050S	Special Angular Measurements, by Prearrangement	At Cost

Fees are subject to change without notice.

### G. Laser Measurements

<u>Technical Contact:</u> Jack Stone	<u>Telephone:</u> (301) 975-5638	Email: jack.stone@nist.gov	<u>Mailing Address:</u> NIST
	(202) / / 2020	J	100 Bureau Drive, Stop 8211
			Gaithersburg, MD 20899-8211

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
14510C	Laser Frequency/Wavelength, Full Calibration	
14511C	Quick Check of Frequency/Wavelength at Laboratory Conditions	1615

### H. Surface Texture

Technical Contact: T. Brian Renegar <u>Telephone:</u> (301) 975-4274 Email: brenegar@nist.gov Mailing Address: NIST 100 Bureau Drive, Stop 8212 Gaithersburg, MD 20899-8212

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	
15010C	Roughness Calibration Specimens	
15030C	Step Height Measurements	
15040S	Surface Roughness and Topography Special Tests	At Cost

Fees are subject to change without notice.

### I. Nanostructures

<b>Technical Contact:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Kris Bertness	(301) 975-5069	kris.bertness@nist.gov	NIST

100 Bureau Drive, Stop 8212 Gaithersburg, MD 20899-8212

Service ID Number	Description of Services	Fee (\$)
15510C	Nanostructures with scanning electron microscopy	536

### **CHAPTER 5** MECHANICAL MEASUREMENTS

### A. Hydrometers

<b>Technical Contacts:</b>			
Sherry Sheckels			
John D. Wright			

Telephone: (301) 975-5940 (301) 975-5937 Email: sherry.sheckels@nist.gov john.wright@nist.gov <u>Mailing Address:</u> NIST 100 Bureau Drive, Stop 8361 Gaithersburg, MD 20899-8361

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
16010C	Reference Standard Hydrometers	
16020S	Hydrometers Special Tests	

Fees are subject to change without notice.

### **B.** Volume and Density

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Sherry Sheckels	(301) 975-5940	sherry.sheckels@nist.gov	NIST
John D. Wright	(301) 975-5937	john.wright@nist.gov	100 Bureau Drive, Stop 8361
			Gaithersburg, MD 20899-8361

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
17010C	Volume Standards < 380 L	2207
17020C	Volume Standards > 380 L, 2 points	3074
17030C	Volume Standards > 380 L, 5 points	4375
17040S	Volume Special Tests	At Cost

### **C.** Flow Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email</u>	Mailing Address:
Gina Kline	(301) 975-4813	gina.kline@nist.gov	NIST
(Gas Flow)			100 Bureau Drive, Stop 8361
John D. Wright	(301) 975-5937	john.wright@nist.gov	Gaithersburg, MD 20899-8361
(Gas Flow)			
Iosif Shinder	(301) 975-5943	iosif.shinder@nist.gov	
(Water Flow)			
Aaron Johnson	(301) 975-5954	aaron.johnson@nist.gov	
(Gas Flow and Hydrocarb	on Flow)		
Sherry Sheckels	(301) 975-5940	sherry.sheckels@nist.gov	
(Hydrocarbon Flow)			

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
18010C	Gas Flow Meters	5293
18015C	Natural Gas Flow Calibration	At Cost
18020C	Water Flow Meters	4784
18040C	Transfer Standards	At Cost
18050S	Gas Flow Special Tests	At Cost
18060S	Water Flow Special Tests	At Cost
18070S	Hydrocarbon Liquid Flow Special Tests	At Cost

Fees are subject to change without notice.

See 30063S Special Tests for Low-Gas-Flow Instrumentation

### **D.** Flow Measurements at Cryogenic Temperatures

<b>Technical Contact:</b>	<b>Telephone:</b>	<u>Email</u>	Mailing Address:
Michael Lewis	(303) 497-3458	mlewis@boulder.nist.gov	NIST
Keith Gillis	(301) 975-2468	keith.gillis@nist.gov	325 Broadway, MC 838.09
			Boulder, CO 80305-3328

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
18800S	Special Tests of Cryogenic Liquid Flow – Calibrations of customer supplied cryogenic liquid flow meters in liquid nitrogen from 0.95 kg/s to 9.5 kg/s.	At Cost

### E. Air Speed Measurements

Technical Contacts:TelIosif Shinder(30)

<u>Telephone:</u> (301) 975-5943 Email: iosif.shinder@nist.gov Mailing Address: NIST 100 Bureau Drive, Stop 8361 Gaithersburg, MD 20899-8361

#### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
19010C	High Air Speed Instruments 1.3 m/s to 67 m/s (3 mph to 150 mph)	2889
19030S	High Air Speed Special Tests	At Cost

Fees are subject to change without notice.

### F. Mass Standards

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Patrick Abbott	(301) 975-4218	patrick.abbott@nist.gov	NIST
Zeina J. Kubarych	(301) 975-4468	zeina.kubarych@nist.gov	100 Bureau Drive, Stop 8221
-			Gaithersburg, MD 20899-8221

### **IMPORTANT NOTES TO OUR CUSTOMERS:**

1. Please contact the technical staff for correct Fee and appropriate Service ID Number for your equipment.

2. Please do not send purchase orders and equipment to NIST without scheduling a calibration.

3. Calibrations for variations of complete standard weight sets are available. These may require fewer (or more) than the number of measurement series required for the calibration of a complete standard weight set. These variations will affect pricing of the service. Contact the technical staff for details.

4. If you request a calibration estimate (which includes cost and turnaround time estimates and start date of calibration), please note that we need to receive a confirmation from you to reserve the calibration start date. If no confirmation is received within 30 days, the reservation will be cancelled and the start date given to the next customer.

Please contact the technical staff before shipping instruments or standards to the address listed above.
--

Service ID Number	Description of Services	Fee (\$)
22011C	Weight cleaning	317
22021C	Single or two equal weights 1 kg or 100 g	2959
22023C	Combination of 5,2,2,1 in the range of 1 kg - 1 mg	2959
22032C	Single or two equal weights 10 kg to 50 kg	2969
22110S	Single Weights > 50 kg to 1200 kg	At Cost
221208	Single Weights 1200 kg to 28000 kg	At Cost

Fee Schedule 2017

22160C	Single Weights for Dead Weight Pressure Testers < 10 kg	1171
22140C	Single Weights for Dead Weight Pressure Testers > 22.7 kg (> 50 lb)	At Cost
22161C	Single Weights for Dead Weight Pressure Testers $> 10$ kg to 50 kg	1493
22170S	Special Mass Measurement Services	At Cost

### **G.** Force Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Rick L. Seifarth	(301) 975-6652	ricky.seifarth@nist.gov	NIST
Samuel L. Ho	(301) 975-6648	samuel.ho@nist.gov	100 Bureau Drive, Stop 8222
Kevin L. Chesnutwood	(301) 975-6653	kchesnut@nist.gov	Gaithersburg, MD 20899-8222

 Administrative and Logistics:

 June Eckley
 (301) 975-5866

 Fax:
 (301) 417-0514

june.eckley@nist.gov

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
23010C	Force Transducers to 112 540 N (25 300 lbf) 1 mode	3825
23020C	Extra observation	76
23030C	Additional bridges	1026
23040C	Force Transducers to 112 540 N (25 300 lbf) 2 modes	6311
23050C	Extra observation	76
23060C	Additional bridges	1042
23070C	Force Transducers 112 540 N to 498 201 N (25 300 lbf to 112 000 lbf) 1 mode	4375
23080C	Extra observation	76
23090C	Additional bridges	1185
23100C	Force Transducers 112 540 N to 498 201 N (25 300 lbf to 112 000 lbf) 2 modes	8641
23110C	Extra observation	227
23120C	Additional bridges	2397
23130C	Force Transducers 498 205 N to 1 334 467 N (112 000 lbf to 300 000 lbf) 1 mode	8993
23140C	Extra observation	227
23150C	Additional bridges	1490
23160C	Force Transducers 498 205 N to 1 334 467 N (112 000 lbf to 300 000 lbf)	14305

Fee Schedule 2017

	2 modes	
23170C	Extra observation	307
23180C	Additional bridges	2678
23190C	Force Transducers 1 334 471 N to 4 448 222 N (300 00 lbf to 1 000 000 lbf) 1 mode	10693
23200C	Extra observation	227
23210C	Additional bridges	2087

23220C	Force Transducers 1 334 471 N to 4 448 222 N (300 00 lbf to 1 000 000 lbf) 2 modes	16853
23230C	Extra observation	296
23240C	Additional bridges	3735
232508	Force Transducers over 4 448 222 N (1 000 000 lbf) compression only	At Cost
23260S	Special Tests of Force Transducers	At Cost

### H. Vibration Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address
Richard A. Allen	(301) 975-5026	richard.allen@nist.gov	NIST
		_	100 Bureau Drive

#### Mailing Address: NIST 100 Bureau Drive, Stop 8223 Sound Bldg. (233) Rm. B102 Gaithersburg, MD 20899-8223

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
24110C	Accelerometer Sensitivity, Sinusoidal, 10 Hz to 20 kHz, for accelerometer mass $\leq$ 350 g	2107
24130S	Accelerometer Special Test	At Cost

### I. Acoustic Measurements

Technical Contacts:	Telephone:	Email:	Mailing Address:
Randall P. Wagner	(301) 975-6619	<u>randall.wagner@nist.gov</u>	NIST
			100 Bureau Drive, Stop 8221
			Gaithersburg, MD 20899-8221

Administrative and Logistics:

Beverly Connelly (301) 975-2485 Fax: (301) 990-8291

(301) 975-2485 <u>beverly.connelly@nist.gov</u>

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
25010C	Pressure Response: WE Type 640AA microphones or equivalent (e.g., Tokyo Riko Type ECL MR103; Bruel & Kjaer Type 4160, Bruel & Kjaer Types 4144 or 4132 with DB0111 adapter), 50 Hz to 10 000 Hz	7043
25020C	Pressure Response: WE Type 640AA microphones or equivalent (e.g., Tokyo Riko Type ECL MR103; Bruel & Kjaer Type 4160; Bruel & Kjaer Types 4144 or 4132 with DB0111 adapter), 50 Hz to 20 000 Hz	8492
25030C	Pressure Response: Tokyo Riko Type ECL MR112, Bruel & Kjaer Type 4134, or equivalent half-inch microphones, 50 Hz to 10 000 Hz	8202
25040C	Pressure Response: Tokyo Riko Type EC MR112, Bruel & Kjaer Type 4134, or equivalent half-inch microphones, 50 Hz to 20 000 Hz	10356
25060S	Special Tests of Acoustic Devices	At Cost

### **CHAPTER 6** THERMODYNAMIC QUANTITIES

### **A. Pressure Measurements**

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
C. Dawn Cross	(301) 975-4822	christina.cross@nist.gov	NIST
(All Services)		_	100 Bureau Drive, Stop 8364
Kevin Douglass	(301) 975-6489	kevin.douglass@nist.gov	Gaithersburg, MD 20899-8364
(All Services)			-
(29010C, 29030C, 29035C	C, 29040S)		

#### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	
29010C	Deadweight Piston Gages	4550
29020S	Controlled Clearance Piston Gages	At Cost
29030S	Pressure Gages and Transducers	At Cost
290358	Non-mercurial Barometers and Manometers	At Cost
29040S	Special Tests of Pressure Gages	At Cost

Fees are subject to change without notice.

### **B.** Vacuum, Low Pressure and Leak Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Jacob Ricker (30005C)	(301) 975-4475	jacob.ricker@nist.gov	NIST
(30010C-30025C, 30040S	5)		100 Bureau Drive, Stop 8364
Jay H. Hendricks	(301) 975-4836	jay.hendricks@nist.gov	Gaithersburg, MD 20899-8364
(30005C-30025C, 30040S	5)		
James A. Fedchak	(301) 975-8962	james.fedchak@nist.gov	
(30029C-30032S, 30034C	2-30038C, 30050S)		
C. Dawn Cross	(301) 975-4832	christina.cross@nist.gov	
(30060S-30063S, 30062C)	)		

### Please contact the technical staff before shipping instruments or standards to the address listed above.

**NOTE:** 1 Torr = 133.322 Pa

Service ID Number	Description of Services	
30005C	Vacuum, Comparison Calibration	
30010C	One Low-Pressure Transducer Absolute or Differential Relative to Vacuum	2935
300255	Piston Gauges versus an Ultrasonic Interferometer Manometer	At Cost
30029C	Spinning Rotor Gages, below 0.1 Pa, Nitrogen Gas with NIST Controller	3632

30030C	Spinning Rotor Gages, below 0.1 Pa, Nitrogen Gas Customer Controller with IEEE-488	3632
30031C	Spinning Rotor Gages, below 0.1 Pa, Additional Gas	4440
300328	Special Test of Spinning Rotor Gages, Transition Range (above 0.1 Pa)	At Cost
30036C	Ionization Gages, $10^{-7}$ Pa to $10^{-1}$ Pa, Nitrogen Gas	5587
30037S	Ionization Gages, Additional Filament or Gas for Above Tests	At Cost
30040S	Special Tests of Low-Pressure Gages	At Cost
30050S	Special Tests of Vacuum Gages	At Cost
30060S	Special Tests of Leak Artifacts ( $10^{-13}$ mol/s to $10^{-6}$ mol/s)	At Cost
30061C	Helium Leaks, Primary Calibration (10 <sup>-13</sup> mol/s to 10 <sup>-6</sup> mol/s)	2361
30062C	Helium Leaks, Comparison Calibration (10 <sup>-13</sup> mol/s to 10 <sup>-9</sup> mol/s)	1786
30063S	Special Tests of Low-Gas-Flow Instruments	At Cost

**NOTE:** Due to the time and effort required preparing vacuum instrumentation for calibration it is particularly important that they be known to be in proper operating condition when they are submitted to NIST. Equipment will be inspected upon receipt and the customer notified of any obvious damage. If the schedule permits, we will cooperate with the customer's efforts to repair or replace damaged equipment so that the calibration of their equipment can proceed. However, concealed damage or operational deficiencies most likely will not be detected before the instrument is operating on the vacuum system or the calibration has started; in such cases, if the equipment cannot be calibrated, we will charge 20 % of the regular calibration fee for low-pressure transducers and 30 % of the regular fee for spinning rotor and ionization gages.

### C. Laboratory and Industrial-Grade Thermometers

Technical Contact: C. Dawn Cross <u>Telephone:</u> (301) 975-4822

<u>Email:</u> <u>dawn.cross@nist.gov</u> Mailing Address: NIST 100 Bureau Drive, Stop 8363 Gaithersburg, MD 20899-8363

### Please contact the technical staff before shipping instruments or standards to the address listed above.

**NOTE:** NIST no longer calibrates mercury in glass thermometers as of March 1, 2011. Fahrenheit ranges are not direct conversions of the Celsius ranges.

Service ID Number	Description of Services	
31010C	Organic Liquid in Glass Thermometers (0 °C to 200 °C) (32 °F to 392 °F)	
31040C	Organic Liquid in Glass Thermometers (-1 °C to -110 °C) (31 °F to -166 °F)	404/pt
31050C	Organic Liquid in Glass Thermometers (Liquid N <sub>2</sub> ) (-196 °C or -321 °F)	284/pt
31100S	Quantity Tests of Liquid-In-Glass Thermometers	At Cost
31110C	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (0 °C to 150 °C) (32 °F to 300 °F)	165/pt
31200S	Preliminary Examination of Ineligible Thermometer	At Cost
31260S	Special Thermometry Services, by Prearrangement	At Cost

### D. Thermocouples, Thermocouple Materials, Thermometer Indicators

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Karen Garrity	(301) 975-4818	kgarrity@nist.gov	NIST
(32010C-32101C)			100 Bureau Drive, Stop 8363
C. Dawn Cross	(301) 975-4822	dawn.cross@nist.gov	Gaithersburg, MD 20899-8363
(32110C-32120C)			

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Comparison Calibrations, Temperature Measured with Thermocouple (TC)						
Service ID Number	ТС Туре	Temp Range °C	Points	Min. Length (mm)	Temp. (°C)	Fee (\$)
32010C	S	0 to 1450	1 °C or 1 °F Interv. Table	700	0 to 1100 1450	815
32020C	R	0 to 1450	1 °C or 1 °F Interv. Table	700	0 to 1100 1450	815
32030C	В	0 to 1750	1 °C or 1 °F Interv. Table	1000	0 to 800 800 to 1100 1450 1750	1263
32031C	В	800 to 1750	1 °C or 1 °F Interv. Table	1000	800 to 1100 1450 1750	815
32040C	Е	0 to 1000	4 to 15	700	0 to 1000	815
32041C	J	0 to 760	4 to 15	700	0 to 760	815
32042C	K	0 to 1100	4 to 15	700	0 to 1100	815
32043C	Ν	0 to 1100	4 to 15	700	0 to 1100	815
32044C	Т	0 to 400	4 to 15	700	0 to 400	815
32050C	32050C Comparison calibration, two point minimum, per point, for all items above					357/pt
32060C	Each additional table of results at 1 °C or 1 °F intervals, for type S, R, or B at later date				268	
32070C	Thermocouple minimum lengt	materials tested agains	st Pt Thermoelectric s	tandard, 4 to 15 po	ints, 700 mm	1076

	Calibration at Metal Freezing Points, Minimum TC Wire Diameter 0.4 mm, Freezing Point Determination at Au, Ag, Al, and Zn					
Service ID Number	TC Type	Temp Range °C	Points	Min. Length (mm)	Temp. (°C)	Fee (\$)
32090C	S or R	0 to 1450	Table 1 °C or 1 °F Interv. and equations to generate table	1000	at freezing points 0 to 1100 1450	1930
32091C	Type S or	T, freezing point deter	rmination, per point, two poin	nt minimum		566
	Cali	bration of Digital Th	nermometer Indicator or Po	ortable Potentio	meter	
32100C	Indicator or Potentiometer, first dial or range			1234		
32101C	Indicator or Potentiometer, each additional dial or range       67			679		
Compa	Comparison Calibration of Thermocouples or Thermocouple Materials Tested against Pt Thermoelectric Standard, Temperature Measured with Standard Platinum Resistance Thermometer, Minimum TC Wire Length 1.0 m, 2 Point Minimum					
32110C	-	0 °C to 315 °C and Li Expanded Uncertaint	quid N <sub>2</sub> (–196 °C) or –166 °I y 0.4 °C	F to 600 °F and I	Liquid N <sub>2</sub>	420/pt
			rmocouple for any of the fo covered under fee schedule			

**NOTE:** Due to the extra time involved in calibrating sheathed thermocouples, a surcharge of 20 % of the cost of calibrating bare-wire thermocouples will be added to the relevant fees listed above.

### E. Resistance Thermometry

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Weston L. Tew	(301) 975-4811	wtew@nist.gov	NIST
(0.65 K to 84 K)			100 Bureau Drive, Stop 8363
Michal J. Chojnacky	(301) 975-4821	michalc@nist.gov	Gaithersburg, MD 20899-8363
(83 K to 962 °C)			

### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
33010C	Capsule SPRT (13.8 K to 30 °C) e-H <sub>2</sub> to Ga	11125
33020C	Capsule SPRT (13.8 K to 157 °C) e-H <sub>2</sub> to In	11631
33030C	Capsule SPRT (13.8 K to 232 °C) e-H <sub>2</sub> to Sn	12137
33031C	Capsule SPRT (24.5 K to 30 °C) Ne to Ga	8079
33032C	Capsule SPRT (24.5 K to 157 °C) Ne to In	8584

33033C	Capsule SPRT (24.5 K to 232 °C) Ne to Sn	9089
33040C	Capsule SPRT(54 K to 30 °C) O <sub>2</sub> to Ga	6977
33050C	Capsule SPRT (54 K to 157 °C) O <sub>2</sub> to In	7482
33060C	Capsule SPRT (54 K to 232 °C) O <sub>2</sub> to Sn	7986
33065S	Capsule SPRT (83 K to 0.01 °C) Ar to TPW	At Cost
33070C	Capsule SPRT (83 K to 30 °C) Ar to Ga	3596
33080C	Capsule SPRT (83 K to 157 °C) Ar to In	3848
33090C	Capsule SPRT (83 K to 232 °C) Ar to Sn	4291
33100C	Capsule SPRT (0 °C to 30 °C) TPW to Ga	1110
33110C	Capsule SPRT (0 °C to 157 °C) TPW to In	1931
33120C	Capsule SPRT (0 °C to 232 °C) TPW to Sn	2663
33130C	Capsule SPRT (234 K to 30 °C) Hg to Ga	2632
33140C	Rhodium-Iron or Platinum-Cobalt Resistance Thermometers (0.65 K to 24.6 K)	12818
33141C	Rhodium-Iron or Platinum-Cobalt Resistance Thermometers (0.65 K to 83.8 K)	15429
33142C	n-Type Germanium Resistance Thermometers (0.65 K to 24.6 K)	13009
33150C	Long Stem SPRT (83 K to 0.01 °C) Ar to TPW	2903
33160C	Long Stem SPRT (83 K to 30 °C) Ar to Ga	3282
33170C	Long Stem SPRT (83 K to 157 °C) Ar to In	3584
33180C	Long Stem SPRT (83 K to 232 °C) Ar to Sn	3888
33190C	Long Stem SPRT (83 K to 420 °C) Ar to Zn	4189
33200C	Long Stem SPRT (83 K to 661 °C) Ar to Al	5237
33210C	Long Stem SPRT (234 K to 30 °C) Hg to Ga	2480
33220C	Long Stem SPRT (234 K to 157 °C) Hg to In	2782
33230C	Long Stem SPRT (234 K to 232 °C) Hg to Sn	3086
33240C	Long Stem SPRT (234 K to 420 °C) Hg to Zn	3388
33250C	Long Stem SPRT (234 K to 661 °C) Hg to Al	4436
33260C	Long Stem SPRT (0 °C to 30 °C) TPW to Ga	1022
33270C	Long Stem SPRT (0 °C to 157 °C) TPW to In	1325
33280C	Long Stem SPRT (0 °C to 232 °C) TPW to Sn	1628
33290C	Long Stem SPRT (0 °C to 420 °C) TPW to Zn	1931
33300C	Long Stem SPRT (0 °C to 661 °C) TPW to Al	2978

Fee Schedule 2017

33310C	Long Stem SPRT (0 °C to 962 °C) TPW to Ag	7862
33330C	Additional Copy of Table from Results of 33010C–33310C at a Later Date	275
33340C	Minimum Charge for Unsuitable Thermometer	1223
33350S	Special Tests of Resistance Thermometers	At Cost
33355S	Special Tests of Cryogenic Resistance Thermometers	At Cost
33360S	Special Tests of Thermometric Fixed-Point Devices	At Cost
33370M	Measurement Assurance Program for Temperature 83 K to 420 °C (Ar to Zn)	14657
33380M	Measurement Assurance Program for Temperature 83 K to 661 °C (Ar to Al)	17431

### F. Radiance Temperature Measurements

<b>Technical Contact:</b>		<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Charles E. Gibson		(301) 975-2329	cgibson@nist.gov	NIST
	Fax:	(301) 869-5700		100 Bureau Drive, Stop 8441
				Gaithersburg, MD 20899-8441

Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)		
Calibration	Calibration reports are issued giving the radiance temperature of the lamp at 655.48 nm versus the lamp current			
35050C	Radiance Temperature Standard, Tungsten Strip Lamp (800 °C to 2300 °C, 6 to 16 points)	11005		
35051C	Recalibration of Tungsten Strip Lamp (800 °C to 2300 °C, 6 to 16 points)	9181		
35060C	Radiance Temperature Standard, Tungsten Strip Lamp (800 °C to 2300 °C, 5 or fewer points)	6901		
35061C	Recalibration of Tungsten Strip Lamp (800 °C to 2300 °C, 5 or fewer points)	5533		
	Calibration reports are issued giving the radiance temperature of the reference blackbody at 655.48 nm, 900 nm or 1000 nm versus the display reading, output current, or output voltage			
35070S	Special Tests of Radiation Thermometers (800 °C to 2700 °C)	At Cost		
35071C	Radiance Temperature Standard, Radiation Thermometer (800 °C to 2700 °C, 6 to 20 points)	9181		
35072C	Radiance Temperature Standard, Radiation Thermometer (800 °C to 2700 °C, 5 or fewer points)	4621		
Calibration reports are issued giving the thermodynamic temperature of the reference blackbody versus the radiation thermometer display reading, output current, or output voltage.				
35080S	Special Tests of Radiation Thermometers (-46 °C to 900 °C)	At Cost		
35085C	Radiance Temperature Standard, Radiation Thermometer (-46 °C to 900 °C, 3 points)	4478		
------------	--	---------	--	--
35086C	Radiance Temperature Standard, Radiation Thermometer (-46 °C to 900 °C, Each additional point when ordered with 35085C)			
Calibratio	Calibration reports are issued giving the thermodynamic temperature of the reference blackbody versus the test blackbody source display reading.			
35090S	Special Tests of Blackbody Sources (-46 °C to 900 °C)	At Cost		
Calibrat	Calibration reports are issued giving heat flux at the sensor surface versus the output voltage.			
35100S	Special Tests of Radiative Heat Flux Sensors	At Cost		
35101C	Radiative Heat Flux Sensors (1 W/cm <sup>2</sup> to 5 W/cm <sup>2</sup> , 9 points, Gardon and Schmidt-Boelter type sensors)	3025		
35102C	Additional Radiative Heat Flux Sensor (same model as 35101C)	2113		

Calibration Schedule: Requests for calibration services are scheduled after receipt of a purchase order.

## **G.** Humidity Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email</u>	Mailing Address:
Tobias Herman	(301) 975-4808	tobias.herman@nist.gov	NIST
	(301) 975-2626		100 Bureau Drive, Stop 8363
Gregory E. Scace	(301) 975-2626	gregory.scace@nist.gov	Gaithersburg, MD 20899-8363
			Fax: (301) 548-0206

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
36070S	Special Tests of Humidity	At Cost

Fees are subject to change without notice.

## **H.** Thermal Resistance Measurements

<b>Technical Contact:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Robert Zarr	(301) 975-6436	robert.zarr@nist.gov	NIST
			100 Bureau Drive, Stop 8632

100 Bureau Drive, Stop 8632 Gaithersburg, MD 20899-8632 **Fax:** (301) 975-5433

Service ID Number	Material	Specimen Thickness (mm)	Mean Temp. (K)	Temp. Difference (K)	Relative Expanded Uncertainty k = 2 (%)	Fee (\$)
----------------------	----------	-------------------------------	----------------------	----------------------------	---	----------

36110C	Fibrous glass blanket	25	297	22 or 28	1.0	3412/pt
36120C	Fibrous glass blanket	75	297	22 or 28	1.5	3412/pt
36130C	Fibrous glass blanket	150	297	22 or 28	2.5	3412/pt
36140C	Fibrous glass blanket	225	297	22 or 28	3.0	3412/pt
36150C	Quantity Tests of Fibrous glass blanket		297	22 or 28		At Cost
36199S	Special Tests of Thermal Insulation		280 to 330	22 or 28		At Cost

# **CHAPTER 7** OPTICAL RADIATION MEASUREMENTS

## A. Photometric Measurements

Technical Contact:	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Yuqin Zong	(301) 975-2332	yuqin.zong@nist.gov	NIST
Maria Nadal	(301) 975-4632	maria.nadal@nist.gov	100 Bureau Drive, Stop 8442
Cameron Miller	(301) 975-4713	cameron.miler@nist.gov	Gaithersburg, MD 20899-8442
		-	Fax: (301) 840-8551

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
37010C	Luminous Intensity and Color Temperature Standard Lamps	4506
370208	Special Tests for luminous Intensity and Color Temperature of Submitted Lamps	At Cost
37030C	Color Temperature Standard Lamps	3703
37040C	Each Additional Color Temperature for 37030C	602
37050S	Special Tests for Color Temperature of Submitted Lamps	At Cost
37060S	Special Tests for Total Luminous Flux of Submitted Incandescent Lamps and Florescent Lamps	At Cost
37070C	Opal Glass Luminance Coefficient Standards	3121
37080S	Special Tests for Submitted Luminance Sources and Transmitting Diffusers	At Cost
37090S	Special Tests for Photometers, Illuminance Meters and Luminance Meters	At Cost
37100S	Special Photometric Tests	At Cost
37110S	Special Tests for Submitted Flashing-Light Photometers	At Cost
37130S	Special Tests for Luminous Intensity and Luminous Flux of LEDs	At Cost
37220M	Luminous Intensity Measurement Assurance Program	3713
37230M	Solid-state Lighting Measurement Assurance Program	4216
37240M	Solid-state Lighting and Compact Fluorescent Lamp Measurement Assurance Program	5622
37250M	Total Radiant Flux Measurement Assurance Program	4718

## **B.** Ozone Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
James Norris	(301) 975-3936	james.norris@nist.gov	NIST
			100 D D' C

100 Bureau Drive, Stop 8393 Gaithersburg, MD 20899-8393

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
37510C	Ozone Instrument Calibrations	2408
37515S	Additional Special Tests for Ozone Instruments	At Cost
37520C	NIST Standard Reference Photometer (NIST SRP)	90684
375258	NIST Standard Reference Photometer Maintenance	At Cost
37530C	Validation of NIST Standard Reference Photometer (NIST SRP)	5110
37540C	Certification of Mercury Calibration Gas Generator	5112
375358	Additional Special Tests for Validation of NIST Standard Reference Photometer (NIST SRP)	At Cost

Fees are subject to change without notice.

## C. Optical Properties of Materials Measurements

<u>Technical Contacts:</u> Catherine Cooksey	<u>Telephone:</u> (301) 975-6208	Email: catherine.cooksey@nist.gov	<u>Mailing Address:</u> NIST
(38020C-38061S)			100 Bureau Drive, Stop 8442
Melody Smith (38065C–38070S)	(301) 975-8533	melody.smith@nist.gov	Gaithersburg, MD 20899-8442 Fax: (301) 840-8551

Service ID Number	Description of Services	Fee (\$)
38020C	Spectral Transmittance Filters (Copper Green Glass)	3688
38060S	Special Tests of Spectral Reflectance (250 nm to 2500 nm)	At Cost
38061S	Special Tests of Spectral Transmittance and Index of Refraction (120 nm to 2500 nm)	At Cost
38065C	Recertification of NIST photometric Standard Reference Materials SRM 930, SRM 1930, or SRM 2930	1550
38066C	Recertification of NIST photometric Standard Reference Material SRM 2031	2158
38067C	Recertification of NIST photometric Standard Reference Material SRM 2030	1145

38068C	Replacement filter for NIST photometric Standard Reference Materials SRM 930, SRM 1930, SRM 2030 or SRM 2930	1274
38069C	Replacement filter for NIST photometric Standard Reference Material SRM 2031	1695
38070S	Special tests of transmittance and special requests/handling of UV/visible	At Cost

## **D.** Surface Color and Appearance

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Maria E. Nadal	(301) 975-4632	maria.nadal@nist.gov	NIST
(38090S and 38091S)			100 Bureau Drive, Stop 8442
Martin Wilson	(301) 975-2356	martin.wilson@nist.gov	Gaithersburg, MD 20899-8442
(38100C-38130C)			Fax: (301) 840-8551

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
38090S	Specular Gloss	At Cost
38091S	Special Test of 0°/45° Surface Color	At Cost
38100C	X-Ray Film Step Tablet Transmission Density Standard (Replacement for SRM 1001)	1088
38110C	Recalibration of an X-Ray Film Step Tablet Transmission Density Standard	1197
38120C	Photographic Film Step Tablet Transmission Density Standard (Replacement for SRM 1008)	1268
38130C	Recalibration of a Photographic Film Step Tablet Transmission Density Standard	1358

Fees are subject to change without notice.

## E. Spectroradiometric Measurements

## **E.1 Spectroradiometric Source Measurements**

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing/Shipping Address:
Charles E. Gibson	(301) 975-2329	cgibson@nist.gov	NIST
(39010C-39060S)			100 Bureau Drive, Stop 8441
Jeanne M. Houston	(301) 975-2327	jeanne.houston@nist.gov	Gaithersburg, MD 20899-8441
(39071C-39081S)			Fax: (301) 869-5700
Thomas C. Larason	(301) 975-2334	tlarason@nist.gov	
(39080S, 39081S, 39100S	, 39300S, 39310C)		
George Eppeldauer	(301) 975-2338	geppeldauer@nist.gov	
(39090S)			

	E.1 Spectroradiometric Source Measurements	
Service ID Number	Description of Services	Fee (\$)
NIST c	alibrates and issues a type 30A/T24/13 tungsten strip lamp with a mogul bi-pos	t base.
39010C	Spectral Radiance Standard, Tungsten Strip Lamp (225 nm to 2400 nm) (other spectral ranges are available under no. 39060S)	15850
NIST ca	alibrates customer supplied integrating sphere sources and maps the source ap	erture.
39020C	Spectral Radiance Standard, Integrating Sphere Source (300 nm to 1000 nm in 25 nm steps)	7585
39021C	Spectral Radiance Standard, Integrating Sphere Source (300 nm to 2400 nm in 25 nm steps)	11690
NIST c	alibrates and issues an 1000 W, tungsten quartz-halogen lamp mounted in a mo bi-post base. The calibrations are performed at 50 cm.	edium
39030C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 450 nm)	9576
39031C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 450 nm)	5760
39032C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (350 nm to 800 nm)	9576
39033C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (350 nm to 800 nm)	5760
39040C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 1600 nm)	11855
39041C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 1600 nm)	8042
39045C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 2400 nm)	14581
39046C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 2400 nm)	10778
NIST	calibrates and issues a 30 W deuterium arc lamp mounted in a medium bi-post	base.
39050C	Spectral Irradiance Standard, 30W Deuterium Arc Lamp (200 nm to 400 nm)	13196
39051C	Recalibration of 30 W Deuterium Arc Lamp (200 nm to 400 nm)	8954
39060S	Special Tests of Radiometric Sources	At Cost
	E.2 Spectroradiometric Detector Measurements	•
39071C	UV Silicon Photodiodes	1610
39072C	Recalibration of UV Silicon Photodiodes	1393
39073C	Visible to NIR Silicon Photodiodes	4779
39074C	Recalibration of Visible to NIR Silicon Photodiodes	3212
390758	Special Tests of NIR Photodiodes	At Cost
39077C	UV to Near-Infrared Silicon Photodiodes (Hamamatsu S2281)	5680

39078C	Recalibration of UV to Near-Infrared Silicon Photodiodes (Hamamatsu S1337–1010BQ or S2281)	4015
39080S	Special Tests of Radiometric Detectors	At Cost
39081S	Special Tests of Photodetector Responsivity Spatial Uniformity	At Cost
39090S	Special Tests of IR Detectors	At Cost
39100S	Special Tests of Irradiance Detectors	At Cost
39200S	Special Tests of Aperture Area	At Cost
39300S	Special Tests of Current-to-Voltage Converters	At Cost
39310C	Gain and Linearity of Current-to-Voltage Converters	2037

## F. Radiometric Standards in the Ultraviolet

<u>Technical Contact:</u> Robert E. Vest	<u>Telephone:</u> (301) 975-3992	Email: rvest@nist.gov	<u>Mailing Address:</u> NIST 100 Bureau Drive, Stop 8411 Gaithersburg, MD 20899-8411
Charles S. Tarrio	(301) 975-3737	ctarrio@nist.gov	NIST
Steven Grantham	(301) 975-5528	grantham@nist.gov	100 Bureau Drive, Stop 8410
Thomas B. Lucatorto	(301) 975-3734	tlucatorto@nist.gov	Gaithersburg, MD 20899-8410

Please contact the technical staff before shipping instruments or standards to the address listed above.

Standard Detectors in the Far Ultraviolet			
Service ID Number	Description of Services	Fee (\$)	
40710C	EUV Detector Calibration	633	
40711C	Detector Responsivity Calibration (5 nm to 17 nm)	1441	
40712C	Detector Responsivity Calibration (18 nm to 49 nm)	1441	
40713C	Detector Responsivity Calibration (52 nm to 122 nm)	760	
40714C	Detector Responsivity Calibration (116 nm to 254 nm)	760	
40790C	New Al <sub>2</sub> O <sub>3</sub> Photoemissive Transfer Standard Detector	508	
40791C	New Si Transfer Standard Photodiode	1215	
40799S	Special Test in the Extreme Ultraviolet	At Cost	

#### G. Laser and Optoelectronic Components Used with Lasers

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:			
Marla Dowell	(303) 497-7455	marla.dowell@nist.gov	NIST			
(General Technical Inquin	ries)		325 Broadway, MC 815.01			
Paul D. Hale	(303) 497-5367	hale@boulder@nist.gov	Boulder, CO 80305-3328			
(High Speed Measuremer	nts)					
Paul Williams	(303) 497-3805	paul.williams@nist.gov				
(Laser Radiometry)						
Bill Swann	(303) 497-7381	william.swann@nist.gov				
(Optical Fiber and Component Measurements - other than Fiber Power)						
Administrative and Logistics:						
John Lomax	(303) 497-3842	john.lomax@boulder.nist.go	V			

John Lomax FAX: (303) 497-4286

Service ID Number	Description of Services	Fee (\$)
	Laser Power and Energy Meter (or Detector) Calibrations at a Single Standard Wavelength and Power (See Table 4)	
42110C	CW Laser Power below 2 Watts	3786
42230C	Pulsed Laser Energy (Q-switched YAG) at 1064 nm	5308
42240C	CW Laser Power at 1064 nm above 2 Watts and 10.6 µm	6370
42250C	Pulsed Laser Energy (Excimer) at 248 nm and 193 nm	6068
	Same as 42110C, Additional Standard Wavelengths or Powers (See Table	e 4)
42111C	CW Laser Power below 2 Watts	1663
42231C	Pulsed Laser Energy (Q-switched YAG) at 1064 nm	3451
42241C	CW Laser Power at 1064 nm above 2 Watts and 10.6 µm above 1 Watt	4778
42251C	Pulsed Laser Energy (Excimer) at 248 nm and 193 nm	4267
42120M	Laser Power and Energy Measurement Assurance Program (MAP)	At Cost
42130C	Optical Fiber Power Meter (or Detectors Used with Lasers) Calibrations at a Single Standard Wavelength and Connector Type (See Table 5)	3553
42131C	Same as 42130C, Additional Standard Wavelengths or Connector Types (See Table 5)	1291
42140M	Optical Fiber Power Meter Measurement Assurance Program (MAP)	At Cost
42150M	Low-Level Laser Measurement Assurance Program (MAP)	At Cost
42151S	Low-Level Laser Radiometer Calibration	At Cost
42155C	Calibration Service of Optoelectronic Frequency Response for Combined Photodiode/RF Power Sensor Transfer Standards	At Cost

42161S	Special Test for Impulse Response Measurements of Detectors Used with Lasers	At Cost
42162S	Special Test for High Accuracy Laser and Optical Fiber Power Measurements	At Cost
42164C	Spectral Responsivity Measurements of Laser and Optical Fiber Power Meters (or Detectors Used with Lasers)	3185
42165S	Special Test for Spatial Uniformity of Laser and Optical Fiber Power Meters and Detectors Used with Lasers	At Cost
42166C	Calibration for Linearity Measurements of Optical Fiber Power Meters (or Detectors Used with Lasers)	2422
42167S	Special Test for Linearity Measurements of High-Power Laser Power Meters (or Detectors Used with Lasers)	At Cost
42170S	Special Test for General Laser Measurements, by Prearrangement	At Cost
42180S	Special Test for General Optical Fiber Power Measurements, by Prearrangement	At Cost
42190S	Special Test for Optical Fiber and Fiber Component Measurements (other than Fiber Power), by Prearrangement	At Cost
42210C	Spectral Responsivity Measurements with Curve Fitting of Laser and Optical Meters (or Detectors used with Lasers)	4113
422208	Calibration Service for Instruments that Measure Laser Beam Diameter	At Cost

# **CHAPTER 8** IONIZING RADIATION MEASUREMENTS

## A. Radioactivity Sources

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Lisa R. Karam	(301) 975-5561	lisa.karam@nist.gov	NIST
(All Services)			100 Bureau Drive, Stop 8462
M.P. Unterweger	(301) 975-5536	munterweger@nist.gov	Gaithersburg, MD 20899-8462
(43030C, 43040C, 43070S	5, 43090S)		Attn: Jeffrey Cessna
Jeffrey T. Cessna	(301) 975-5539	jcessna@nist.gov	
(43010C, 43020C, 43060C	C, 43070S)		
Lynne King	(301) 975-5544	lynne.king@nist.gov	
(43030C, 43040C, 43070S	, 43090S)		

## Administrative and Logistics:

Jeffrey Cessna (301) 975-5539 jcessna

jcessna@nist.gov

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
43010C	Gamma-Ray-Emitting Radionuclides in Solution (Half Lives Greater than 15 Days)	3701
43020C	Gamma-Ray-Emitting Radionulcides in Solution (Half Lives Less than 15 Days)	5970
43030C	Alpha- and Beta-Particle-Emitting Solid Sources, NIST 2 $\pi\alpha/\beta$ Proportional Counter	2849
43040C	Beta-Particle-Emitting Solid Sources (Activity), NIST 2 $\pi\alpha/\beta$ Proportional Counter	4170
43050C	Mixed Alpha-Emitting Solid Sources, NIST 2 $\pi\alpha/\beta$ Proportional Counter in Conjunction with a Solid State Detector	4489
43060C	Beta-Particle-Emitting Solution Sources, Liquid Scintillation Counting	6713
43070S	Special Tests of Beta-Particle-Emitting Solution Sources, Other Techniques	At Cost
43090S	Special Tests of Alpha-Particle-Emitting Solid Sources	At Cost

## **B.** Neutron Sources and Neutron Dosimetry

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
M. Scott Dewey	(301) 975-4843	mdewey@nist.gov	NIST
(All Services Except 440	60C)		100 Bureau Drive, Stop 8461
Alan K. Thompson	(301) 975-4666	alan.thompson@nist.gov	Gaithersburg, MD 20899-8461
(44060C, 44100S)			

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
44010C	Radioactive Neutron Sources Emission Rates $(10^5 \text{ s}^{-1} \text{ to } 10^9 \text{ s}^{-1})$	7111
44020C	Radioactive Neutron Sources Emission Rates ( $10^8 \text{ s}^{-1}$ to $10^{10} \text{ s}^{-1}$ )	7111
44060C	Personnel Protection Instrumentation, Californium Source Bare and Moderated	At Cost
44070C	Activation Detector Dosimetry, Thermal Neutrons	At Cost
44080C	Activation Detector Dosimetry, Californium Fission Neutrons	At Cost
44090C	Activation Detector Dosimetry, <sup>235</sup> U Cavity Fission Sources	At Cost
44100S	Special Tests of Neutron Sources and Dosimeters	At Cost

Fees are subject to change without notice.

## C. Dosimetry of X-Rays, Gamma-Rays, and Electrons

## C.1 X-Ray and Gamma-Ray Measuring Instruments

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Michelle O'Brien	(301) 975-2014	michelle.obrien@nist.gov	NIST
(46010C-46050S)			100 Bureau Drive, Stop 8460
Ronaldo Minniti	(301) 975-5586	ronaldo.minniti@nist.gov	Gaithersburg, MD 20899-8460
(46010C-46110C)			Fax: (301) 869-7682
Michael G. Mitch	(301) 975-5491	michael.mitch@nist.gov	
(46010C-47040S)			

C.1 X-Ray and Gamma-Ray Measuring Instruments					
Service ID Number	Description of Services	Fee (\$)			
	Air-Kerma (Exposure)				
46010C	Radiation Detectors—Calibration in <sup>60</sup> Co and <sup>137</sup> Cs Gamma-Ray Beams, per Detector, per Set-Up, per Beam Code	2564			
46011C	Radiation Detectors—Calibration in X-Ray Beams (see Tables 6, 7 and 8), per Detector, per Set-Up, per Beam Code	2263			

46012C	Well-ionization Chamber for one Model S700 Electronic Brachytherapy Source	6323
46013C	Each Additional Model S700 Electronic Brachytherapy Source Submitted With Same Well-ionization Chamber for 46012C	3319
46020C	Passive Dosimeters—Irradiation of Up to Six, One Beam Quality at One Set-up	2764
46021C	Up to Six Additional Dosimeters at Same Set-up and Beam Quality	1740
46030C	High-Gain Electrometers - Charge Sensitivity, One Set of Switch Positions, with 46010C/46011C, by Prearrangement	1785
46040S	Special Tests of kV Measuring Devices	At Cost
46050S	Special Tests of X-Ray and Gamma-Ray Measuring Instruments	At Cost
	Absorbed Dose to Water From <sup>60</sup> Co Beam	
46110C	Radiation Detectors - Calibration in a <sup>60</sup> Co Gamma-Ray Beam	3245
C.2	Sealed Gamma-Ray Sources or Beta-Particle Sources, and Measuring Instrume	ents
47010C	Gamma-Ray Sources Similar to NIST Standards - ${}^{60}$ Co to ${}^{137}$ Cs, Having Air-Kerma Strengths 10 $\mu$ Gy m <sup>2</sup> /h to 1500 $\mu$ Gy m <sup>2</sup> /h; and ${}^{192}$ Ir Sources of the Same Type Used to Calibrate Reentrant Chamber, Having Air-Kerma Strengths 0.1 $\mu$ Gy m <sup>2</sup> /h to 30 $\mu$ Gy m <sup>2</sup> /h	5505
47011C	Each Additional Gamma-Ray Source of Same Radionuclide	5299
47020C	$^{125}$ I or $^{103}$ Pd Sources: Seeds Having Air-Kerma Strengths 0.5 $\mu$ Gy m <sup>2</sup> /h to 100 $\mu$ Gy m <sup>2</sup> /h	4128
47021C	Each Additional <sup>125</sup> I or <sup>103</sup> Pd Source of Same Radionuclide/Design Submitted with Above	4002
47035C	Beta-Particle Sources Calibrated for Radiation Protection	1338
47036C	Ionization Chamber Calibrated with Beta-Particle Sources for Radiation Protection	1338
47040S	Special Tests of Gamma-Ray and Beta-Particle Sources	At Cost

# **D.** Dosimetry for High-Dose Applications

## **D.1 Dosimetry of High-Energy Electron Beams**

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Lonnie Cumberland	(301) 975-6869	lonnie.cumberland@nist.gov	NIST
Michael G. Mitch	(301) 975-5491	michael.mitch@nist.gov	100 Bureau Drive, Stop 8460
			Gaithersburg, MD 20899-8460

Service ID Number	Description of Services			
	D.1 Dosimetry of High-Energy Electron Beams			
48010M	Dose Interpretation of NIST-Packaged Dosimeters Irradiated by Customer - Two Dosimeters	1721		
48011M	Each Additional Dosimeter	788		
48020S	Special Tests of Electron-Beam Dosimeters	At Cost		

<b>D.2</b> Dosimetry of Photon Beams				
49010C	First Irradiation of a Customer Supplied Dosimeter with <sup>60</sup> Co Gamma-Rays	1589		
49011C	Each Additional Irradiation at Ambient (20 °C to 30 °C) Temperatures	165		
49015C	Setup for Each Non-Ambient Irradiation Temperature (-77 °C to +19 °C and +31 °C to +70 °C)	497		
49016C	Each Additional Irradiation at Non-Ambient Temperature Under 49015C	242		
49020C	Dose Measurement Session of 1 NIST Transfer Dosimeter and Certificate	1669		
49021C	Additional Measurement Session of 1 NIST Transfer Dosimeter, Same Certificate with 49020C	777		
49022C	Additional Measurement of 1 NIST Transfer Dosimeter, Same Session	165		
49030C	Dose Measurement Session of 1 Dosimeter and 90 Day Summary Certificate	1389		
49031C	Additional Measurement Session of 1 Dosimeter, Same Certificate with 49030C	394		
49032C	Additional Measurement of 1 Dosimeter, Same Session	67		
49050S	Special Measurement Services for Dosimeter Response and Dose Distributions	At Cost		

# **CHAPTER 9** ELECTROMAGNETIC MEASUREMENTS

## **A. Resistance Measurements**

#### A.1 DC Resistance Standards and Measurements

<u>Technical Contacts:</u> Randolph E. Elmquist Marlin E. Kraft	<u>Telephone:</u> (301) 975-6591 (301) 975-4239	<u>Email:</u> relmquist@nist.gov marlin.kraft@nist.gov	<u>Mailing Address:</u> NIST 100 Bureau Drive, Stop 8170 Gaithersburg, MD 20899-8170			
Administrative and Logi	Administrative and Logistics:					

Denise D. Prather (301) 975-4221 dprather@nist.gov

#### Please contact the technical staff before shipping instruments or standards to the address listed above.

Calibration fees are the most critical element in funding the metrology services that we provide, and represent the direct cost of providing calibration services for dc resistors and shunts. These services often reach beyond traceability to include detailed consultation. Currently our fees also must recover some of the rapidly increasing costs of providing year-round, readily accessible services and maintaining state-of-the-art traceability through the quantum Hall effect standard. Customers of our most critical calibration services, NIST Service ID numbers 51130C and 51131C, have benefited the most from our efforts to reduce turn-around time through automation, and to provide the world's best level of uncertainty, while keeping these test fees at a reasonable level.

Service ID Number	Description of Services	Fee (\$)
51100S	Special Resistance Measurements Services, by Prearrangement	At Cost
51110M	Measurement Assurance Program for Resistance	At Cost
51130C	Standard Resistor, Thomas-Type, 1 $\Omega$	3572
51131C	Standard Resistor, Evanohm Wirewound High Precision, 10 k $\Omega$	3503
51132C	Standard Resistor, Four-Terminal 0.0001 $\Omega$	2791
51133C	Standard Resistor, Four-Terminal 0.001 $\Omega$	2351
51134C	Standard Resistor, Four-Terminal 0.01 $\Omega$	2357
51135C	Standard Resistor, Four-Terminal 0.1 $\Omega$	1721
51136C	Standard Resistor, Four-Terminal 1 $\Omega$	1721
51137C	Standard Resistor, Four-Terminal 10 Ω	1721
51138C	Standard Resistor, Four-Terminal 100 $\Omega$	1721
51139C	Standard Resistor, Four-Terminal 1 kΩ	1721
51140C	Standard Resistor, 10 kΩ	2225
51141C	Standard Resistor, 100 kΩ	2651
51142C	Standard Resistor, 1 MΩ	2651

Fee Schedule 2017

51143C	Standard Resistor, $10 \text{ M}\Omega$	3344
51144C	Additional Voltage, 10 MΩ	2645
51145C	Standard Resistor, 100 M $\Omega$	3344
51146C	Additional Voltage, 100 MΩ	2645
51147C	Standard Resistor, 1 GΩ	3344
51148C	Additional Voltage, 1 GΩ	2645
51149C	Standard Resistor, 10 GΩ	4412
51150C	Additional Voltage, 10 GΩ	3466
51151C	Standard Resistor, 100 G $\Omega$	4412
51152C	Additional Voltage, 100 GΩ	3466
51153C	Standard Resistor, 1 TΩ	4618
51154C	Additional Voltage, 1 TΩ	3466
51160C	Standard Resistor for Current Measurements (Shunts) with all determinations at 300 A or Below, One Range, One Current Level	1933
51161C	Standard Resistor for Current Measurements (Shunts), with At Least One Determination Above 300 A (maximum current 2000 A), One Range, One Current Level	1933
51162C	Standard Resistor for Current Measurements (Shunts), Additional Range of a Multi-Range Resistor	492
51163C	Standard Resistor for Current Measurements (Shunts), Additional Determination at Another Current Level	492

## A.2 High-Voltage Standard Resistors

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Gerald J. FitzPatrick	(301) 975-8922	gfitzpatrick@nist.gov	NIST
		• •	100 Dunnen Duine Ster 9170

100 Bureau Drive, Stop 8170 Gaithersburg, MD 20899-8170

## Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

Service ID Number	Description of Services	Fee (\$)
51210C	High-Voltage Standard Resistors	4182

# **B.** Impedance Measurements (Except Resistors)

## **B.1** Low-Frequency Capacitance and Inductance Measurements and Standards

ldress:
Drive, Stop 8170
g, MD 20899-8170

## Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

Service ID Number	Description of Services	Fee (\$)
521008	Special Four Terminal-Pair (4TP) Capacitance and Dissipation Factor Characterization	At Cost
52110S	Special LF Capacitance Measurements, by Prearrangements	At Cost
521208	Special Measurement Assurance Program for Standard Capacitors (100 pF and 1000 pF, at a Frequency of 1000 Hz)	At Cost
52130C	Fixed, Fused-Silica Dielectric Standard Capacitors (1, 10, and 100) pF, at a Frequency of (100, 400, or 1000) Hz	4305
52131C	Additional Measurement at One of the Above Frequencies	451
52140C	Fixed Three-Terminal, High-Precision Nitrogen Dielectric Standard Capacitors with Coaxial Connectors, Small Uncertainty, (10, 100 and 1000) pF, at a Frequency of (100, 400, or 1000) Hz	2826
52141C	Additional Measurement at One of the Above Frequencies	402
52150C	Physical Tests for Three-Terminal Standard Capacitors with Coaxial Connectors, Large Uncertainty (0.001 pF to 10 000 pF) at a Frequency of (100, 400, or 1000) Hz	2607
52160C	Fixed Three-Terminal Standard Capacitors with Coaxial Connectors, Large Uncertainty (0.001 pF to 10 000 pF) at a Frequency of (100, 400, or 1000) Hz	1790
52161C	Additional Measurement at One of the Above Frequencies	402
52170C	Two- or Three- Terminal Mica Dielectric Standard Capacitors with Binding Post Connectors (0.001 $\mu$ F to 1 $\mu$ F), at a Frequency of (66, 100, 400, 1000 or 10 000) Hz	3072
52171C	Additional Measurement at One of the Above Frequencies	2523
52176C	Two-Terminal Standard Capacitors with Precision High Frequency (HF) Coaxial Connectors (0.001 pF to 10 000 pF), at a Frequency of 1000 Hz	402
52180C	Fixed Standard Inductors (0.00005 H to 10 H), at a Frequency of (100, 400, 1000, or 10 000) Hz	1839
52181C	Additional Measurement at One of the Above Frequencies	1635

52190S	Special LF Inductance Measurements, by Prearrangement	At Cost
--------	---	---------

#### **B.2 High-Frequency Standard Capacitors and Inductors**

Technical Contacts: Ronald A. Ginley	<u>Telephone:</u> (303) 497-3634	Email: rginley@boulder.nist.gov	Mailing Address: NIST M.C. 818.01 325 Broadway Boulder, CO 80305-3325

#### Administrative and Logistics:

Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov

(301) 975-4221

#### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
522108	Two-Terminal Low-Loss Standard Capacitors - 10 kHz to 250 MHz; 1 pF to 20 pF	At Cost
522118	Two-Terminal Low-Loss Standard Capacitors (High Accuracy) - 10 kHz to 30 MHz, (50, 100, 200, 500, and 1000) pF	At Cost
522218	Three-Terminal Low-Loss Standard Capacitors (High Accuracy) - 10 kHz to 10 MHz, $(10^{-2}, 10^{-1}, 1, 10, 10^2, \text{ and } 10^3) \text{ pF}$	At Cost
52310S	Two-Terminal, High-Q Standard Inductors ( $10^{-2} \mu H$ to 1 H)	At Cost

## **B.3 Power-Frequency Capacitors**

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Gerald J. FitzPatrick	(301) 975-8922	gfitzpatrick@nist.gov	NIST
			100 Bureau Drive, Stop 8170
			Gaithersburg, MD 20899-8170

#### Administrative and Logistics:

Denise D. Prather

dprather@nist.gov

Please contact the technical staff before shipping instruments or standards to the address listed above.

#### B.4 Q-Standard

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Ronald A. Ginley	(303) 497-3634	rginley@boulder.nist.gov	NIST
			M.C. 818.01
			325 Broadway
			Boulder, CO 80305-3325
Administrative and Log	gistics:		
Puanani L. DeLara	(303) 497-3753	calibration@boulder.nist.gov	

Service ID Number	Description of Services	Fee (\$)
52710S	Inductive Q-Standards; 50 kHz to 45 MHz, 0.25 µH to 25 mH	At Cost
52711S	Each Additional Frequency for 52710C	At Cost

## **C.** Voltage Measurements

## C.1 DC Voltage Measurements and Standards

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Yi-Hua Tang	(301) 975-4691	ytang@nist.gov	NIST
			100 Bureau Drive, Stop 8170
			Gaithersburg, MD 20899-8170

## Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
53110S	Special DC Voltage Measurements, by Prearrangement	At Cost
53160C	Tests of Solid-State Voltage Reference Standard (1 Output, 1 V to 10 V)	2311
53161C	Each Additional Output	1472
53180S	Special Handling (Equipment Pickup or Delivery)	267
53190S	Special Handling (Cleaning, Minor Repair, Return Service Charge)	543

## C.2 AC Voltage Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Bryan C. Waltrip	(301) 975-2438	bwaltrip@nist.gov	NIST
Richard L. Steiner	(301) 975-4226	richard.steiner@nist.gov	100 Bureau Drive, Stop 8170
			Gaithersburg, MD 20899-8170

## Administrative and Logistics:

Denise D. Prather (301) 975-4221

dprather@nist.gov

#### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
532008	Special Tests of High-Accuracy Digital Multimeters, Multifunction Calibrators, by Prearrangement	At Cost
53201S	Special Tests of Low-Voltage AC-DC Transfer Standards, by Prearrangement	At Cost
53202C	25-Point Test of Digital Multimeters (DMMs), by Prearrangement	4333
53203S	Each Additional DMM Test Point for 53202S	At Cost

Fees are subject to change without notice.

## C.3 AC-DC Thermal Voltage and Current Converters (to 1 MHz)

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Thomas E. Lipe	(301) 975-4251	tlipe@nist.gov	NIST
-			Duilding 220 Doom D1

Building 220, Room B146 100 Bureau Drive, Stop 8170 Gaithersburg, MD 20899-8170

## Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

#### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
53310S	Special AC-DC Measurement Services, by Prearrangement	At Cost
53350C	Set-up Charge (No Test Points Included) for a Standard or Standards Set for AC-DC Difference (Voltage or Current)	2632
53351C	First Point for Each Applied Voltage or Current	1092
53352C	Additional Points for Each Applied Voltage and Current Level (Additional Frequency/Voltage or Frequency/Current Points)	78

## **D.** Precision Ratio Measurements

## **D.1 Inductive Dividers**

Technical Contact:	<b>Telephone:</b>	<u>Email:</u>	Mailing Address
Scott Shields	(301) 975-4232	scott.shields@nist.gov	NIST
			100 D D 1

Mailing Address: NIST 100 Bureau Drive, Stop 8170 Gaithersburg, MD 20899-8170

#### Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54110S	Special Ratio Measurements and Tests of Inductive Voltage Dividers, by Prearrangement	At Cost
54120C	Inductive Voltage Dividers – (Single Frequency, Voltage to be Specified, Each Setting of 3 Most Significant Dials)	5123
54121C	Additional Frequency Points	5123
54130C	Inductive Voltage Dividers – (Single Frequency, Voltage to be Specified, Each Setting of Most Significant Dial Only)	3212
54131C	Additional Frequency Points	3212

Fees are subject to change without notice.

## **D.2 Resistive Dividers**

Technical Contacts: Gerald J. FitzPatrick	<u>Telephone:</u> (301) 975-8922	Email: gfitzpatrick@nist.gov	<u>Mailing Address:</u> NIST 100 Bureau Drive, Stop 8170 Gaithersburg, MD 20899-8170
			e

#### Administrative and Logistics:

Denise D. Prather

(301) 975-4221 dprather@nist.gov

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54210C	Resistor and Resistive Dividers, Total Resistance or Voltage Ratio, Two Direct Voltage Levels Between 10 kV and 150 kV	4284
542118	Special Tests of Resistor and Resistive Dividers at Direct Voltage Levels, by Prearrangement	At Cost
542138	Special Tests of Resistor and Resistive Dividers at 60 Hz, by Prearrangement	At Cost

## **D.3 Capacitive Dividers**

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Gerald J. FitzPatrick	(301) 975-8922	gfitzpatrick@nist.gov	NIST
			100 Bureau Drive, Stop 8170
			Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather (301) 975-4221

dprather@nist.gov

#### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54310S	Special Test of Capacitive Dividers at 60 Hz, by Prearrangement	At Cost

#### **D.4 Voltage and Current Transformers**

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Gerald J. FitzPatrick	(301) 975-8922	gfitzpatrick@nist.gov	NIST
Thomas L. Nelson	(301) 975-2986	tnelson@nist.gov	100 Bureau Drive, Stop 8170
			Gaithersburg, MD 20899-8170

## Administrative and Logistics:

Denise D. Prather (301) 975-4221 dprather@nist.gov

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
54520C	Current Transformer, Ratio & Phase Angle, 1 Range at 1 Frequency, 1 Burden, Secondary Currents (0.5, 1, 2, 3, 4, 5) A, Primary Current Not Over 12 000 A	4753
54521C	Current Transformer, Ratio & Phase Angle, 1 Secondary Current, Additional Combination of Range, Frequency, and Burden, Primary Current Not Over 12 000 A	446
54522C	Current Transformer, Ratio & Phase at Each Additional Secondary Current, Same Combination of Range, Frequency, and Burden as 54520C or 54521C	364
54600S	Special Tests of Dividers and Transformers, by Prearrangement	At Cost

# E. Phase Meters and Standards and VOR Measurements

Technical Contacts:	Telephone:	Email:	Mailing Address:
Bryan C. Waltrip	(301) 975-2438	bwaltrip@nist.gov	NIST 100 Bureau Drive, Stop 8170
			Gaithersburg, MD 20899-8170

Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

#### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
55110S	Special Tests of Phase Standards and Related Instruments, by Prearrangement	At Cost
55120C	Phase Meters – One Combination of Input Voltages (0.5 V to 120 V) at One Frequency (2 Hz to 100 kHz) – the Input Voltage Ratio Shall Not Exceed 10	3076
55121C	Phase Meters – Each Additional Combination of Input Voltages (0.5 V to 120 V) at the Same or at a Different Frequency (2 Hz to 100 kHz) – the Input Voltage Ratio Shall Not Exceed 10	979
55130C	Phase Meters – One Additional Combination of One Input Voltage (0.5 V to 120 V) and One Input Current (1 A to 5 A) at One Frequency (2 Hz to 4 kHz)	4138
55131C	Phase Meters – Each Additional Combination of One Input Voltage (0.5 V to 120 V) and One Input Current (0.5 A to 5 A)	1118
55140C	Phase Meters – One Input Voltage (120 V to 240 V) and Another Input Voltage (120 V to 240 V) at One Frequency (2 Hz to 5 kHz)	4138
55141C	Phase Meters – Each Additional Combination of One Input Voltage (120 V to 240 V) and Another Input Voltage (120 V to 240 V) at the Same or at a Different Frequency (2 Hz to 5 kHz)	1118

# F. Power and Energy Measurements, Low-Frequency

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Thomas L. Nelson	(301) 975-2986	tnelson@nist.gov	NIST
Gerald J. FitzPatrick	(301) 975-8922	gfitzpatrick@nist.gov	100 Bureau Drive, Stop 8170
			Gaithersburg, MD 20899-8170

## Administrative and Logistics:

Denise D. Prather

(301) 975-4221

dprather@nist.gov

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
56110S	Special Test of AC-DC Wattmeters, by Prearrangement	At Cost
56200C	Watt, Watthour, Var, Varhour Meter, Initial Two Determinations of Same Meter at 60 Hz	4307
56201C	Each Additional Determination, Same Meter at 50 Hz	257
56202C	Initial Two Determinations of One or Two Meters Run Simultaneously with the First (56200C)	3942
56210M	Measurement Assurance Program for Watthour Meters	5592
56220C	Watthour Meter with Pulse Output; 120 Volts, 5 Amperes, 60 Hz at 0.5 Lag, Unity and 0.5 Lead Power Factors	1817
56230S	Special Test of Phasor Measurement Units, PMUs	At Cost

## G. RF, Microwave and Millimeter-Wave Measurements

#### **G.1 Thermistor Detectors**

<u>Technical Contacts:</u> Ronald A. Ginley Thomas P. Crowley	<u>Telephone:</u> (303) 497-3634 (303) 497-4133	Email: rginley@boulder.nist.gov crowley@boulder.nist.gov	<u>Mailing Address:</u> NIST 325 Broadway, MC 818.01 Boulder, CO 80305-3328	
Administrative and Logistics:				

Administrative and Logistics: Puanani L. DeLara (303) 497-3753

**Fax:** (303) 497-3970

calibration@boulder.nist.gov

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services		
The follow	ring tests are for 50 $\Omega$ thermistor and thermoelectric detectors with coaxial com	nectors.	
61100C	Measurement setup charge (applies to all coaxial power measurements—one setup charge for multiple detectors with the same connectors and frequencies <sup>1</sup> )	2777	
61110C	Coaxial Detectors in the Frequency Range from 0.1 MHz to 10 MHz	3181	
61120C	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type <sup>2</sup> . Up to 20 Frequency Points	3428	
61121C	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type <sup>2</sup> . From 20 to 40 Frequency Points	3970	
61122C	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type <sup>2</sup> . From 40 to 120 Frequency Points	4240	

61123C	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type <sup>2</sup> . More than 120 Frequency Points	4782
61137C	NIST Model CN Coaxial Detectors at 21 Frequencies within the Frequency Range of 50 MHz to 18 GHz	7875
61138C	NIST Model CN Coaxial Detectors at Single Customer Selected Frequency within the Frequency Range of 50 MHz to 18 GHz	50
	The following tests are for thermistor detectors with waveguide flanges.	
61140C	Measurement setup charge (applies to all waveguide power measurements EXCEPT WR15—one charge for multiple detectors with the same connectors and frequencies <sup>1</sup> )	5213
61141C	Measurement setup charge (applies to all WR15 waveguide power measurements—one charge for multiple detectors with the same connectors and frequencies <sup>1</sup> )	4131
61142C	Rectangular Waveguide Detectors with WR90 Flanges <sup>2</sup>	3251
61143C	Rectangular Waveguide Detectors with WR62 Flanges <sup>2</sup>	3541
61144C	Rectangular Waveguide Detectors with WR42 Flanges <sup>2</sup>	3541

Fee Schedule 2017

61145C	Rectangular Waveguide Detectors with WR28 Flanges <sup>2</sup>	3922	
61146C	Rectangular Waveguide Detectors with WR22 Flanges <sup>2</sup>	3922	
61147C	Rectangular Waveguide Detectors with WR15 Flanges <sup>2</sup>	6358	
61148C	Rectangular Waveguide Detectors with WR10 Flanges26358		
Miscellaneous Tests			
61190S	Special Microwave and RF Power Measurement Services, by Prearrangement	At Cost	

<sup>1</sup> Only one setup charge is necessary for multiple detectors sent in at the same time with the same connector type and measurement frequencies.

<sup>2</sup> Measurement Frequencies

## G.2 Scattering Parameters of Passive One and Two-Port Devices

<b>Technical Contacts:</b>	Telephone:	Email:	Mailing Address:
Ronald A. Ginley	(303) 497-3634	rginley@boulder.nist.gov	NIST
			325 Broadway, MC 818.01
			Boulder, CO 80305-3328
Administrative and Log	istics:		

Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov **Fax:** (303) 497-3970

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
61290S	Special Microwave and RF Scattering-Parameter Measurement Services, by Prearrangement	At Cost

Fees are subject to change without notice.

## **G.3 Thermal Noise Measurements**

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
David Walker	(303) 497-5490	dwalker@boulder.nist.gov	NIST
James Randa	(303) 497-3150	randa@boulder.nist.gov	325 Broadway, MC 818.01 Boulder, CO 80305-3328

#### Administrative and Logistics:

Puanani L. DeLara	0	(303) 497-3753	calibration@boulder.nist.gov
	Fax:	(303) 497-3970	

Service ID Number	Freq.	Connector Type	Device Requirements/Service	Fee (\$)
----------------------	-------	----------------	-----------------------------	----------

61410C	30 MHz 60 MHz Set Up Charge,	Coaxial N Precision (PIN) GPC 3.5 (PIN) GPC 7 14 mm per order	Temperature < 15 000 K (ENR < 17 dB) VSWR < 1.2	3532
-	Per Frequency			5527
61420C	1.0 GHz to 12.4 GHz Continuous Frequencies Set Up Charge,	Coaxial 14 mm (1 to 4 GHz) GPC 7 N Precision (PIN) GPC 3.5 (PIN) GPC 2.4 (PIN) (8 GHz to 12.4 GHz) per order	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	6049
	Per Frequency		715	
61425C	12.4 GHz to 18.0 GHz Continuous Frequencies	Coaxial GPC 7 N Precision (PIN) GPC 3.5 (PIN) GPC 2.4 (PIN)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge, per order			8220
	Per Frequency			4540
61430C	18.0 GHz to 26 GHz Continuous Frequencies	Coaxial GPC 3.5 (PIN) GPC 2.4 (PIN)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	Set Up Charge,	per order		7974
	Per Frequency			4417

61435C	26.5 GHZ to 40 GHz	Coaxial	Temperature < 15 000 K	
017550	Continuous	GPC 2.4 (PIN)	(ENR < 17 dB)	
	Frequencies		Reflection Coefficient < 0.2	
	Set Up Charge,	per order		11181
	Per Frequency	<b>F</b>		6021
	8.2 GHz to		Temperature <15 000 K	
	12.4 GHz	Waveguide	(ENR < 17  dB)	
	Continuous	WR 90	Reflection Coefficient < 0.2	
61450C	Frequencies			
	Set Up Charge, per order			
	Per Frequency	-		715
	12.4 GHz to		Temperature < 15 000 K	
	18.0 GHz	Waveguide	(ENR < 17 dB)	
61455C	Continuous	WR 62	Reflection Coefficient $< 0.2$	
011550	Frequencies		Reflection Coefficient < 0.2	0005
	Set Up Charge,	per order		8097
	Per Frequency		l	4417
	18.0 GHz to	Waveguide WR 42	Temperature < 15 000 K	
	26.0 GHz Continuous		(ENR < 17 dB)	
61460C	Frequencies	WR 42	Reflection Coefficient < 0.2	
	Set Up Charge,	per order		7727
	Per Frequency	F		4293
	26.5 GHz to 40.0 GHz	Waveguide	Temperature < 15 000 K	
	Continuous	WR 28	(ENR < 17 dB)	
61465C	Frequencies	WK 20	Reflection Coefficient < 0.2	
	Cat Us Ob and			
	Set Up Charge,	per order		8220
	Per Frequency			4343
	33.0 GHz to 50.0 GHz	Waveguide	Temperature <15 000 K	
	Continuous		(ENR < 17 dB)	
61470C	Frequencies	WR 22	Reflection Coefficient <0.2	
	Set Up Charge,	per order		8097
	Per Frequency	-		4293
	50.0 GHz to		Temperature < 15 000 K	
	65.0 GHz	Waveguide	(ENR, 17  dB)	
61475C	Continuous	WR 15	Reflection Coefficient $< 0.2$	
511,50	Frequencies	non ondon		10441
	Set Up Charge, Per Frequency	per order		10441 7008
(14053				
61495S	Special Noise Te	emperature Measurem	ents, by Prearrangement	At Cost

## H. Electromagnetic Field Strength and Antenna Measurements

#### H.1 Microwave Antenna Parameter Measurements

<u>Technical Contacts:</u> Perry F. Wilson	<u>Telephone:</u> (303) 497-3406	<u>Email:</u> pfw@boulder.nist.gov	<u>Mailing Address:</u> NIST
(63100S-63400S)	(303) 477 3400	prive bounder.mst.gov	325 Broadway, MC 818.02
Jeff Guerrieri (63100S)	(303) 497-3863	jeff.guerrieri@nist.gov	Boulder, CO 80305-3328
Michael H. Francis (63200S)	(303) 497-5873	mfrancis@boulder.nist.gov	
Administrative and Logi	stics:		
Puanani L. Delara	(303) 497-3753	calibration@boulder.nist.gov	,

Puanani L. Delara		(303) 497-3753	calibrat
	Fax:	(303) 497-3970	

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
63100S	Gain and Polarization Calibrations of Standard Antennas Using Extrapolation Range	At Cost
63200S	Measurement of Pattern, Gain, and Polarization of Arbitrary Antennas Using Near-Field Scanning Techniques	At Cost
63400S	Special Consulting, Advisory, and Other Services	At Cost

#### H.2 Field Strength Parameter Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
Dennis G. Camell	(303) 497-3214	camell@boulder.nist.gov	NIST
Perry F. Wilson	(303) 497-3406	pfw@boulder.nist.gov	325 Broadway, MC 818.02 Boulder, CO 80305 3328
			Boulder, CO 80305-3328

#### Administrative and Logistics:

Puanani L. DeLara (303) 497-3753 Fax: (303) 497-3970 calibration@boulder.nist.gov

Service ID Number	Description of Services	Fee (\$)
64100S	Special Test Services for Antenna/Field Strength/Measurement, Using the Transverse Electromagnetic (TEM) Cell Method (10 kHz to 300 MHz)	At Cost
64300S	Special Test Services for Antenna/Field Strength/Reflectivity Measurements, Utilizing the Anechoic Chamber and Standard Field Method	At Cost

## I. High-speed Repetitive Waveform Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Paul Hale	(303) 497-5367	hale@boulder.nist.gov	NIST
		_	325 Broadway, MC 815.01
			Boulder, CO 80305-3328
Administrative and Log	<u>gistics</u> :		

John Lomax (303) 497-3842 john.lomax@nist.gov Fax: (303) 497-4286

#### Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
65200S	Fast Repetitive Waveforms	At Cost
65400S	Fiber-optic time delay (formerly Pulse Time Delay Interval)	At Cost

## J. Pulse Waveform Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Thomas Nelson	(301) 975-2986	thomas.nelson@nist.gov	NIST
Fax:	(301) 926-3972		100 Bureau Drive, Stop 8170
			Gaithersburg, MD 20899-8170

dprather@nist.gov

## Administrative and Logistics:

Denise Prather (301) 975-4221

Service ID Number	Description of Services	Fee (\$)
65250S	Repetitive Pulse Waveform Measurements, Including Settling Parameters	At Cost
65500S	Peak-to-Peak Detector Calibration at One Frequency Selected from Those Give in Table 9.23 at 1.2V	At Cost
65501S	Additional Frequency for Peak-to-Peak Detector in 65500S	At Cost

# **CHAPTER 10** TIME AND FREQUENCY MEASUREMENTS

# A. Broadcast and Measurement Services

<b>Technical Contacts:</b>	<b>Telephone:</b>	Email:	Mailing Address:
Michael A. Lombardi	(303) 497-3212	lombardi@boulder.nist.gov	NIST
(Frequency)			325 Broadway, MC 847.40
Marc A. Weiss	(303) 497-3261	mweiss@boulder.nist.gov	Boulder, CO 80305-3328
(Time)			
John Lowe	(303) 497-5453	lowe@boulder.nist.gov	
Stefania Romisch	(303) 497-3446	stefania.romisch@nist.gov	
Administrative and Lasi	ation		
Administrative and Logi			
Trudi Peppler	(303) 497-3338	tpeppler@boulder.nist.gov	

(303) 497-3338 **Fax:** (303) 497-6461

tpeppler@boulder.nist.gov

Service ID Number	Description of Services	Fee (\$)		
	Broadcast Services (WWW, WWVH, WWVB, GOES, ACTS, and NTS)			
76100C	Frequency Measurement and Analysis Service (FMAS), Frequency Delivered to User's Site	Initial One-Time Fee: 1500 Monthly Charge: 500		
76101C	Time Measurement and Analysis Service (TMAS)	Initial One-Time Fee: 1500 Monthly Charge: 750		
76102C	Time Measurement and Analysis Service (TMAS) with NIST disciplined rubidium oscillator	Initial One-Time Fee: 1500 Monthly Charge: 1000		
76103C	Time Measurement and Analysis Service (TMAS) with NIST disciplined cesium oscillator	Initial One-Time Fee: 1500 Monthly Charge: 1000		
76120S	Characterization of Global Positioning System (GPS) Satellite Receivers	At Cost		

## B. Calibration and Characterization of Oscillators and Amplifiers

<b>Technical Contacts:</b>	<b>Telephone:</b>	<u>Email:</u>	Mailing Address:
David Howe Stefania Romisch	(303) 497-3277 (303) 497-3446	dhowe@boulder.nist.gov stefania.romisch@nist.gov	NIST 325 Broadway, MC 847 Boulder, CO 80305-3328

## Administrative and Logistics:

Trudi Peppler		(303) 497-3338
	Fax:	(303) 497-6461

tpeppler@boulder.nist.gov

## Please contact the technical staff before shipping instruments or standards to the address listed above.

Service ID Number	Description of Services	Fee (\$)
77110C	Characterization of Atomic Frequency Standards	
77120C	Characterization of Oscillators: Time Domain	At Cost

## C. Test of PM/AM Noise Measurement Systems

<b>Technical Contact:</b>	Telephone:	Email:	Mailing Address:
David Howe	(303) 497-3277	dhowe@boulder.nist.gov	NIST 325 Broadway, MC 847.30
			Boulder, CO 80305-3328

## Administrative and Logistics:

Trudi Peppler (303) 497-3338 **Fax:** (303) 497-6461

tpeppler@boulder.nist.gov

Service ID Number	Description of Services	Fee (\$)
77135C	Tests of RF PM/AM Noise Measurement Systems: On-Site Tests	At Cost
77136C	Tests of Microwave PM/AM Noise Measurement Systems: On-Site Tests	At Cost
77140S	Special Time/Frequency Measurements: Oscillators and Other Components	At Cost

# CHAPTER 11 SEMINARS

The following announcements concern notification of changes in services and information about future NIST Measurement Seminars. General policy questions regarding NIST measurement services should be referred to the Calibration Program.

#### NIST MEASUREMENT SEMINARS

NIST holds seminars and workshops that provide advice and assistance on measurements and calibrations. This affords laboratories outside NIST an opportunity to learn how to make measurements consistent with national standards which NIST maintains. Participation is open to a limited number of people who have the appropriate education, work experience, and current profession in measurement and standards laboratory activities.

Each seminar lasts from one to five days and is devoted to lectures, group discussions, and laboratory demonstrations. A course may be cancelled if registration is insufficient. However, in the past, requests for enrollment have nearly always exceeded the numbers that could be accommodated.

Acceptance letters will be mailed no later than 4 weeks prior to the scheduled date of the course. Detailed information on schedules and housing will be included. Those accepted will be expected to study the assigned reading material before coming to the course and should be prepared to discuss their own experiences with related problems.

See the Weights and Measures Program web site www.nist.gov/pml/wmd/index.cfm for the National Conference on Weights and Measures (NCWM) Calendar of Events for other training not listed here.

NIST offers conferences and workshops throughout the year. To see the latest listing go to www.nist.gov for upcoming NIST Conferences and Events.