

1. CAD MODEL \_\_\_\_\_ REV. \_\_ IS  
REQUIRED TO COMPLETE PRODUCT  
DEFINITION.

3. APPLICABLE STANDARDS:  
ASME Y14.41-2003 APPLIES TO  
DATASET AND MOVABLE DATUM  
TARGETS.

④ FULL DIAMETER OF EACH INDICATED HOLE MUST INTERSECT WITH THE CROSS-DRILLED HOLE AT ITS BOTTOM. INDICATED HOLES MUST NOT CONTACT FAR SIDE OF CROSS- DRILLED HOLES.

6. UNITS: MILLIMETERS



Use the view carousel to the left to view MBD saved view configurations.

Note: You must enable 3D content viewing to activate a saved view.

NOTES (UNLESS OTHERWISE SPECIFIED):

1. CAD MODEL \_\_\_\_\_ REV. \_\_\_\_ IS REQUIRED TO COMPLETE PRODUCT DEFINITION.
2. DIRECTLY-TOLERANCED DIMENSIONS AND BASIC DIMENSIONS DEFINED ON THE DRAWING TAKE PRECEDENCE OVER DIMENSIONAL DATA DEFINED BY THE MODEL. OBTAIN ALL OTHER DIMENSIONAL DATA FROM THE MODEL. THE MODEL REPRESENTS BASIC DIMENSIONAL DATA UNLESS OTHERWISE SPECIFIED.
3. APPLICABLE STANDARDS:  
ASME Y14.41-2003 APPLIES TO DATASET AND MOVABLE DATUM TARGETS.  
  
ASME Y14.5M-1994 APPLIES TO DIMENSIONING AND TOLERANCING.
4. FULL DIAMETER OF EACH INDICATED HOLE MUST INTERSECT WITH THE CROSS-DRILLED HOLE AT ITS BOTTOM. INDICATED HOLES MUST NOT CONTACT FAR SIDE OF CROSS-DRILLED HOLES.
5.  $\boxed{\text{1.5}} \boxed{A} \boxed{B} \boxed{C}$  APPLIES TO ALL UNTOLERANCED SURFACES.
6. UNITS: MILLIMETERS









