

Start Up of Naraha Remote Technology Development Center (NRTDC) and

Consideration of Deployed Robot Operation for New Standard Testing Method

Kuniaki KAWABATA, Yoshihito TSUCHIDA, Yuta TANIFUJI, Shinji KAWATSUMA, Tatsuo TRII

Naraha Remote Technology Development Center Fukushima Research Infrastructural Creation Center Sector of Fukushima Research and Development Japan Atomic Energy Agency (JAEA)



Contents

topic I: Introduction of Naraha Remote Technology Development Center (NRTDC), JAEA!

- Aim and status of NRTDC
- Mockup and instruments to be installed
- Research subjects by JAEA at NRTDC

topic II: Examination of Operations by Deployed Robot in 1F for designing Standard Testing Method

- Approach to develop STM for nuclear emergency response robots
- Current examinations on the robot operations in 1F



Aim and status of NRTDC: background

- background

For research and development on the decommissioning of TEPCO's Fukushima Daiichi nuclear power stations (1F), 85 billion JPY was financed to Japan Atomic Energy Agency (JAEA) to construct the research institution in 2012 by Japanese Ministry of Economy, Trade and Industry(METI).

- challenge to create a test environment which can be performed only here to solve new problems concerning the decommissioning by using R&D results which have been accumulated in JAEA.
- integration of wisdom of researchers and engineers who have engaged in national and international related facilities, and nuclear human resource development through the R&D.

JAEA made decision to establish an essential research center with developmental facilities for contributable technology toward the decommissioning of 1F in Fukushima-prefecture, Japan



Aim and status of NRTDC: motivations

- aim & target

In the inside of the 1 F building, person cannot approach to the operation floor because of high radiation dose.



Remote operated technology are necessary for the decommissioning works.

Naraha Remote Technology Development Center (NRTDC)


- contribution to decommissioning of 1F through the establishment of the technical base about remote controlled devices
- creation of the R&D base for the researchers of remote technology
- is being established and will be fully operational from April 2016. (currently, operated in partially)

NRTDC would be utilized for

- development of remote operated technology and the worker's training by IRID and TEPCO.
- emergency response research and development by the researchers of the universities, the institutes and JAEA.



Aim and status of NRTDC: location & layout



- layout of the site







Aim and status of NRTDC: motivations

- aim & target

In the inside of the 1 F building, a person cannot approach to the operation floor because of a high radiation dose.



Remote controlled devices are necessary for the decommissioning works.

Naraha Remote Technology Development Center (NRTDC)

- contribution to decommissioning of 1F through the establishment of the technical base about remote controlled devices
- creation of the R&D base for the researchers of remote technology
- is being established and will be fully operational from April 2016. (currently, operated in partially)

specific functions to be installed to NRTDC

- Demonstration test for the techniques to repair a water leakage at the primary containment vessel (PCV) by utilizing the mock-up of PCV
- Test of the remote controlled devices to be used for the investigation & the decontamination in the 1F by utilizing the mock-up facilities
- Support development of the robot and the operators training by the simulator
- Confirmation and training of the work procedure for the workers in 1F by the virtual reality system




Mockup and instruments to be installed

- facilities

Water pool

Demonstration test area for the technique to repair a water leakage at the PCV and development and demonstration test area for the remote controlled equipments are prepared in Test building




Mock-up staircase

Motion capture camera




Mockup and instruments to be installed

- outlooks of the facilities in Test building









mock-up staircase



motion capture space (with 16 tracking cameras)







Mockup and instruments to be installed

-Virtual Reality (VR) System


- Planning of the work procedure
 - It will be used to validate the working method and procedure, by testing the plan in the virtual space.
- Training and drill

The workers can better understand the work environment, the work methods and procedures by going through the virtual scenarios as experience for real world scenarios.





To make and verify the procedures for the decommissioning



Training and drills based on the procedures




Operation training and validation of remote handling equipment (ex. manipulator)



- outlooks of Virtual Reality System

- Tracking the head motion of an operator and feedback to projection of the view
- 3D-glasses and an input device
- Structural data of 2nd-unit of 1 F (cooperation with TEPCO)

* pictures with dummy env. data





Research subjects by JAEA at NRTDC (1)

- research theme for 7 years from FY 2015.

No.	Research theme				
1		Standard test method			
2	Development of Robotic Technology	Robot simulator			
3		Robotic Technology Powered exoskeleton with radiation shielding			
4		Nuclear emergency response robot			
5		Laser machining technology			
6	Development of Hot testing Technology	Laser diagnostics technology			
7		Gamma-ray CT technology			
8		Advanced instrumentation system			
9		Water stoppage technology using photo-curing resi			



Research subjects by JAEA at NRTDC (2)


- subjects in robot technology for decommissioning

Standard performance test methods for nuclear emergency response robots

Developing test method for quantitatively evaluating common capacities of task performance for nuclear emergency response robot. Clarifying demanded level for robots and technical achievement level for operators

Robot simulator used for decommissioning of 1 F

Inputting data into PC which include changeable work site environment for decommissioning and Developing simulator with the aim to plan and training of decommissioning work for robot, and its streamlined development




*Robotic simulation system is based on AIST's Choreonoid



Research subjects by JAEA at NRTDC (3)


- subjects in robot technology for emergency response



Light operation Robot for door opening



International cooperation



Worldwide Robotics Certification System

Establishment of strategic partnership

Successive development and operation

- Establishment of the standard test method for nuclear emergency response robot
- Planning a robot competition

Promotion of utilization

- Survey of overseas facilities utilized for remote technology development and emergency response and establish a partnership.
- Open for foreign researchers and engineers to use

- International workshop on Standard Test MeMethod (Nov. 6th & 7th, 2015)



 International workshop on Emergency Response Robotics (Dec. 2nd & 3rd, 2015)







Summary of topic I

- JAEA follows the medium-and-long term road map and pushes forward the establishment of the construction or design works of facilities.
- JAEA aims at the establishment of an attractive international base facility for R&D based on user's needs.
- NRTDC: the facilities for development of the remote controlled technology and device are available partially and will be in full operation from April 2016.

http://naraha.jaea.go.jp



Contents

topic I: Introduction of Naraha Remote Technology Development Center (NRTDC), JAEA

- Aim and status of NRTDC
- Mockup and instruments to be installed
- Research subjects by JAEA at NRTDC

topic II: Examination of Operations by Deployed Robot in 1F for designing Standard Testing Method

- Approach to develop STM for nuclear emergency response robots
- Current examinations on the robot operations in 1F



Background

- Utilization of the remote technology is indispensable for the long-term decommissioning missions in Fukushima Daiichi Nuclear power station.
- There were the cases that the troubles happened during the operations because of the working environment is complicated.



Advance preparations would contribute to reduce the risks

- measuring the performance of the remote equipment
- carrying out frequent training and rehearsal of the operators

realized by providing the simulated/expected working environment

Common evaluation is important to recognize/understand the robot's capability and the operator's proficiency.

- the quantitative evaluation methods are required



Aim

Standard Test Method(s) for response robots

- a comprehensive set of standard test methods and associated performance metrics to quantify key capabilities of emergency response robots
- providing the standardized evaluation methods to evaluate the robots' and the operators' performance quantitatively.






concept/idea of STM coincides with the contributions to reliable decommissioning operations by using remote equipment

design of STM for nuclear emergency response robots

- analysis of the robot operations during the missions in 1F
- reviews on the accidents that were occurred to the robots.




Developmental flow of STM for NERR



- 1) <u>Practical operations in 1F</u>
 - collect the robots types information and their activity data
- 2) Operation analysis
 - analysis of the robot tasks, the operation performance, etc.
- 3) Review of compatibility with STMs
 - examine the compatibility among the results of 2) and NIST-STM for extracting insufficiencies
 - fundamental test trials with prototypes if necessary
- 4) Consideration on the supplementary factors
- 5) Test of designed method
- 6) Evaluation towards standardization



Robots that work in 1 F



Videos & photos: http://www.tepco.co.jp/en/news/library/index-e.html



Video data opened by TEPCO

http://www.tepco.co.ip/tepconews/library/archive-i.html

	sconews, his ai y, ai chive j.himi			
type of the robot	number of information	number of video	data size	main works in the contents
510 PackBot	27	43	1411.1MB	removal of obstacles, dosimetry, decontamination
Quince	16	30	857.66 M B	removal of obstacles, dosimetry, decontamination, sampling
RQ-16 T-Hawk	5	2	232.3MB	observation
Quadruped robot	5	4	249.3MB	investigation of vent pipe
710 Warrior	4	3	109.3MB	removal of obstacles, dosimetry, sampling
MEISTER	2	0	-	dosimetry, sampling
Survey runner	2	2	798.5MB	dosimetry
FRIGO-MA	2	2	-	dosimetry
JAEA-3	1	1	11.2MB	dosimetry using gamma camera
ASTACO-SoRa	1	0	_	removal of obstacles

- most of the robots were utilized to survey missions.
- most of video data were the missions with Packbot and Quince.

analysis candidates: works with PackBot and Quince



Comparison of video data related to PackBot and Quince

PackBot

http://photo.tepco.co.jp/date/ 2011/201104-j/110420-01j.html



- the view from backside
- the view is not suitable to recognize the situation

Quince

http://photo.tepco.co.jp/date/ 2012/201202-j/120228-01j.html



- the operation screen view
- easier to recognize the situation of the robot and the operation

Quince video data is better candidate for work analysis.



Time analysis on the operation of the robot

Approach: time analysis on the operation

- definition of the sub-tasks on the operation/state
- classifying the operation of the robot into sub-tasks & counting accumulated use time.

extracted 9 categories from the video contents.

- 1 traveling (flat surface, puddle, passing the obstacle)
- 2 stop (capturing images, state confirmations)
- 3 traveling on gap (stairs, steps)
- 4 angular adjustment of sub crawler
- 5 camera adjustment
- 6 video signal lost*
- (7) turn
- 8 traveling in narrow space
- 9 turn at half landing of the stairs



Time analysis on Quince operation (1/2)

[mission on Feb.2. 2012, operation time 90min.]

	category		time(m:s)		ratio(%)		sum(%)	
	traveling	flat	26:01	37:42	29	42	29	42
1		puddle	06:27		7		36	
		obstacle	05:14		6		42	
2	2 stop		10:48		12		54	
3	traveling	stairs	04:32	09:52	5	11	59	65
9	on gap	step	05:20		6		65	
4	angular adjustment of sub crawler		09:48		10		75	
⑤	camera adjustment		06:39		7		82	
6	video signal lost		05:44		6		88	
7	turn		04:14		5		93	
8	traveling in narrow space		03:10		4		97	
9	turn at half landing of the stairs		02:26		3		100	

major sub-tasks to be thought in the operation



Time analysis on Quince operation (2/2)

[mission on June 13, 2012, operation time 167min. 12sec.]

	category		time(m:s)		ratio(%)		sum(%)	
	traveling	flat	26:57	54:31	16.1	32.6	16.1	32.6
1		puddle	06:05		3.6		19.7	
		obstacle	21:29		11.6		31.3	
3	traveling	stairs	07:55	50:41	4.7	30.3	37.3	62.0
3	on gap	step	42:46		25.6		62.9	62.9
4	angular adjustment of sub crawler		22:58		13.7		76.6	
2	stop		17:31		10.5		87.1	
6	video signal lost		12:01		7.2		94.3	
7	turn		04:	18 2.9		2.9	97.2	
9	turn at half landing of the stairs		02:11		1.3		98.5	
8	traveling in narrow space		01:24		0.8		99.3	
5	camera adjustment		06:39		0.7		100	


major sub-tasks to be thought in the operation



Results of time analysis

5 sub-tasks accounted for 80%+ of accumulated use time during the operations

- 1 traveling (flat surface, puddle, passing obstacle)
- 2 stop
 (capturing images, state monitoring)
- 3 traveling on gap (stairs, steps)
- 4 angular adjustment of sub crawlers
- 5 camera adjustment



It is estimated the state monitoring is to recognize the surroundings and the cable state etc.



Accident occurrence on the robots

Approach: occurred accident investigation

- approx. 35 robots and machines were applied to the missions during 3 years after the nuclear power station accident.
- for indoor use, investigation/inspection robots accounted for 40%+.
- 5 robots could not return / be recovered.

Missions		Туре	Numbers	Missions
Rubble remove	outdoor use	Unmanned construction machine	(approx. 10)	?
<u> </u>	indoor use	BROKK	5	?
Reconnaissanc	at surface e	PackBOT QUINCE JAEA-3 QUINCE-2,3 Survey Runner	9	43 3 1 6 2
	at high place		1	2
De-contaminati	for lower floor		3	3
De-contaminati	for higher floor		1	?
	core sampling	Meister	1 (common use: decont.)	2
Others	obstacle deconstruction	Warrior	1	6



(AEA) Accidents that occurred during the operations

	Type of robot	Occurred accident			
C	T-Hawk	Out of control?			
الم الم	QUINCE	Communication cable was broken down?			
Un-repatriated robots	Survey Runner	Communication cable was broken down?			
	Child robot of quadruped robot	Communication cable was jammed			
	Warrior	Tumbled by mis-operation			
Returned but troubled robots	QUINCE 2	Communication cable was broken down? collected by wireless communication relay with QUINCE3			
	Quadruped robot	Tumbled by mis-recognition of the material of the step collected by the operator			
	JAEA-3	Communication / Power cable affected travelling performance (not smooth motion)			

- accidents of ground robots accounted for approx. 50% of all cases
 - Un-repatriated robots left in 1F become the OBSTACLES and modify the env.
- accidents were caused by the troubles of the cable / tether
 - remodeling communication part into WIRED type for applying the works in nuclear power station



Possible subject for evaluating NERR

facts in the robot operation


- wireless signal is shielded by concrete structure a building
- possibility of system or operation failure under complicated env..
- robot is contaminated by high dose of the radiation

Wired signal transmission

Recovered/removed by the other robot

Remote operated maintenance

Possible subjects



Influence of the cable

influence of the cable tension should be evaluated quantitatively



Removability

recoverability/
removability by
the remote
operation should
be evaluated.



Remote maintenance ability

 Maintenance time, and the number of the tools to use should be evaluated quantitatively



Summary of topic II

- Towards design of Standard Test Method for nuclear emergency response robots......

- approach & current works
 - conduct time analysis of the operations with Quince based on the video open by TEPCO.
 - summarize occurred accidents on the robot that worked in 1F.
 - extract the issues to design standard test methods for nuclear emergency response robots.

- future directions

- attempt to design the prototypes of STM for NERR based on analysis results
- interviews with the operators of the robots and the workers



Conclusions

- Presented topics

- Introduction of Naraha Remote Technology Development Center, JAEA
- Examinations on robot (Quince) operations in 1 F to contribute toward design of Standard Test Method for nuclear emergency response robots

Acknowledgements

We'd like to express our gratitude to Mr. Fumiaki Mori and Mr. Norihito Shirasaki of JAEA. They gave the efforts to discuss topics II.