



**CYBERSECURITY FRAMEWORK
MANUFACTURING PROFILE**

September 7, 2016

NIST
National Institute of
Standards and Technology
U.S. Department of Commerce

Table of Contents

| | |
|---|-----------|
| Executive Summary | 2 |
| 1. Introduction | 3 |
| 1.1 Purpose & Scope | 3 |
| 1.2 Audience | 4 |
| 1.3 Document Structure | 4 |
| 2. Overview of Manufacturing Systems | 5 |
| 3. Overview of the Cybersecurity Framework | 6 |
| 3.1 Framework Core | 6 |
| 4. Manufacturing Profile Development Approach | 9 |
| 5. Manufacturing Business/Mission Objectives | 10 |
| 5.1 Alignment of Subcategories to Meet Mission Objectives | 10 |
| 6. Manufacturing System Categorization and Risk Management | 15 |
| 6.1 Categorization Process | 15 |
| 6.2 Profile's Hierarchical Supporting Structure | 17 |
| 6.3 Risk Management | 17 |
| 7. Manufacturing Profile Subcategory Guidance | 18 |
| Appendix A - Acronyms and Abbreviations | 47 |
| Appendix B - Glossary | 48 |
| Appendix C - References | 52 |

Executive Summary

This document provides the Cybersecurity Framework implementation details developed for the manufacturing environment. The “Manufacturing Profile” of the Cybersecurity Framework can be used as a roadmap for reducing cybersecurity risk for manufacturers that is aligned with manufacturing sector goals and industry best practices.

The Profile gives manufacturers:

- A method to identify opportunities for improving the current cybersecurity posture of the manufacturing system
- An evaluation of their ability to operate the control environment at their acceptable risk level
- A standardized approach to preparing the cybersecurity plan for ongoing assurance of the manufacturing system’s security

The Profile is built around the primary functional areas of the Cybersecurity Framework which enumerate the most basic functions of cybersecurity activities. The five primary functional areas are: Identify, Protect, Detect, Respond, and Recover. There are 98 distinct security objectives within the primary functional areas. These 98 objectives comprise a starting point from which to develop a manufacturer-specific or sector-specific Profile at the defined risk levels of Low, Moderate and High.

This Manufacturing “Target” Profile focuses on desired cybersecurity outcomes and can be used as a roadmap to identify opportunities for improving the current cybersecurity posture of the manufacturing system. The Manufacturing Profile provides a prioritization of security activities to meet specific business/mission goals. Relevant and actionable security practices that can be implemented to support key business/mission goals are then identified.

This Manufacturing Profile provides a voluntary, risk-based approach for managing cybersecurity activities and reducing cyber risk to manufacturing systems. The Manufacturing Profile is meant to enhance but not replace current cybersecurity standards and industry guidelines that the manufacturer is embracing.

1. Introduction

The Executive Order 13636, “Improving Critical Infrastructure Cybersecurity,” [1] directed the development of the voluntary Cybersecurity Framework that provides a prioritized, flexible, repeatable, performance-based, and cost-effective approach to manage cybersecurity risk [1] for those processes, information, and systems directly involved in the delivery of critical infrastructure services.

The Cybersecurity Framework is a voluntary risk-based assemblage of industry standards and best practices designed to help organizations manage cybersecurity risks [2]. The Framework, created through collaboration between government and the private sector, uses a common language to address and manage cybersecurity risk in a cost-effective way based on business needs without imposing additional regulatory requirements.

The Profile defines specific cybersecurity activities and outcomes for the protection of the manufacturing system, its components, facility, and environment. Through use of the Profile, the manufacturer can align cybersecurity activities with business requirements, risk tolerances, and resources. The Profile provides a manufacturing sector-specific approach to cybersecurity from standards, guidelines, and industry best practices.

1.1 Purpose & Scope

This document represents a ‘Target Profile’ that focuses on the desired cybersecurity outcomes and provides an approach to the desired state of cybersecurity posture of the manufacturing system. It can be used to identify opportunities for improving cybersecurity posture by comparing the current state with the desired (Target) state. The Target Profile can also be used for comparison with the current state to influence process improvement priorities for the organization. The manufacturing system’s ‘Current Profile’ represents the outcomes from the Framework Core that are currently being achieved.

The Manufacturing “Target” Profile focuses on desired cybersecurity outcomes and can be used as a guideline to identify opportunities for improving the current cybersecurity posture of the manufacturing system. The Manufacturing Profile provides a prioritization of security activities to meet specific business/mission goals. Relevant and actionable security practices that can be implemented to support key business/mission goals are then identified.

Comparison of Profiles (e.g., the Current Profile and Target Profile) may reveal gaps to be addressed to meet cybersecurity risk management objectives. An action plan to address these gaps can contribute to the roadmap. Prioritization of gap mitigation is driven by the organization’s business needs and risk management processes. This risk-based approach enables an organization to gauge resource estimates (e.g., staffing, funding) to achieve cybersecurity goals in a cost-effective, prioritized manner. The following are examples of how the Target Profile may be used:

- A manufacturer may utilize the Target Profile to express cybersecurity risk management requirements to an external service provider.

- A manufacturer may express a system’s cybersecurity state through a Current Profile to report results relative to the Target Profile, or to compare with acquisition requirements.
- A critical infrastructure owner/operator, having identified an external partner upon whom that infrastructure depends, may use the Target Profile to convey required cybersecurity outcomes.
- A critical infrastructure sector may establish a baseline that can be used among its constituents as sector-specific starting point from which to build tailored Target Profiles.

The Manufacturing Profile provides a voluntary, risk-based approach for managing cybersecurity activities and reducing cyber risk to manufacturing systems.

1.2 Audience

This document covers details specific to manufacturing systems. Readers of this document should be acquainted with operational technology, general computer security concepts, and communication protocols such as those used in networking. The intended audience is varied and includes the following:

- Control engineers, integrators, and architects who design or implement secure manufacturing systems.
- System administrators, engineers, and other information technology (IT) professionals who administer, patch, or secure manufacturing systems.
- Managers who are responsible for manufacturing systems.
- Senior management who are trying to understand implications and consequences as they justify and implement a manufacturing systems cybersecurity program to help mitigate impacts to business functionality.
- Researchers and analysts who are trying to understand the unique security needs of manufacturing systems.

1.3 Document Structure

The remainder of this guide is divided into the following major sections:

- Section 2 provides an overview of manufacturing systems.
- Section 3 provides an overview of the *Framework for Improving Critical Infrastructure Cybersecurity* (Cybersecurity Framework).
- Section 4 discusses the manufacturing profile development approach.
- Section 5 provides rationale for integrating cybersecurity into manufacturing Business/mission objectives.
- Section 6 discusses cyber risk management and the risk categorization of the manufacturing system.
- Section 7 provides the manufacturing implementation of the CSF subcategories.
- Appendix A— provides a list of acronyms and abbreviations used in this document.
- Appendix B— provides a glossary of terms used in this document.
- Appendix C— provides a list of references used in the development of this document.

2. Overview of Manufacturing Systems

Manufacturing is a large and diverse industrial sector. Manufacturing industries can be categorized as either *process-based* or *discrete-based* [3].

Process-based manufacturing industries typically utilize two main process types:

- **Continuous Manufacturing Processes.** These processes run continuously, often with phases to make different grades of a product. Typical continuous manufacturing processes include fuel or steam flow in a power plant, petroleum in a refinery, and distillation in a chemical plant.
- **Batch Manufacturing Processes.** These processes have distinct processing steps, conducted on a quantity of material. There is a distinct start and end to a batch process with the possibility of brief steady state operations during intermediate steps. Typical batch manufacturing processes include food, beverage, and biotech manufacturing.

Discrete-based manufacturing industries typically conduct a series of operations on a single part to create the end product. Electronic and mechanical parts assembly and parts machining are typical examples of this type of industry. Both process-based and discrete-based industries utilize similar types of control systems, sensors, and networks. Some facilities are a hybrid of discrete and process-based manufacturing.

Manufacturing industries are usually located within a confined factory or plant-centric area. Communications in manufacturing industries are typically performed using fieldbus and local area network (LAN) technologies that are reliable and high speed. Wireless networking technologies are gaining popularity in manufacturing industries. Fieldbus includes, for example, DeviceNet, Modbus, and Controller Area Network (CAN) bus.

The Manufacturing sector of the critical infrastructure community includes public and private owners and operators, along with other entities operating in the manufacturing domain. Members of the distinct critical infrastructure sector perform functions that are supported by industrial control systems (ICS) and by information technology (IT). This reliance on technology, communication, and the interconnectivity of ICS and IT has changed and expanded the potential vulnerabilities and increased potential risk to manufacturing system operations.

3. Overview of the Cybersecurity Framework

The Profile defines specific practices to address the Framework Core. It is the next layer of detail for implementing cybersecurity best practices for each category expressed in the Framework.

3.1 Framework Core

The Framework Core is a set of cybersecurity activities and desired outcomes determined to be essential across critical infrastructure sectors [2]. The Core presents industry standards, guidelines, and practices in a manner that allows for communication of cybersecurity activities and outcomes across the organization from the executive level to the implementation/operations level. The Framework Core consists of five concurrent and continuous Functions—Identify, Protect, Detect, Respond, Recover. When considered together, these Functions provide a high-level, strategic view of the organization’s management of cybersecurity risk. The Framework Core then identifies underlying key Categories and Subcategories for each Function, and matches them with example Informative References such as existing standards, guidelines, and practices for each Subcategory [2].

The five Framework Functions can be performed concurrently and continuously to form an operational culture that addresses the dynamic cybersecurity risk.

Table 1 Cybersecurity Framework Functions and Categories

| Function Unique Identifier | Function | Category Unique Identifier | Category |
|----------------------------|----------|----------------------------|---|
| ID | Identify | ID.AM | Asset Management |
| | | ID.BE | Business Environment |
| | | ID.GV | Governance |
| | | ID.RA | Risk Assessment |
| | | ID.RM | Risk Management Strategy |
| PR | Protect | PR.AC | Access Control |
| | | PR.AT | Awareness and Training |
| | | PR.DS | Data Security |
| | | PR.IP | Information Protection Processes and Procedures |
| | | PR.MA | Maintenance |
| | | PR.PT | Protective Technology |
| DE | Detect | DE.AE | Anomalies and Events |
| | | DE.CM | Security Continuous Monitoring |
| | | DE.DP | Detection Processes |
| RS | Respond | RS.RP | Response Planning |
| | | RS.CO | Communications |
| | | RS.AN | Analysis |
| | | RS.MI | Mitigation |
| | | RS.IM | Improvements |
| RC | Recover | RC.RP | Recovery Planning |
| | | RC.IM | Improvements |
| | | RC.CO | Communications |

The five “functions” of the Framework Core are:

Identify – Develop the organizational understanding to manage cybersecurity risk to systems, assets, data, and capabilities. The activities in the Identify Function are foundational for effective use of the Framework. Understanding the business context, the resources that support critical functions and the related cybersecurity risks enables an organization to focus and prioritize its efforts, consistent with its risk management strategy and business needs. Examples of outcome Categories within this Function include: Asset Management; Business Environment; Governance; Risk Assessment; and Risk Management Strategy.

Protect – Develop and implement the appropriate safeguards to ensure delivery of critical infrastructure services. The activities in the Protect Function support the ability to limit or contain the impact of a potential cybersecurity event. Examples of outcome Categories within this Function include: Access Control; Awareness and Training; Data Security; Information Protection Processes and Procedures; Maintenance; and Protective Technology.

Detect – Develop and implement the appropriate activities to identify the occurrence of a cybersecurity event. The activities in the Detect Function enable timely discovery of cybersecurity events. Examples of outcome Categories within this Function include: Anomalies and Events; Security Continuous Monitoring; and Detection Processes.

Respond – Develop and implement the appropriate activities to take action regarding a detected cybersecurity event. The activities in the Respond Function support the ability to contain the impact of a potential cybersecurity event. Examples of outcome Categories within this Function include: Response Planning; Communications; Analysis; Mitigation; and Improvements.

Recover – Develop and implement the appropriate activities to maintain plans for resilience and to restore any capabilities or services that were impaired due to a cybersecurity event. The activities in the Recover Function support timely recovery to normal operations to reduce the impact from a cybersecurity event. Examples of outcome Categories within this Function include: Recovery Planning; Improvements; and Communications.

The Manufacturing Profile for the Cybersecurity Framework (“Profile”) presents detailed implementation language for the cybersecurity standards expressed in the Framework categories and subcategories. The Profile is intended to support cybersecurity outcomes based on business needs that the manufacturer has selected from the Framework Categories and Subcategories [2]. The Profile can be characterized as the alignment of standards, guidelines, and practices to the Framework Core in a practical implementation scenario.

4. Manufacturing Profile Development Approach

The manufacturing profile was developed to be an actionable approach for implementing cybersecurity controls into a manufacturing system and its environment. The specific statements in the subcategories are derived from the security controls of the NIST SP 800-53 Rev.4, and are customized to the manufacturing domain. The general informative references of ISA/IEC 62443 from the Framework are also listed in the References column. COBIT 5 is sourced for subcategories that have no corresponding 800-53 references. Additional input came from NIST SP 800-82, Rev. 2, both in section 6.2 (Guidance on the Application of Security Controls to ICS) and in Appendix G (ICS Overlay) [3]. For informative references to an entire control family, or set of controls (such as subcategory ID.GV-1's informative reference to all "policy and procedures" controls), the approach took a holistic view of the controls comprising the family/set.

In the Reference column in Section 7, hyperlinks are provided to the specific and relevant source influences for the subcategory statements.

The Profile expresses tailored values for cybersecurity controls for the manufacturing system environment. These represent the application of the Categories and Subcategories from the Framework based on domain-specific relevance, business drivers, risk assessment, and the manufacturer's priorities. Users of the Profile can also add Categories and Subcategories as needed to address unique and specific risks.

5. Manufacturing Business/Mission Objectives

The development of the Manufacturing Profile included the identification of common business/mission objectives to the manufacturing sector. These business/mission objectives provide the necessary context for identifying and managing applicable cybersecurity risk mitigation pursuits. Five common business/mission objectives for the manufacturing sector were initially identified: *Maintain Human Safety*, *Maintain Environmental Safety*, *Maintain Quality of Product*, *Maintain Production Goals*, and *Maintain Trade Secrets*. Other business/mission objectives were identified for the manufacturing sector but not included in this initial profile. Key cybersecurity practices are identified for supporting each business/mission objective, allowing users to better prioritize actions and resources according to the user's defined needs.

These Business/Mission Objectives Are Not Listed in Prioritized Order.

Maintain Human Safety

Manage cybersecurity risks that could potentially impact human safety. Cybersecurity risk on the manufacturing system could potentially adversely affect human safety. Personnel should understand cybersecurity and safety interdependencies.

Maintain Environmental Safety

Manage cybersecurity risks that could adversely affect the environment, including both accidental and deliberate damage. Cybersecurity risk on the manufacturing system could potentially adversely affect environmental safety. Personnel should understand cybersecurity and environmental safety interdependencies.

Maintain Quality of Product

Manage cybersecurity risks that could adversely affect the quality of product. Protect against compromise of integrity and confidentiality of product data.

Maintain Production Goals

Manage cybersecurity risks that could adversely affect production goals. Cybersecurity risk on the manufacturing system could potentially adversely affect production goals. Personnel should understand cybersecurity and production goal interdependencies.

Maintain Trade Secrets

Manage cybersecurity risks that could lead to the loss or compromise of the organization's intellectual property and sensitive business data.

5.1 Alignment of Subcategories to Meet Mission Objectives

To align cybersecurity goals with overall mission success, the Profile subcategories are prioritized in order to support specific business/mission objectives. This allows the manufacturer to focus on implementing those cybersecurity measures against threats that could severely compromise their ability to perform their essential mission.

For each business/mission objective, the most critical Subcategories initially determined to support the objective are highlighted in the tables under each Function.

Identify - This Function guides the manufacturer in the development of the foundation for cybersecurity management, and in the understanding of cyber risk to systems, assets, data, and capabilities.

Table 2 IDENTIFY Business Mission Objectives

| | | Maintain Human Safety | Maintain Environmental Safety | Maintain Quality of Product | Maintain Production Goals | Maintain Trade Secrets |
|----------|--------------------------|-----------------------|-------------------------------|-----------------------------|---------------------------|------------------------|
| Category | | Subcategories | | | | |
| ID | Asset Management | ID.AM-1 | ID.AM-1 | ID.AM-1 | ID.AM-1 | ID.AM-1 |
| | | ID.AM-2 | ID.AM-2 | ID.AM-2 | ID.AM-2 | ID.AM-2 |
| | | ID.AM-3 | ID.AM-3 | ID.AM-3 | ID.AM-3 | ID.AM-3 |
| | | ID.AM-4 | ID.AM-4 | ID.AM-4 | ID.AM-4 | ID.AM-4 |
| | | ID.AM-5 | ID.AM-5 | ID.AM-5 | ID.AM-5 | ID.AM-5 |
| | | ID.AM-6 | ID.AM-6 | ID.AM-6 | ID.AM-6 | ID.AM-6 |
| | Business Environment | ID.BE-1 | ID.BE-1 | ID.BE-1 | ID.BE-1 | ID.BE-1 |
| | | ID.BE-2 | ID.BE-2 | ID.BE-2 | ID.BE-2 | ID.BE-2 |
| | | ID.BE-3 | ID.BE-3 | ID.BE-3 | ID.BE-3 | ID.BE-3 |
| | | ID.BE-4 | ID.BE-4 | ID.BE-4 | ID.BE-4 | ID.BE-4 |
| | | ID.BE-5 | ID.BE-5 | ID.BE-5 | ID.BE-5 | ID.BE-5 |
| | Governance | ID.GV-1 | ID.GV-1 | ID.GV-1 | ID.GV-1 | ID.GV-1 |
| | | ID.GV-2 | ID.GV-2 | ID.GV-2 | ID.GV-2 | ID.GV-2 |
| | | ID.GV-3 | ID.GV-3 | ID.GV-3 | ID.GV-3 | ID.GV-3 |
| | | ID.GV-4 | ID.GV-4 | ID.GV-4 | ID.GV-4 | ID.GV-4 |
| | Risk Assessment | ID.RA-1 | ID.RA-1 | ID.RA-1 | ID.RA-1 | ID.RA-1 |
| | | ID.RA-2 | ID.RA-2 | ID.RA-2 | ID.RA-2 | ID.RA-2 |
| | | ID.RA-3 | ID.RA-3 | ID.RA-3 | ID.RA-3 | ID.RA-3 |
| | | ID.RA-4 | ID.RA-4 | ID.RA-4 | ID.RA-4 | ID.RA-4 |
| | | ID.RA-5 | ID.RA-5 | ID.RA-5 | ID.RA-5 | ID.RA-5 |
| | | ID.RA-6 | ID.RA-6 | ID.RA-6 | ID.RA-6 | ID.RA-6 |
| | Risk Management Strategy | ID.RM-1 | ID.RM-1 | ID.RM-1 | ID.RM-1 | ID.RM-1 |
| | | ID.RM-2 | ID.RM-2 | ID.RM-2 | ID.RM-2 | ID.RM-2 |
| | | ID.RM-3 | ID.RM-3 | ID.RM-3 | ID.RM-3 | ID.RM-3 |

Protect – Protect Function supports the ability to limit the impact of a potential cybersecurity event.

Table 3 PROTECT Business Mission Objectives

| | | Maintain Human Safety | Maintain Environmental Safety | Maintain Quality of Product | Maintain Production Goals | Maintain Trade Secrets |
|----------|---|-----------------------|-------------------------------|-----------------------------|---------------------------|------------------------|
| Category | Subcategories | | | | | |
| PR | Access Control | PR.AC-1 | PR.AC-1 | PR.AC-1 | PR.AC-1 | PR.AC-1 |
| | | PR.AC-2 | PR.AC-2 | PR.AC-2 | PR.AC-2 | PR.AC-2 |
| | | PR.AC-3 | PR.AC-3 | PR.AC-3 | PR.AC-3 | PR.AC-3 |
| | | PR.AC-4 | PR.AC-4 | PR.AC-4 | PR.AC-4 | PR.AC-4 |
| | | PR.AC-5 | PR.AC-5 | PR.AC-5 | PR.AC-5 | PR.AC-5 |
| | Awareness and Training | PR.AT-1 | PR.AT-1 | PR.AT-1 | PR.AT-1 | PR.AT-1 |
| | | PR.AT-2 | PR.AT-2 | PR.AT-2 | PR.AT-2 | PR.AT-2 |
| | | PR.AT-3 | PR.AT-3 | PR.AT-3 | PR.AT-3 | PR.AT-3 |
| | | PR.AT-4 | PR.AT-4 | PR.AT-4 | PR.AT-4 | PR.AT-4 |
| | | PR.AT-5 | PR.AT-5 | PR.AT-5 | PR.AT-5 | PR.AT-5 |
| | Data Security | PR.DS-1 | PR.DS-1 | PR.DS-1 | PR.DS-1 | PR.DS-1 |
| | | PR.DS-2 | PR.DS-2 | PR.DS-2 | PR.DS-2 | PR.DS-2 |
| | | PR.DS-3 | PR.DS-3 | PR.DS-3 | PR.DS-3 | PR.DS-3 |
| | | PR.DS-4 | PR.DS-4 | PR.DS-4 | PR.DS-4 | PR.DS-4 |
| | | PR.DS-5 | PR.DS-5 | PR.DS-5 | PR.DS-5 | PR.DS-5 |
| | | PR.DS-6 | PR.DS-6 | PR.DS-6 | PR.DS-6 | PR.DS-6 |
| | | PR.DS-7 | PR.DS-7 | PR.DS-7 | PR.DS-7 | PR.DS-7 |
| | Information Protection Processes and Procedures | PR.IP-1 | PR.IP-1 | PR.IP-1 | PR.IP-1 | PR.IP-1 |
| | | PR.IP-2 | PR.IP-2 | PR.IP-2 | PR.IP-2 | PR.IP-2 |
| | | PR.IP-3 | PR.IP-3 | PR.IP-3 | PR.IP-3 | PR.IP-3 |
| | | PR.IP-4 | PR.IP-4 | PR.IP-4 | PR.IP-4 | PR.IP-4 |
| | | PR.IP-5 | PR.IP-5 | PR.IP-5 | PR.IP-5 | PR.IP-5 |
| | | PR.IP-6 | PR.IP-6 | PR.IP-6 | PR.IP-6 | PR.IP-6 |
| | | PR.IP-7 | PR.IP-7 | PR.IP-7 | PR.IP-7 | PR.IP-7 |
| | | PR.IP-8 | PR.IP-8 | PR.IP-8 | PR.IP-8 | PR.IP-8 |
| | | PR.IP-9 | PR.IP-9 | PR.IP-9 | PR.IP-9 | PR.IP-9 |
| | | PR.IP-10 | PR.IP-10 | PR.IP-10 | PR.IP-10 | PR.IP-10 |
| | | PR.IP-11 | PR.IP-11 | PR.IP-11 | PR.IP-11 | PR.IP-11 |
| | | PR.IP-12 | PR.IP-12 | PR.IP-12 | PR.IP-12 | PR.IP-12 |
| | Maintenance | PR.MA-1 | PR.MA-1 | PR.MA-1 | PR.MA-1 | PR.MA-1 |
| | | PR.MA-2 | PR.MA-2 | PR.MA-2 | PR.MA-2 | PR.MA-2 |
| | Protective Technology | PR.PT-1 | PR.PT-1 | PR.PT-1 | PR.PT-1 | PR.PT-1 |
| PR.PT-2 | | PR.PT-2 | PR.PT-2 | PR.PT-2 | PR.PT-2 | |
| PR.PT-3 | | PR.PT-3 | PR.PT-3 | PR.PT-3 | PR.PT-3 | |
| PR.PT-4 | | PR.PT-4 | PR.PT-4 | PR.PT-4 | PR.PT-4 | |

Detect – The Detect Function enables timely discovery of cybersecurity events. Real time awareness and continuous monitoring of the systems is critical to detect cybersecurity events.

Table 4 DETECT Business Mission Objectives

| | | Maintain Human Safety | Maintain Environmental Safety | Maintain Quality of Product | Maintain Production Goals | Maintain Trade Secrets |
|----------|--------------------------------|-----------------------|-------------------------------|-----------------------------|---------------------------|------------------------|
| Category | | Subcategories | | | | |
| DE | Anomalies and Events | DE.AE-1 | DE.AE-1 | DE.AE-1 | DE.AE-1 | DE.AE-1 |
| | | DE.AE-2 | DE.AE-2 | DE.AE-2 | DE.AE-2 | DE.AE-2 |
| | | DE.AE-3 | DE.AE-3 | DE.AE-3 | DE.AE-3 | DE.AE-3 |
| | | DE.AE-4 | DE.AE-4 | DE.AE-4 | DE.AE-4 | DE.AE-4 |
| | | DE.AE-5 | DE.AE-5 | DE.AE-5 | DE.AE-5 | DE.AE-5 |
| | Security Continuous Monitoring | DE.CM-1 | DE.CM-1 | DE.CM-1 | DE.CM-1 | DE.CM-1 |
| | | DE.CM-2 | DE.CM-2 | DE.CM-2 | DE.CM-2 | DE.CM-2 |
| | | DE.CM-3 | DE.CM-3 | DE.CM-3 | DE.CM-3 | DE.CM-3 |
| | | DE.CM-4 | DE.CM-4 | DE.CM-4 | DE.CM-4 | DE.CM-4 |
| | | DE.CM-5 | DE.CM-5 | DE.CM-5 | DE.CM-5 | DE.CM-5 |
| | | DE.CM-6 | DE.CM-6 | DE.CM-6 | DE.CM-6 | DE.CM-6 |
| | | DE.CM-7 | DE.CM-7 | DE.CM-7 | DE.CM-7 | DE.CM-7 |
| | | DE.CM-8 | DE.CM-8 | DE.CM-8 | DE.CM-8 | DE.CM-8 |
| | Detection Processes | DE.DP-1 | DE.DP-1 | DE.DP-1 | DE.DP-1 | DE.DP-1 |
| | | DE.DP-2 | DE.DP-2 | DE.DP-2 | DE.DP-2 | DE.DP-2 |
| | | DE.DP-3 | DE.DP-3 | DE.DP-3 | DE.DP-3 | DE.DP-3 |
| | | DE.DP-4 | DE.DP-4 | DE.DP-4 | DE.DP-4 | DE.DP-4 |
| | | DE.DP-5 | DE.DP-5 | DE.DP-5 | DE.DP-5 | DE.DP-5 |

Respond – The Respond Function supports the ability to contain the impact of a potential cybersecurity event.

Table 5 RESPOND Business Mission Objectives

| | | Maintain Human Safety | Maintain Environmental Safety | Maintain Quality of Product | Maintain Production Goals | Maintain Trade Secrets |
|----------|-------------------|-----------------------|-------------------------------|-----------------------------|---------------------------|------------------------|
| Category | | Subcategories | | | | |
| RS | Response Planning | RS.RP-1 | RS.RP-1 | RS.RP-1 | RS.RP-1 | RS.RP-1 |
| | Communications | RS.CO-1 | RS.CO-1 | RS.CO-1 | RS.CO-1 | RS.CO-1 |
| | | RS.CO-2 | RS.CO-2 | RS.CO-2 | RS.CO-2 | RS.CO-2 |
| | | RS.CO-3 | RS.CO-3 | RS.CO-3 | RS.CO-3 | RS.CO-3 |
| | | RS.CO-4 | RS.CO-4 | RS.CO-4 | RS.CO-4 | RS.CO-4 |
| | | RS.CO-5 | RS.CO-5 | RS.CO-5 | RS.CO-5 | RS.CO-5 |
| | Analysis | RS.AN-1 | RS.AN-1 | RS.AN-1 | RS.AN-1 | RS.AN-1 |
| | | RS.AN-2 | RS.AN-2 | RS.AN-2 | RS.AN-2 | RS.AN-2 |
| | | RS.AN-3 | RS.AN-3 | RS.AN-3 | RS.AN-3 | RS.AN-3 |
| | | RS.AN-4 | RS.AN-4 | RS.AN-4 | RS.AN-4 | RS.AN-4 |
| | Mitigation | RS.MI-1 | RS.MI-1 | RS.MI-1 | RS.MI-1 | RS.MI-1 |
| | | RS.MI-2 | RS.MI-2 | RS.MI-2 | RS.MI-2 | RS.MI-2 |
| | | RS.MI-3 | RS.MI-3 | RS.MI-3 | RS.MI-3 | RS.MI-3 |
| | Improvements | RS.IM-1 | RS.IM-1 | RS.IM-1 | RS.IM-1 | RS.IM-1 |
| | | RS.IM-2 | RS.IM-2 | RS.IM-2 | RS.IM-2 | RS.IM-2 |

Recover – The Recover Function supports timely recovery to normal operations to reduce the impact from a cybersecurity event. Defined Recovery objectives are needed when recovering from disruptions.

Table 6 RECOVER Business Mission Objectives

| | | Maintain Human Safety | Maintain Environmental Safety | Maintain Quality of Product | Maintain Production Goals | Maintain Trade Secrets |
|----------|-------------------|-----------------------|-------------------------------|-----------------------------|---------------------------|------------------------|
| Category | | Subcategories | | | | |
| RC | Recovery Planning | RC.RP-1 | RC.RP-1 | RC.RP-1 | RC.RP-1 | RC.RP-1 |
| | Improvements | RC.IM-1 | RC.IM-1 | RC.IM-1 | RC.IM-1 | RC.IM-1 |
| | | RC.IM-2 | RC.IM-2 | RC.IM-2 | RC.IM-2 | RC.IM-2 |
| | Communications | RC.CO-1 | RC.CO-1 | RC.CO-1 | RC.CO-1 | RC.CO-1 |
| | | RC.CO-2 | RC.CO-2 | RC.CO-2 | RC.CO-2 | RC.CO-2 |
| | RC.CO-3 | RC.CO-3 | RC.CO-3 | RC.CO-3 | RC.CO-3 | |

6. Manufacturing System Categorization and Risk Management

In addition to the Business/Mission Objectives for aligning a focused set of cybersecurity controls to support critical business goals, the Manufacturing Profile is also structured into three levels of security to be applied to a manufacturing system according to its categorization of Low, Moderate, or High.

6.1 Categorization Process

The Profile guidance is provided at three security levels: Low, Moderate, and High. These designations identify the security capability, functionality, and specificity for a defined risk level. A manufacturer or industry sector applies the Profile to a manufacturing system by categorizing its system or component(s) to a security level of Low, Moderate, or High.

The categorization is based on the potential impact if a security breach jeopardizes the manufacturing system or components, operational assets, individuals, or the organization. Security categorizations are to be used in conjunction with vulnerability and threat information in assessing the risk to an organization. FIPS 199, for example, defines three levels of potential impact on systems should there be a breach of security (i.e., a loss of integrity, availability, or confidentiality). The application of these definitions must take place within the context of the organization, facility, and manufacturing system.

The Profile defines the three security levels as follows:

1. The *potential impact* is **LOW** if the loss of integrity, availability, or confidentiality could be expected to have a **limited** adverse effect on manufacturing operations, assets, personnel, the general public, or the environment.
2. The *potential impact* is **MODERATE** if the loss of integrity, availability, or confidentiality could be expected to have a **serious** adverse effect on manufacturing operations, assets, personnel, the general public, or the environment.
3. The *potential impact* is **HIGH** if the loss of integrity, availability, or confidentiality could be expected to have a **severe or catastrophic** adverse effect on manufacturing operations, assets, personnel, the general public, or the environment.

The security categorization process influences the level of effort expended when implementing the Profile. Manufacturing systems supporting the most critical and/or sensitive operations and assets demand the greatest level of attention and effort to ensure that appropriate operational security and risk mitigation are achieved.

The tables below provide examples of mission-based rationale for selecting the security categorization of the manufacturing system:

Table 7 Manufacturing System Impact Levels [5]

| Impact Category | Low-Impact | Moderate-Impact | High-Impact |
|----------------------------|-----------------------------------|--------------------------|-----------------------------------|
| Injury | Cuts, bruises requiring first aid | Requires hospitalization | Loss of life or limb |
| Financial Loss | \$1,000 | \$100,000 | Millions |
| Environmental Release | Temporary damage | Lasting damage | Permanent damage, off-site damage |
| Interruption of Production | Minutes | Days | Weeks |
| Public Image | Temporary damage | Lasting damage | Permanent damage |

Table 8 Manufacturing System Impact Levels Based on Product Produced and Industry Concerns [5]

| Category | Low-Impact | Moderate-Impact | High-Impact |
|-------------------|---|--|---|
| Product Produced | Non-hazardous materials or products Non-ingested consumer products | Some hazardous products or steps during production High amount of proprietary information | Critical infrastructure (e.g., electricity) Hazardous materials Ingested products |
| Industry Examples | Plastic injection molding Warehousing | Automotive metal stamping Pulp and paper Semiconductors Automotive production | Utilities Petrochemical Food and beverage Pharmaceutical Military Contractors |

A limited adverse effect means that, for example, the loss of integrity, availability, or confidentiality might:

- cause a degradation in mission capability to an extent and duration that the system is able to perform its primary functions, but the effectiveness of the functions is noticeably reduced;
- result in minor damage to operational assets;
- result in minor financial loss;
- result in minor harm to individuals.

A serious adverse effect means that, for example, the loss of integrity, availability, or confidentiality might:

- cause a significant degradation in mission capability to an extent and duration that the system is able to perform its primary functions, but the effectiveness of the functions is significantly reduced;
- result in significant damage to operational assets;
- result in significant financial loss;
- result in significant harm to individuals but does not involve loss of life or serious life threatening injuries.

A severe or catastrophic adverse effect means that, for example, the loss of integrity, availability, or confidentiality might:

- cause a severe degradation in or loss of mission capability to an extent and duration that the system is not able to perform one or more of its primary functions;
- result in major damage to operational assets;
- result in major financial loss;
- result in severe or catastrophic harm to individuals involving loss of life or serious life threatening injuries.

6.2 Profile's Hierarchical Supporting Structure

The Profile guidance is scalable and supports intensifying security protections where needed, while maintaining a conventional baseline. Each higher security level builds from the baseline starting with the Low designation. The Moderate and High each include all of the stipulations from the levels below.

- A Moderate categorization includes all Moderate and Low security implementations
- A High categorization includes all High, Moderate, and Low security implementations

Each security level is positioned as the platform to support the next higher security level implementation, or categorization. The security level implementation starts with Low and increases in rigor through the Moderate and High implementations. The Low security level represents the starting baseline for all manufacturing systems. The Moderate security level will implement the Low security guidance as well as the Moderate. The High security level will implement all of the Low and Moderate guidance as well as the High inputs.

6.3 Risk Management

The Profile relies on the manufacturer's risk management processes to inform and prioritize decisions regarding cybersecurity. It supports recurring risk assessments and validation of business drivers to help manufacturers select target states for cybersecurity activities that reflect desired outcomes.

To manage cybersecurity risks, a clear understanding of the business drivers and security considerations specific to the Manufacturing system and its environment is required. Each organization's risk is unique, along with its use of ICS and IT, thus the implementation of the profile will vary.

The Manufacturing Profile is meant to enhance but not replace current cybersecurity standards and industry guidelines that the manufacturer is currently embracing. Manufacturers can determine activities that are important to critical service delivery and can prioritize investments to maximize the impact of each dollar spent. Ultimately, the Profile is aimed at reducing and better managing cybersecurity risks. The Profile, along with the Cybersecurity Framework, are not one-size-fits-all approaches to managing cybersecurity risk for critical infrastructure. Manufacturers will continue to have unique risks – different threats, different vulnerabilities, different risk tolerances – and how they implement security practices will vary.

7. Manufacturing Profile Subcategory Guidance

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|---|--------------------------------|---|---|---|
| IDENTIFY | ID.AM | ID.AM-1 | Low | 62443-2-1:2009 4.2.3.4 62443-3-3:2013 SR 7.8 |
| | | | Document an inventory of manufacturing system components that reflects the current system. | CM-8 |
| | | | Manufacturing system components include for example PLCs, sensors, actuators, robots, machine tools, firmware, network switches, routers, power supplies, and other networked components or devices. System component inventory is reviewed and updated as defined by the organization. | |
| | | | Moderate | |
| | | Employ automated mechanisms where feasible to detect the presence of unauthorized hardware and firmware components within the system. | CM-8 (1)(3)(5) | |
| | | High | | |
| | | Identify individuals who are both responsible and accountable for administering manufacturing system components. | CM-8 (2)(4) | |
| | | ID.AM-2 | Low | 62443-2-1:2009 4.2.3.4 62443-3-3:2013 SR 7.8 |
| Document an inventory of manufacturing system software components that reflects the current system. | CM-8 | | | |
| Manufacturing system software components include for example software license information, software version numbers, HMI and other ICS component applications, software, operating systems. System software inventory is reviewed and updated as defined by the organization. | | | | |
| | Moderate | | | |
| Update the inventory of manufacturing system software as an integral part of component installations, removals, and system updates. Employ automated mechanisms where feasible to detect the presence of unauthorized software within the system. | CM-8 (1)(3)(5) | | | |
| High | | | | |
| | | Identify individuals who are both responsible and accountable for administering manufacturing system software. | CM-8 (2)(4) | |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|----------|----------|-------------------------|---|--|
| IDENTIFY | | ID.AM-3 | <p style="text-align: center;">Low</p> <p>Document all connections within the manufacturing system, and between the manufacturing system and other systems. All connections are documented, authorized, and reviewed.</p> <p>Connection information includes, for example, the interface characteristics, data characteristics, ports, protocols, addresses, description of the data, security requirements, and the nature of the connection.</p> | 62443-2-1:2009 4.2.3.4 CA-3 |
| | | | <p style="text-align: center;">Moderate and High</p> <p>Map the flow of information within the manufacturing system and to external systems.</p> | AC-4 |
| | | ID.AM-4 | <p style="text-align: center;">Low</p> <p>Identify and document all external connections for the manufacturing system.</p> <p>Examples of external systems include engineering design services, and those that are controlled under separate authority, personal devices, and other hosted services.</p> | AC-20 |
| | | | <p style="text-align: center;">Moderate and High</p> <p>Require external providers to identify the functions, ports, protocols, and other services required for the use with the manufacturing system.</p> | SA-9(2) |
| | | ID.AM-5 | <p style="text-align: center;">Low, Moderate and High</p> <p>Identify and prioritize manufacturing system components and functions based on their classification, criticality, and business value.</p> <p>Identify the types of information in possession, custody, or control for which security safeguards are needed (e.g. sensitive or protected information). Address the security of protected information in its third-party relationships.</p> | 62443-2-1:2009 4.2.3.6 CP-2 |
| | | ID.AM-6 | <p style="text-align: center;">Low, Moderate and High</p> <p>Establish and maintain personnel cybersecurity roles and responsibilities for the manufacturing system. Include cybersecurity roles and responsibilities for third-party providers.</p> <p>Third-party providers are required to notify the organization of any personnel transition (including transfers or terminations) involving personnel with physical or logical access to the manufacturing system components.</p> <p>Third-party providers include, for example, service providers, contractors, and other organizations providing manufacturing system development, technology services, outsourced applications, or network and security management.</p> | 62443-2-1:2009 4.3.2.3.3 CP-2 PS-7 |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|-------------------------|---|--|--|-------------------------------|
| IDENTIFY | ID.BE | ID.BE-1 | <p align="center">Low and Moderate</p> <p>Define and communicate the organization's role in the supply chain. Identify the upstream and downstream supply channels that are outside of the organization's operations. Identify the overall mission supported by the manufacturing system.</p> | CP-2(1)(3)(8) |
| | | | <p align="center">High</p> <p>Protect against supply chain threats to the manufacturing system, system components, or system services by employing security safeguards as part of a comprehensive, defense-in-breadth security strategy.</p> | SA-12 |
| | | ID.BE-2 | <p align="center">Low, Moderate and High</p> <p>Define and communicate the manufacturer's place in critical infrastructure and its industry sector.</p> | PM-8 |
| | | | <p>Define and communicate critical infrastructure and key resources relevant to the manufacturing system. Develop, document, and maintain a critical infrastructure and key resources protection plan.</p> | |
| ID.BE-3 | <p align="center">Low, Moderate and High</p> <p>Establish and communicate priorities for manufacturing missions, objectives, and activities with consideration for security and the resulting risk to manufacturing operations, components, and individuals.</p> | 62443-2-1:2009 4.2.2.1 | | |
| | <p>Identify critical manufacturing system components and functions by performing a criticality analysis.</p> | PM-11 SA-14 | | |
| ID.BE-4 | <p align="center">Low</p> <p>Identify and prioritize supporting services for critical manufacturing system processes and components.</p> | PM-8,SA-14 | | |
| | <p>Provide an uninterruptable power supply for identified critical manufacturing system components to facilitate the transition of the manufacturing system to long-term alternate power in the event of a primary power source loss.</p> | PE-11 | | |
| | <p align="center">Moderate and High</p> <p>Identify alternate and redundant supporting services for critical manufacturing system processes and components.</p> | PE-9(1) | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference | |
|----------|----------|-------------|--|--|--|
| IDENTIFY | ID.BE-5 | | Low | CP-2 CP-2(3) CP-2(8) CP-2(2) CP-2(4)(5) | |
| | | | Establish resilience requirements for the manufacturing system to support delivery of critical services. | | |
| | | | Moderate | | |
| | | | Define a time period for the resumption of essential manufacturing system processes. | | |
| | | | Identify critical manufacturing system assets that support essential manufacturing system processes. | | |
| | ID.GV | ID.GV-1 | | Low, Moderate and High | 62443-2-1:2009 4.3.2.6 800-53 Security Policies-1 |
| | | | | Develop and disseminate a security policy that provides an overview of the security requirements for the manufacturing system. The policy includes for example the identification and assignment of roles, responsibilities, management commitment, coordination among organizational entities, and compliance. It also reflects coordination among organizational entities responsible for the different aspects of security (i.e., technical, physical, personnel, cyber-physical, access control, media protection, vulnerability management, maintenance, monitoring), and covers the full life cycle of the manufacturing system. | |
| | | | | Ensure the security policy is approved by a senior official with responsibility and accountability for the risk being incurred by manufacturing operations. | |
| | | | | Low, Moderate and High | |
| | | | | Develop and disseminate a security program for the manufacturing system that includes, for example, the identification of personnel security roles and assignment of responsibilities, management commitment, coordination among organizational entities, and compliance. This includes security requirements, roles and responsibilities for third-party providers. | |
| ID.GV-2 | | | Low, Moderate and High | 62443-2-1:2009 4.3.2.3.3 PM-1, PS-7 | |
| | | | Develop and disseminate a security program for the manufacturing system that includes, for example, the identification of personnel security roles and assignment of responsibilities, management commitment, coordination among organizational entities, and compliance. This includes security requirements, roles and responsibilities for third-party providers. | | |
| | | | Low, Moderate and High | | |
| ID.GV-3 | | | Low, Moderate and High | 62443-2-1:2009 4.4.3.7 800-53 Security Policies-1 | |
| | | | Ensure that legal and regulatory requirements affecting the manufacturing operations regarding cybersecurity are understood and managed. | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|----------|----------|-------------------------|--|--|
| IDENTIFY | ID.RA | ID.GV-4 | <p>Low, Moderate and High</p> <p>Develop a comprehensive strategy to manage risk to manufacturing operations. Include cybersecurity considerations in the risk management strategy. Determine and allocate required resources to protect the manufacturing system.</p> | 62443-2-1:2009 4.2.3.1, 4.2.3.3, 4.2.3.8, 4.2.3.9 PM-9 , PM-11 |
| | | ID.RA-1 | <p>Low and Moderate</p> <p>Develop a plan to identify, document, and report vulnerabilities that exist on the manufacturing system. Include the use of vulnerability scanning where feasible on the manufacturing system, its components, or a representative system.</p> <p>Develop a plan for continuous monitoring of the security posture of the manufacturing system to facilitate ongoing awareness of vulnerabilities.</p> <p>Conduct risk assessments on the manufacturing system that take into account vulnerabilities and potential impact to manufacturing operations and assets.</p> <p>High</p> <p>Conduct performance/load testing and penetration testing on the manufacturing system with care to ensure that manufacturing operations are not adversely impacted by the testing process.</p> <p>Identify where manufacturing system vulnerabilities may be exposed to adversaries.</p> <p>Production systems may need to be taken off-line before testing can be conducted. If the manufacturing system is taken off-line for testing, tests are scheduled to occur during planned manufacturing outages whenever possible. If penetration testing is performed on non-manufacturing networks, extra care is taken to ensure that tests do not propagate into the manufacturing network.</p> | 62443-2-1:2009 4.2.3, 4.2.3.7, 4.2.3.9, 4.2.3.12 CA-2 CA-7 RA-3 CA-2(2) , RA-5(4) |
| | | ID.RA-2 | <p>Low and Moderate</p> <p>Establish and maintain ongoing contact with security groups and associations, and receive security alerts and advisories. Security groups and associations include, for example, special interest groups, forums, professional associations, news groups, and/or peer groups of security professionals in similar organizations. Implement a threat awareness program that includes a cross-organization information-sharing capability. Organizations should consider having both an unclassified and classified information sharing capability.</p> | 62443-2-1:2009 4.2.3, 4.2.3.9, 4.2.3.12 PM-15 |

| Function | Category | Subcategory | Manufacturing Profile | Reference | |
|----------|----------|-------------------------|--|--|---|
| IDENTIFY | | | <p>Collaborate and share information about potential vulnerabilities and incidents on a timely basis. The DHS National Cybersecurity & Communications Integration Center (NCCIC) serves as a centralized location where operational elements involved in cybersecurity and communications reliance are coordinated and integrated. The Industrial Control Systems Cyber Emergency Response Team (ICS-CERT) collaborates with international and private sector Computer Emergency Response Teams (CERTs) to share control systems-related security incidents and mitigation measures.</p> <p style="text-align: center;">High</p> <p>Employ automated mechanisms where technically feasible to make security alert and advisory information available throughout the organization.</p> | <p>PM-16</p> <p>SI-5(1)</p> | |
| | | ID.RA-3 | <p style="text-align: center;">Low, Moderate and High</p> <p>Conduct and document periodic assessment of risk to the manufacturing system that takes into account threats and likelihood of impact to manufacturing operations and assets. The risk assessment includes threats from insiders and external parties.</p> | <p>62443-2-1:2009 4.2.3, 4.2.3.9, 4.2.3.12</p> <p>RA-3</p> | |
| | | ID.RA-4 | <p style="text-align: center;">Low, Moderate and High</p> <p>Conduct criticality reviews of the manufacturing system that define the potential adverse impacts to manufacturing operations, assets, and individuals if compromised or disabled.</p> | <p>62443-2-1:2009 4.2.3, 4.2.3.9, 4.2.3.12</p> <p>RA-2</p> | |
| | | ID.RA-5 | <p style="text-align: center;">Low, Moderate and High</p> <p>Conduct risk assessments of the manufacturing system incorporating threats, vulnerabilities, likelihood, and impact to manufacturing operations, assets, and individuals. Disseminate risk assessment results to relevant stakeholders.</p> | <p>RA-3, PM-16</p> | |
| | | ID.RA-6 | <p style="text-align: center;">Low, Moderate and High</p> <p>Develop and implement a comprehensive strategy to manage risk to the manufacturing system that includes the identification and prioritization of risk responses.</p> | <p>PM-9</p> | |
| | | ID.RM | ID.RM-1 | <p style="text-align: center;">Low, Moderate and High</p> <p>Establish a risk management process for the manufacturing system that effectively identifies, communicates, and facilitates addressing risk-related issues and information among key stakeholders internally and externally.</p> | <p>62443-2-1:2009 4.3.4.2</p> <p>PM-9</p> |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|----------|----------|-------------------------|--|---|
| IDENTIFY | | ID.RM-2 | <p>Low, Moderate and High</p> <p>Define the risk tolerance for the manufacturing system.</p> | 62443-2-1:2009 4.3.2.6.5 PM-9 |
| | | ID.RM-3 | <p>Low, Moderate and High</p> <p>Ensure the risk tolerance for the manufacturing system is informed by the organization's role in critical infrastructure and sector-specific risk analysis.</p> | PM-9, PM-8 |
| PROTECT | PR.AC | PR.AC-1 | <p>Low</p> <p>Establish and manage identification mechanisms and credentials for users and devices of the manufacturing system.</p> | 62443-2-1:2009 4.3.3.5.1; SR 1.1, 1.2, 1.3, 1.4, 1.5,1.7 IA-Family AC-2(1) |
| | | | <p>Moderate</p> <p>Employ automated mechanisms where feasible to support the management and auditing of information system credentials.</p> | AC-2(5) |
| | | | <p>High</p> <p>Deactivate system credentials after a specified time period of inactivity. Monitor the manufacturing system for atypical use of system credentials. Credentials associated with significant risk are disabled.</p> | AC-2(12)(13) |
| | | PR.AC-2 | <p>Low</p> <p>Protect physical access to the manufacturing facility. Determine access requirements during emergency situations. Maintain and review visitor access records to the facility where the manufacturing system resides. Physical access controls may include, for example, lists of authorized individuals, identity credentials, escort requirements, guards, fences, turnstiles, locks, monitoring of facility access.</p> | 62443-2-1:2009 4.3.3.3.2 PE-Family , PE-8 |
| | | | <p>Moderate</p> <p>Protect power equipment, power cabling, network cabling, and network access interfaces for the manufacturing system from accidental damage, disruption, and physical tampering. Employ redundant and physically separated power cables for critical manufacturing operations.</p> | PE-9 (1) |
| | | | <p>High</p> <p>Control physical access to the manufacturing system in addition to the physical access for the facility.</p> | PE-3 (1) |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|--|---|--|--|--|
| PROTECT | | PR.AC-3 | Low | 62443-2-1:2009 4.3.3.6.6 62443-3-3:2013 SR 1.13,2.6 |
| | | | Establish usage restrictions, connection requirements, implementation guidance, and authorizations for remote access to the manufacturing system. Provide an explicit indication of active remote access connections to users physically present at the devices. Remote access methods include, for example, wireless, dial-up, broadband, VPN connections, mobile device connections, and communications through external networks. | AC-17.19.20 SC-15 |
| | | Moderate and High | Allow remote access only through approved and managed access points. | AC-17(1)(2)(3)(4) AC-20(1)(2) |
| | | Monitor remote access to the manufacturing system, and employ cryptographic mechanisms where determined necessary. Allow only authorized use of privileged functions from remote access. Establish agreements and verify security for connections with external systems. | | |
| PR.AC-4 | Low | 62443-2-1:2009 4.3.3.7.3; 62443-3-3:2013 SR 2.1 AC-Controls AC-14 | | |
| | Define and manage access permissions for users of the manufacturing system. Identify and document user actions that can be performed on the manufacturing system without identification or authentication (e.g. during emergencies). | | | |
| | Moderate | Employ automated mechanisms where feasible to support the management of manufacturing system user accounts, including the disabling, auditing, notification, and removal of user accounts. Implement separation of duties for manufacturing system users. Limit, document, and explicitly authorize privileged user access to the manufacturing system. Audit the execution of privileged functions on the manufacturing system. | AC-2(1)(3) AC-5 AC-6(1)(2)(5)(9) | |
| High | Separation of duties includes, for example: dividing operational functions and system support functions among different roles; conducting system support functions with different individuals; and ensuring security personnel administering access control functions do not also administer audit functions. | | | |
| Enforce account usage restrictions for specific time periods and locality. Monitor manufacturing system usage for atypical use. Disable accounts of users posing a significant risk. Specific restrictions can include, for example, restricting usage to certain days of the week, time of day, or specific durations of time. Privileged user access through non-local connections to the manufacturing system is restricted and managed. | AC-2(11) (12)(13) | | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|----------|----------|-------------------------|--|--|
| PROTECT | | PR.AC-5 | <p style="text-align: center;">Low</p> <p>Protect network integrity of the manufacturing system, incorporating network segregation where appropriate. Identify and control connections between system components. Monitor and control connections and communications at the external boundary and at key internal boundaries within the manufacturing system. Employ boundary protection devices.</p> <p>Boundary protection mechanisms include, for example, routers, gateways, data diodes, and firewalls separating system components into logically separate networks or subnetworks.</p> | <p>62443-2-1:2009 4.3.3.4 62443-3-3:2013 SR 3.1, 3.8</p> <p>SC-7</p> |
| | | | <p style="text-align: center;">Moderate</p> <p>Limit external connections to the manufacturing system. Monitor and use managed interfaces to conduct external system connections. Deny by default connections to the managed interface. Disable split tunneling and covert channel options in conjunction with remote devices. Ensure the manufacturing system fails securely in the event of the operational failure of a boundary protection device.</p> | <p>AC-4</p> |
| | | | <p style="text-align: center;">High</p> <p>Employ, where feasible, authenticated proxy servers for defined communications traffic between the manufacturing system and external networks.</p> <p>Isolate manufacturing system components performing different missions.</p> | <p>SC-7(8) SC-7(21)</p> |
| | PR.AT | PR.AT-1 | <p style="text-align: center;">Low</p> <p>Provide security awareness training for all manufacturing system users and managers.</p> <p>Training could include, for example, a basic understanding of the protections and user actions needed to maintain security of the system, responding to suspected cybersecurity incidents, and awareness of operational security.</p> | <p>62443-2-1:2009 4.3.2.4.2</p> <p>AT-2</p> |
| | | | <p style="text-align: center;">Moderate and High</p> <p>Incorporate insider threat recognition and reporting into security awareness training.</p> | <p>AT-2(2)</p> |
| | | PR.AT-2 | <p style="text-align: center;">Low, Moderate and High</p> <p>Ensure that users with privileged access to the manufacturing system understand the requirements and responsibilities of their assignments.</p> <p>Establish standards for measuring, building, and validating individual qualifications for privileged users.</p> | <p>62443-2-1:2009 4.3.2.4.2</p> <p>AT-3 PM-13</p> |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|--|-------------------------|---|--|---|
| PROTECT | | PR.AT-3 | <p style="text-align: center;">Low</p> <p>Establish and enforce security requirements for third-party providers and users. Ensure that third-party providers understand their responsibilities regarding the security of the manufacturing system and the responsibilities of their assignments. Require notifications be given for any personnel transfers, termination, or transition involving personnel with physical or logical access to the manufacturing system components.</p> | ISA 62443-2-1:2009 4.3.2.4.2 PS-7 |
| | | | <p>Ensure that providers of external system services comply with defined security requirements. Monitor and audit external service providers for security compliance.</p> | SA-9 |
| | | | <p style="text-align: center;">Moderate and High</p> <p>Require external service providers to identify the functions, ports, protocols, and services necessary for the connection services.</p> | SA-9(2) |
| | | PR.AT-4 | <p style="text-align: center;">Low, Moderate and High</p> <p>Ensure that senior executives understand the requirements for the security and protection of the manufacturing system, and their responsibilities for achieving them.</p> | 62443-2-1:2009 4.3.2.4.2 AT-3 |
| | | PR.AT-5 | <p style="text-align: center;">Low, Moderate and High</p> <p>Ensure that personnel responsible for the physical protection and security of the manufacturing system and facility are trained for, and understand their responsibilities.</p> <p>Establish standards for measuring, building, and validating individual qualifications for physical security personnel.</p> | 62443-2-1:2009 4.3.2.4.2 AT-3 PM-13 |
| | PR.DS | PR.DS-1 | <p style="text-align: center;">Low</p> <p>None</p> | 62443-3-3:2013 SR 3.4, 4.1 |
| <p style="text-align: center;">Moderate and High</p> <p>Protect while at rest manufacturing system information determined to be critical.</p> | | | SC-28 | |
| | PR.DS-2 | <p style="text-align: center;">Low</p> <p>None</p> | 62443-3-3:SR 3.1,3.8,4.1 | |
| | | <p style="text-align: center;">Moderate and High</p> <p>Protect manufacturing system information when in transit.</p> <p>Implement cryptographic mechanisms where determined necessary to prevent unauthorized access, distortion, or modification of system data.</p> | SC-8 SC-8(1) | |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|--|--|---|---|--|
| PROTECT | | PR.DS-3 | Low | 62443-2-1:2009 4. 4.3.3.3.9 62443-3-3:2013 SR 4.2 |
| | | | Enforce accountability for all manufacturing system components throughout the system lifecycle, including removal, transfers, and disposition. | PE-16 |
| | | | Sanitize portable media prior to disposal, release, or reuse. All system components entering and exiting the facility are authorized, monitored, and controlled, and records are maintained of those items. | MP-6 |
| | | | Moderate | |
| | | | Update the inventory of manufacturing system components as an integral part of component installations, removals, and system updates. | CM-8(1) |
| | | | High | |
| | | Employ automated mechanisms where feasible to maintain an up-to-date, complete, accurate, and readily available inventory of manufacturing system components. | CM-8(2) | |
| | | Ensure that disposal actions are approved, tracked, documented, and verified. | MP-6(1) | |
| | | PR.DS-4 | Low, Moderate and High | 62443-3-3:2013 SR 7.1, 7.2 |
| | | Ensure that adequate resources are maintained for manufacturing system information processing, networking, telecommunications, and data storage. | CP-2(a).1.4.5 | |
| Protect the manufacturing system against, or limit the effects of, denial of service attacks. Off-load audit records from the manufacturing system for processing to an alternate system. | SC-5 AU-4(1) | | | |
| PR.DS-5 | Low | 62443-3-3:2013 SR 5.2 | | |
| Protect the manufacturing system against data leaks. Monitor the manufacturing system at the external boundary and at key internal points to detect unauthorized access and use. | SI-4 SC-7 | | | |
| Heighten system monitoring activity whenever there is an indication of increased risk to manufacturing operations and assets. Develop and document access agreements for all users of the manufacturing system. | SI-4 PS-6 | | | |
| Moderate and High | | | | |
| Regulate the information flow within the manufacturing system and to outside systems. Enforce controls restricting connections to only authorized interfaces. | AC-4 SC-7(3)(4) SI-4(4) | | | |
| Protect the system from information leakage due to electromagnetic signals emanations. | PE-19 | | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|----------|----------|-------------------------|--|---|
| PROTECT | | PR.DS-6 | <p style="text-align: center;">Low</p> <p>None</p> | 62443-3-3:SR 3.1, 3.3, 3.4, |
| | | | <p style="text-align: center;">Moderate</p> <p>Employ Software, firmware, and information integrity checks to detect unauthorized changes to manufacturing system components during startup and when determined necessary.</p> <p>Incorporate the detection of unauthorized changes to the manufacturing system into the system's incident response capability.</p> | SI-7(1) SI-7(7) |
| | | | <p style="text-align: center;">High</p> <p>Employ automated tools where feasible to provide notification upon discovering discrepancies during integrity verification.</p> <p>Employ automatic response capability with pre-defined security safeguards when integrity violations are discovered.</p> | SI-7(2) SI-7(5) |
| | | PR.DS-7 | <p style="text-align: center;">Low, Moderate and High</p> <p>Utilize an off-line development and testing system for implementing and testing changes to the manufacturing system.</p> | CM-2 |
| | PR.IP | PR.IP-1 | <p style="text-align: center;">Low</p> <p>Develop, document, and maintain a baseline configuration for the manufacturing system.</p> <p>Baseline configurations include for example, information about manufacturing system components (e.g. software license information, software version numbers, HMI and other ICS component applications, software, operating systems), current version numbers and patch information on operating systems and applications; and configuration settings/parameters), network topology, and the logical placement of those components within the system architecture.</p> <p>Configure the manufacturing system to provide only essential capabilities. Review the baseline configuration and disable unnecessary capabilities.</p> | 62443-2-1:2009 4.3.4.3.2, 62443-3-3:2013 SR 7.6 CM-2 CM-6 CM-7 CM-7(1) |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|----------|----------|-------------------------|--|--|
| PROTECT | | | <p align="center">Moderate</p> <p>Review and update the baseline configuration of the manufacturing system as an integral part of system component installations and upgrades. Retain previous versions of the baseline configuration to support rollback. Employ software program usage restrictions.</p> <p>Develop a configuration management plan for the manufacturing system. The plan includes, for example, configuration processes, roles, lifecycle definition, configuration items, and control methods.</p> <p>Define configuration parameters, capabilities, and fail-to-known-state procedures such that, upon a system failure (or failure conditions), assets revert to a state that achieves a predetermined mode of operation.</p> <p>Employ a deny-all, permit-by-exception policy to allow the execution of only authorized software programs.</p> | <p>CM-2(1)(3)</p> <p>CM-7(2)</p> <p>CM-9</p> <p>SC-24</p> <p>CM-7(5)</p> |
| | | | <p align="center">High</p> <p>Employ automated mechanisms where feasible to maintain an up-to-date, complete, accurate, and readily available baseline configuration of the manufacturing system. Automated system support includes for example, documentation, notification, and management of the change control process on the manufacturing system.</p> <p>Review system changes to determine whether unauthorized changes have occurred.</p> | <p>CM-2(2) CM-3(1)</p> <p>CM-5(1)(2)</p> |
| | | PR.IP-2 | <p align="center">Low</p> <p>Manage the manufacturing system using a system development life cycle that includes security considerations.</p> <p>Include security requirements into the acquisition process of the manufacturing system and its components.</p> <p align="center">Moderate and High</p> <p>Require the developer of the manufacturing system and system components to provide a description of the functional properties of security controls, and design and implementation information for security-relevant system interfaces.</p> <p>Apply security engineering principles into the specification, design, development, implementation, and modification of the manufacturing system.</p> <p>Employ configuration management and change control during the development of the manufacturing system and its components, and include flaw tracking and resolution, and security testing.</p> | <p>62443-2-1:2009 4.3.4.3.3</p> <p>SA-3</p> <p>SA-4</p> <p>SA-4(1)(2)</p> <p>SA-8</p> <p>SA-10</p> |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|---|--|--|---|--|
| PROTECT | | PR.IP-3 | Low | 62443-2-1:2009 4.3.4.3.2 62443-3-3:2013 SR 7.6 |
| | | | Employ configuration change control for the manufacturing system and its components. Conduct security impact analyses in connection with change control reviews. | CM-3 CM-4 |
| | | | Moderate | |
| | | | Test, validate, and document changes to the manufacturing system before implementing the changes on the operational system. | CM-3(2) |
| | | | Review and authorize proposed configuration-controlled changes prior to implementing them on the manufacturing system. | |
| | | High | | |
| | | Employ automated mechanisms where feasible to support the change control process. | CM-3(1) CM-4(1) | |
| | | Conduct security impact analysis in a separate test environment before implementation into an operational environment for planned changes to the manufacturing system. | | |
| | | PR.IP-4 | Low | 62443-2-1:2009 4.3.4.3.9 62443-3-3:2013 SR 7.3, 7.4 |
| | | | Conduct and maintain backups for manufacturing system data. | CP-9 CP-4 |
| Manufacturing system data includes for example software, configurations and settings, documentation, system configuration data includes computer configuration backups, application configuration backups, operational control limits, control bands and set points for pre-incident operation for all ICS programmable equipment | | | | |
| Moderate | | | | |
| Verify the reliability and integrity of backups. | CP-9(1) | | | |
| Coordinate backup testing with organizational elements responsible for related plans. | CP-4(1) | | | |
| Establish a separate alternate storage site for system backups and ensure the same security safeguards are employed. | CP-6 | | | |
| High | | | | |
| Include into contingency plan testing the conducting of restorations from backup data. | CP-9(2) CP-9(3) | | | |
| Store critical manufacturing system backup information separately. | | | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference | |
|--|---|---|---|--|--|
| PROTECT | PR.IP | PR.IP-5 | Low and Moderate | 62443-2-1:2009 4.3.3.3.1 | |
| | | | Define, implement, and enforce policy and regulations regarding emergency and safety systems, fire protection systems, and environment controls for the manufacturing system. | PE-Family [10,12,13,14,15,18] PE-13(3) | |
| | | | Fire suppression mechanisms should take the manufacturing environment into account (e.g., water sprinkler systems could be hazardous in specific environments). | | |
| | | | | High | |
| | | Employ fire detection devices that activate and notify key personnel automatically in the event of a fire. | PE-13(1)(2) | | |
| | | PR.IP-6 | Low and Moderate | 62443-2-1:4.3.3.3.1 62443-3-3:2013 SR 4.2 | |
| | | | Ensure that manufacturing system data is destroyed according to policy. | MP-6 | |
| | | | High | | |
| | | Ensure that media sanitization actions are approved, tracked, documented, and verified. Test sanitation equipment and procedures. | MP-6(1)(2)(3) | | |
| Apply nondestructive sanitization techniques to portable storage devices connecting to the manufacturing system. | | | | | |
| PR.IP-7 | Low | 62443-2-1:2009 4.4.3.1, 4.4.3.2, 4.4.3.3, 4.4.3.4, | | | |
| | Incorporate improvements derived from the monitoring, measurements, assessments, and lessons learned into protection process revisions. | PM-6 CA-2 CA-7 SI-4 | | | |
| | Ensure that the security plan for the manufacturing system facilitates the review, testing, and continual improvement of the security protection processes. | PL-2 , PM-14 | | | |
| | | Moderate and High | | | |
| Employ independent teams to assess the protection process. | CA-2(1) , CA-7(1) | | | | |
| Independent teams, for example, may include internal or external impartial personnel. Impartiality implies that assessors are free from any perceived or actual conflicts of interest with regard to the development, operation, or management of the manufacturing system under assessment or to the determination of security control effectiveness. | | | | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference | |
|----------|--------------------------|---|--|--|-------------------------|
| PROTECT | | PR.IP-8 | Low, Moderate and High | AC-21 AC-21(1) | |
| | | | Collaborate and share information about manufacturing system related security incidents and mitigation measures with designated sharing partners. | | |
| | | | Employ automated mechanisms where feasible to assist in information collaboration. | | |
| | | | | Manufacturing systems are often connected to business systems or interconnected. Any single system can be an attack vector for all systems. It is therefore necessary to provide a uniform defense encompassing all baselines. | |
| | PR.IP | PR.IP-9 | Low | 62443-2-1:2009 4.3.2.5.3, CP-2 IR-8 | |
| | | | Develop and maintain response and recovery plans that identify essential functions and associated contingency requirements, as well as providing a roadmap for implementing incident response. Plans should incorporate recovery objectives, restoration priorities, metrics, contingency roles, personnel assignments and contact information. Address maintaining essential functions despite system disruption, and the eventual restoration of the manufacturing system. | | |
| | | | Define incident types, resources and management support needed to effectively maintain and mature the incident response and contingency capabilities. | | |
| | | | | Moderate and High | CP-2(1) |
| | | Coordinate contingency plan development with stakeholders responsible for related plans. | | | |
| | | | | Low | |
| | PR.IP-10 | Test response and recovery plans to determine the effectiveness of the plans, and the readiness to execute the plans. | 162443-2-1:2009 4.3.2.5.7 62443-3-3:2013 SR 3.3 CP-4 , PM-14 | | |
| | | Moderate and High | CP-4(1) IR-3(2) | | |
| | | Coordinate testing of response and recovery plans with relevant stakeholders. Related plans include, for example, Business Continuity Plans, Disaster Recovery Plans, Continuity of Operations Plans, Crisis Communications Plans, Critical Infrastructure Plans, Cyber Incident Response Plans, and Occupant Emergency Plans. | | | |
| | PR.IP-11 | Low, Moderate and High | 62443-2-1:2009 4.3.3.2.1 PS- Family | | |
| | | Develop and maintain a personnel security program for the manufacturing system. Personnel security program should include policy, position risk designations, personnel screening, terminations and transfers, access agreements, third-party roles and responsibilities, and personnel sanctions. | | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference | |
|--|-------------------------|--------------------------|--|--|-------------------------|
| PROTECT | | PR.IP-12 | Low | RA-3 , SI-2 | |
| | | | Establish and maintain a process that allows continuous review of vulnerabilities, and defines strategies to mitigate them. | | |
| | | | Moderate | | |
| | | | | Restrict access to privileged vulnerability data. | RA-5(5) |
| | | | | High | |
| | | | | Identify where manufacturing system vulnerabilities may be exposed to adversaries. | RA-5(4) |
| | PR.MA | PR.MA-1 | Low | 62443-2-1:2009 4.3.3.3.7 | |
| | | | Schedule, perform, document and review records of maintenance and repairs on manufacturing system components. | | |
| | | | Establish a process for maintenance personnel authorization, and escort non-authorized maintenance personnel. | | MA-5 |
| | | | Verify impacted security controls following maintenance or repairs. | | MA-2 |
| Moderate | | | | | |
| Enforce approval requirements, control, and monitoring of maintenance tools for use on the manufacturing system. Maintenance tools can include, for example, hardware/software diagnostic test equipment and hardware/software packet sniffers. | | | MA-3 | | |
| Perform preventative maintenance at defined intervals. Inspect maintenance tools brought into the facility. | | | MA-6 MA-3(1) | | |
| Check media containing diagnostic and test programs for malicious code before they are used on the manufacturing system. | MA-3(2) | | | | |
| | | | High | | |
| | | | Employ automated mechanisms where feasible to schedule, conduct, and document maintenance and repairs; and to produce records of maintenance activity. | MA-2(2) MA-3(3) | |
| | | | Prevent the unauthorized removal of maintenance equipment containing manufacturing system information. | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|----------|----------|-------------------------|--|---|
| PROTECT | | PR.MA-2 | <p style="text-align: center;">Low and Moderate</p> <p>Enforce approval requirements, control, and monitoring, of remote maintenance activities. Employ strong authenticators, record keeping, and session termination for remote maintenance.</p> | 62443-2-1:2009 4.3.3.6.5 MA-4 |
| | | | <p style="text-align: center;">High</p> <p>Require that diagnostic services pertaining to remote maintenance be performed from a system that implements a security capability comparable to the capability implemented on the manufacturing system.</p> | MA-4(3) |
| | PR.PT | PR.PT-1 | <p style="text-align: center;">Low</p> <p>Generate audit records containing information that establishes what type of event occurred, when the event occurred, where the event occurred, the source of the event, the outcome of the event, and the identity of any individuals or manufacturing components associated with the event. Ensure that audit processing failures on the manufacturing system generate alerts and trigger defined responses. Generate time stamps from an internal system clock that is mapped to Coordinated Universal Time (UTC) or Greenwich Mean Time (GMT).</p> <p style="text-align: center;">Moderate</p> <p>Review and update audit events.</p> <p>Employ automated mechanisms to integrate audit review, analysis, and reporting.</p> <p>Compare and synchronize the internal system clocks to an authoritative time source. Authoritative time sources include for example, an internal NTP server, radio clock, atomic clock, GPS time source.</p> <p style="text-align: center;">High</p> <p>Integrate analysis of audit records with physical access monitoring.</p> <p>Conduct time correlation of audit records.</p> <p>Enable authorized individuals to extend audit capabilities when required by events.</p> | 62443-2-1:2009 4.3.3.3.9, 62443-3-3:2013 SR 2.8, AU-3 AU-5 AU-8 AU-2(3) AU-6(1) AU-7(1) AU-6(6) AU-12(1) AU-12(3) |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|---|---|---|---|--|
| PROTECT | | PR.PT-2 | Low | 62443-3-3:2013 SR 2.3 |
| | | | Employ technical safeguards to restrict the use of portable storage devices. | MP-2 |
| | | | Moderate and High | |
| | | Protect and control portable storage devices containing manufacturing system data while in transit and in storage. | MP-4 MP-7 | |
| | | PR.PT-3 | Low | 62443-2-1:2009 4.3.3.5.1, 62443-3-3:2013 SR 1.1, SR AC-3 |
| | | | Employ technical safeguards to control access to the manufacturing system and assets. | |
| | Moderate and High | | | |
| | Disable defined functions, ports, protocols, and services within the manufacturing system deemed to be unnecessary. Employ technical safeguards to enforce a deny-all, permit-by-exception policy to only allow the execution of authorized software programs. | CM-7(1) , CM-7(5) | | |
| | PR.PT-4 | Low | 62443-3-3:2013 SR 3.1, SR | |
| | | Monitor and control communications at the external boundary and at key internal boundaries within the manufacturing system. | SC-7 | |
| | | Moderate and High | | |
| | | Control the flow of information within the manufacturing system and between interconnected systems. Information flow may be supported, for example, by labeling or coloring physical connectors as an aid to manual hookup. Inspection of message content may enforce information flow policy. For example, a message containing a command to an actuator may not be permitted to flow between the control network and any other network. Physical addresses (e.g., a serial port) may be implicitly or explicitly associated with labels or attributes (e.g., hardware I/O address). Manual methods are typically static. Label or attribute policy mechanisms may be implemented in hardware, firmware, and software that controls or has device access, such as device drivers and communications controllers. | AC-4 , | |
| Limit external connections to the system. | | SC-7(3) , | | |
| Manage the interface for external telecommunication services by establishing a traffic flow policy, protecting the confidentiality and integrity of the information being transmitted, reviewing and documenting each exception to the traffic flow policy. | | SC-7(4) | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|---|--|-------------------------|---|---|
| DETECT | DE.AE | DE.AE-1 | Low, Moderate and High | 62443-2-1:2009 4.4.3.3 |
| | | | Ensure that a baseline of network operations and expected data flows for the manufacturing system is developed, documented, and maintained to detect events. | CM-2 |
| | | DE.AE-2 | Low | 62443-2-1:2009 4.3.4.5.6, 62443-3-3:2013 SR 2.8, 2.9 |
| | | | Review and analyze detected events within the manufacturing system to understand attack targets and methods. | AU-6 , IR-4 |
| | | DE.AE-2 | Moderate and High | |
| | | | Employ automated mechanisms where feasible to review and analyze detected events within the manufacturing system. | AU-6(1) IR-4(1) |
| | | DE.AE-3 | Low and Moderate | 62443-3-3:2013 SR 6.1 |
| | | | Ensure that event data is compiled and correlated across the manufacturing system using various sources such as event reports, audit monitoring, network monitoring, physical access monitoring, and user/administrator reports. | IR-5 |
| | | DE.AE-3 | High | |
| | | | Integrate analysis of events where feasible with the analysis of vulnerability scanning information; performance data; manufacturing system monitoring, and facility monitoring to further enhance the ability to identify inappropriate or unusual activity. | AU-6(5)(6) AU-12(1) |
| | | DE.AE-4 | Low | |
| | | | Determine negative impacts to manufacturing operations, assets, and individuals resulting from detected events, and correlate with risk assessment outcomes. | RA-3 |
| Moderate | | | | |
| Employ automated mechanisms to support impact analysis. | IR-4(1) SI-4(2) | | | |
| DE.AE-4 | High | | | |
| | Correlate detected event information and responses to achieve perspective on event impact across the organization. | IR-4(4) | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference | |
|--|-------------------------|---|---|---|---|
| DETECT | | DE.AE-5 | Low | 62443-2-1:2009 4.2.3.10 | |
| | | | Define incident alert thresholds for the manufacturing system. | IR-4 , IR-5 , AU-2 , AU-3 , IR-8 | |
| | | | Moderate and High | | |
| | | | | Employ automated mechanisms where feasible to assist in the identification of security alert thresholds. | IR-4(1) IR-5(1) |
| | DE.CM | DE.CM-1 | Low | 62443-3-3:2013 SR 6.2 | |
| | | | Conduct ongoing security status monitoring of the manufacturing system network to detect attacks and indicators of potential attacks. | CA-7d AC-2g , | |
| | | | Detect unauthorized local, network, and remote connections, and identify unauthorized use of the manufacturing system. | SI-4b | |
| | | | Generate audit records for defined cybersecurity events. | AU-12c | |
| | | | Monitor network communications at the external boundary of the system and at key internal boundaries within the system. | SC-7 , SI-4(4) | |
| | | | Heighten system monitoring activity whenever there is an indication of increased risk. | SI-4e | |
| Moderate | | | | | |
| Employ automated mechanisms to support detection of cybersecurity events. | | | AC-2 (1)(2)(3)(4) , SI-4(2) SI-4(5) | | |
| Generate system alerts when indications of compromise or potential compromise occur. | | | | | |
| | | | High | | |
| | | | Monitor for and report atypical usage of the manufacturing system. | AC-2(12) | |
| | DE.CM-2 | Low | 62443-2-1:2009 4.3.3.3.8 | | |
| Conduct ongoing security status monitoring of the manufacturing system facility to detect physical security incidents. | | CA-7d , PE-6 , PE-3 | | | |
| Moderate and High | | | | | |
| | | | Employ independent teams to monitor the security of the physical environment. | CA-7(1) | |
| | | | Monitor physical intrusion alarms and surveillance equipment. | PE-6(1) PE-6(4) PE-3(1) | |
| | | | Monitor physical access to the manufacturing system and devices in addition to the facility. | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|----------|----------|-------------------------|---|--|
| DETECT | | DE.CM-3 | <p>Low, Moderate and High</p> <p>Conduct security status monitoring of personnel activity associated with the manufacturing system.</p> <p>Enforce software usage and installation restrictions.</p> | <p>62443-3-3:2013 SR 6.2</p> <p>CA-7d CM-10, CM-11</p> |
| | | DE.CM-4 | <p>Low</p> <p>Deploy malicious code protection mechanisms throughout the manufacturing system where feasible to detect and eradicate malicious code.</p> <p>Update malicious code protection mechanisms whenever new releases are available in accordance with the configuration management policy and procedures for the manufacturing system.</p> <p>Manage for false positives during malicious code detection and eradication.</p> <p>Moderate and High</p> <p>Automatically update malicious code protection mechanisms where feasible.</p> | <p>62443-2-1:2009 4.3.4.3.8 62443-3-3:2013 SR 3.2</p> <p>SI-3</p> <p>SI-3d</p> <p>SI-3(2)</p> |
| | | DE.CM-5 | <p>Low</p> <p>None</p> <p>Moderate and High</p> <p>Define acceptable and detect unacceptable mobile code and mobile code technologies. Mobile code technologies include, for example, Java, JavaScript, ActiveX, Postscript, PDF, Shockwave movies, Flash animations, and VBScript.</p> <p>Enforce usage restrictions and establish implementation guidance for acceptable mobile code and mobile code technologies for use with the manufacturing system.</p> <p>The use of mobile code technologies is determined after careful consideration and after verification that it does not adversely impact the operational performance of the manufacturing system.</p> | <p>62443-3-3:2013 SR 2.4</p> <p>SC-18</p> |
| | | DE.CM-6 | <p>Low Moderate and High</p> <p>Conduct ongoing security status monitoring of external service provider activity on the manufacturing system.</p> <p>Detect attacks and indicators of potential attacks from external service providers.</p> <p>Monitor compliance of external providers with personnel security policies and procedures, and contract security requirements.</p> | <p>CA-7d</p> <p>SI-4</p> <p>PS-7, SA-4, SA-9, MA-5</p> |

| Function | Category | Subcategory | Manufacturing Profile | Reference | | | |
|----------|----------|-------------------------|-------------------------------|---|---|-------------------------------|--|
| DETECT | | DE.CM-7 | Low | <p>Conduct ongoing security status monitoring on the manufacturing system for unauthorized personnel, connections, devices, access points, and software.</p> <p>Monitor for system inventory discrepancies.</p> <p>Deploy monitoring devices strategically within the manufacturing system to collect essential information to detect specific events of interest.</p> <p style="text-align: center;">Moderate and High</p> <p>Monitor for unauthorized configuration changes to the manufacturing system.</p> | CA-7d CM-8 SI-4 CM-3 | | |
| | | | Low, Moderate and High | | 62443-2-1:2009 4.2.3.1 RA-5 | | |
| | | | DE.DP | | DE.DP-1 | Low, Moderate and High | 62443-2-1:2009 4.4.3.1 CA-2 , CA-7 , PM-14 |
| | | | | | | Low, Moderate and High | 62443-2-1:2009 4.4.3.2 CA-2 |
| | | | | | | | |
| | | | | | | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|--|---|-------------------------|---|--|
| DETECT | | DE.DP-3 | Low, Moderate and High | 62443-2-1:2009 4.4.3.2 62443-3-3:2013 SR 3.3 |
| | | | Validate that event detection processes are operating as intended. | PM-14 |
| | | DE.DP-4 | Low | 62443-2-1:2009 4.3.4.5.9 62443-3-3:2013 SR 6.1 |
| | | | Communicate event detection information to defined personnel. Event detection information includes for example, alerts on atypical account usage, unauthorized remote access, wireless connectivity, mobile device connection, altered configuration settings, contrasting system component inventory, use of maintenance tools and nonlocal maintenance, physical access, temperature and humidity, equipment delivery and removal, communications at the information system boundaries, use of mobile code, use of VoIP, and malware disclosure. | AU-6 SI-4 |
| | | | Moderate and High | |
| | | | Employ automated mechanisms and system generated alerts to support event detection communication. | AU-6(1) SI-4(5) |
| | | DE.DP-5 | Low | 62443-2-1:2009 4.4.3.4 |
| | | | Incorporate improvements derived from the monitoring, measurements, assessments, and lessons learned into detection process revisions. | CA-2 , CA-7 , SI-4 |
| | | | Ensure the security plan for the manufacturing system provides for the review, testing, and continual improvement of the security detection processes. | PL-2 , PM-14 |
| Moderate | | | | |
| Employ independent teams to assess the detection process. | CA-2(1) , CA-7(1) | | | |
| High | | | | |
| Conduct specialized assessments including in-depth monitoring, vulnerability scanning, malicious user testing, insider threat assessment, performance/load testing, and verification and validation testing on the manufacturing system. | CA-2(7) | | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|--|---|--|---|---|
| RESPOND | RS.RP | <u>RS.RP-1</u> | Low, Moderate and High | 62443-2-1:2009 4.3.4.5.1 |
| | | | Execute the response plan during or after a cybersecurity event on the manufacturing system. | <u>IR-8</u> , <u>IR-4</u> |
| | RS.CO | <u>RS.CO-1</u> | Low, Moderate and High | 62443-2-1:2009 4.3.4.5.2 |
| | | | Ensure personnel understand objectives, restoration priorities, task sequences and assignment responsibilities for event response. | <u>CP-2</u> , <u>CP-3</u> , <u>IR-8</u> |
| | | <u>RS.CO-2</u> | Low | 62443-2-1:2009 4.3.4.5.5 |
| | | | Employ prompt reporting to appropriate stakeholders for cybersecurity events on the manufacturing system. Ensure that cybersecurity events on the manufacturing system are reported consistent with the response plan. | <u>IR-6</u> , <u>AU-6</u> |
| | | | Moderate and High | |
| | | | Employ automated mechanisms to assist in the reporting of cybersecurity events. | <u>IR-6(1)</u> |
| | | <u>RS.CO-3</u> | Low, Moderate and High | 62443-2-1:2009 4.3.4.5.2 |
| | | Share cybersecurity incident information with relevant stakeholders per the response plan. | <u>CA-2d</u> , <u>CA-7g</u> , <u>CP-2f</u> | |
| <u>RS.CO-4</u> | Low | 62443-2-1:2009 4.3.4.5.5 | | |
| | Coordinate cybersecurity incident response actions with all relevant stakeholders. Stakeholders for incident response include for example, mission/business owners, manufacturing system owners, integrators, vendors, human resources offices, physical and personnel security offices, legal departments, operations personnel, and procurement offices. | <u>CP-2</u> , <u>CP-2(1)</u> , <u>IR-4</u> | | |
| Moderate and High | | | | |
| Employ automated mechanisms to support stakeholder coordination. | <u>IR-4(1)</u> | | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference | |
|----------|----------|-------------------------|--|---|--|
| RESPOND | | RS.CO-5 | Low, Moderate and High | PM-15 , SI-5 | |
| | | | Share cybersecurity event information voluntarily, as appropriate, with industry security groups to achieve broader cybersecurity situational awareness. For example, the DHS National Cybersecurity & Communications Integration Center (NCCIC) serves as a centralized location where operational elements involved in cybersecurity and communications reliance are coordinated and integrated. The Industrial Control Systems Cyber Emergency Response Team (ICS-CERT) collaborates with international and private sector Computer Emergency Response Teams (CERTs) to share control systems-related cybersecurity incidents and mitigation measures. | | |
| | | RS.AN-1 | Low | 62443-2-1:2009 4.3.4.5.6 62443-3-3:2013 SR 6.1 IR-4 , CA-7 , AU-6 | |
| | | | Moderate and High | Investigate cybersecurity-related notifications generated from detection systems. Employ automated mechanisms to assist in the investigation and analysis of cybersecurity-related notifications. IR-5(1) , SI-4(2) | |
| | | RS.AN | RS.AN-2 | Low | 62443-2-1:2009 4.3.4.5.6 IR-4(4) |
| | | | | Moderate and High | Understand the full implication of the cybersecurity incident based on thorough investigation and analysis results. Correlate detected event information and incident responses with risk assessment outcomes to achieve perspective on incident impact across the organization. Employ automated mechanisms to support incident impact analysis. IR-4(1) , SI-4(2) |
| | | RS.AN-3 | | Low | 62443-3-3:SR 2.8, 2.9, 2.10 IR-4 |
| | | | | Moderate and High | Conduct forensic analysis on collected cybersecurity event information to determine root cause. Provide on-demand audit review, analysis, and reporting for after-the-fact investigations of cybersecurity incidents. AU-7(1) |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|----------------|--------------|--------------------------------|--|--|
| RESPOND | | <u>RS.AN-4</u> | <p>Low, Moderate and High</p> <p>Categorize cybersecurity incidents according to level of severity and impact consistent with the response plan.</p> | <p>62443-2-1:2009 4.3.4.5.6</p> <p><u>RA-3</u>, <u>PM-9</u>, <u>IR-4</u></p> |
| | RS.MI | <u>RS.MI-1</u> | <p>Low, Moderate and High</p> <p>Contain cybersecurity incidents to minimize impact on the manufacturing system.</p> | <p>62443-2-1:2009 4.3.4.5.6</p> <p>62443-3-3:2013 SR 5.1, SR <u>IR-4</u>, <u>IR-4(1)</u></p> |
| | | <u>RS.MI-2</u> | <p>Low</p> <p>Mitigate cybersecurity incidents occurring on the manufacturing system.</p> | <p>62443-2-1:2009 4.3.4.5.6,</p> <p><u>IR-4</u></p> |
| | | | <p>Moderate and High</p> <p>Employ automated mechanisms to support the cybersecurity incident mitigation process.</p> | <p><u>IR-4(1)</u></p> |
| | | <u>RS.MI-3</u> | <p>Low, Moderate and High</p> <p>Ensure that vulnerabilities identified while responding to a cybersecurity incident are mitigated or documented as accepted risks.</p> | <p><u>RA-5</u>, <u>RA-3</u></p> |
| | RS.IM | <u>RS.IM-1</u> | <p>Low, Moderate and High</p> <p>Incorporate lessons learned from ongoing incident handling activities into incident response procedures, training, and testing, and implement the resulting changes accordingly.</p> | <p>62443-2-1:2009 4.3.4.5.10</p> <p><u>IR-4</u></p> |
| | | <u>RS.IM-2</u> | <p>Low, Moderate and High</p> <p>Update the response plans to address changes to the organization, manufacturing system, attack vectors, or environment of operation and problems encountered during plan implementation, execution, or testing.</p> <p>Updates may include, for example, responses to disruptions or failures, and predetermined procedures.</p> <p>Enable a process for the response plan to evolve to reflect new threats, improved technology, and lessons learned.</p> | <p><u>CP-2</u></p> |

| Function | Category | Subcategory | Manufacturing Profile | Reference | |
|----------|----------|-------------------------|--|---|-------------------------|
| RECOVER | RC.RP | RC.RP-1 | Low and Moderate | IR-8 , CP-10 CP-10(4) | |
| | | | Execute the recovery plan during or after a cybersecurity incident on the manufacturing system. | | |
| | | | Restore the manufacturing system within a predefined time-period from configuration-controlled and integrity-protected information representing a known, operational state for the components. | | |
| | | | | High | |
| | | | | Continue essential manufacturing functions and services with little or no loss of operational continuity, and sustain continuity until full system restoration. | CP-2(5) |
| | | | | | |
| | RC.IM | RC.IM-1 | Low, Moderate and High | 62443-2-1 4.4.3.4 IR-4 | |
| | | RC.IM-2 | Low, Moderate and High | CP-2 , IR-8 | |
| | | | | | |
| | RC.CO | RC.CO-1 | Low | COBIT 5 EDM03.02 | |
| | | | Centralize and coordinate information distribution, and manage the public facing representation of the organization. | | |
| | | | Public relations management may include, for example, managing media interactions, coordinating and logging all requests for interviews, handling and ‘triaging’ phone calls and e-mail requests, matching media requests with appropriate and available internal experts who are ready to be interviewed, screening all of information provided to the media, ensuring personnel are familiar with public relations and privacy policies. | | |
| | | | | | |
| | | | Moderate | | |
| | | | Assign a Public Relations Officer. | | |
| | | | | | |
| | | | High | | |
| | | | Pre-establish media contacts. | | |
| | | | Utilize external assets to manage public relations. | | |

| Function | Category | Subcategory | Manufacturing Profile | Reference |
|----------|----------|-------------------------|---|---------------------------|
| RECOVER | | RC.CO-2 | <p>Low, Moderate and High</p> <p>Employ a crisis response strategy to protect against negative impact and repair organizational reputation.</p> <p>Crisis response strategies include, for example, actions to shape attributions of the crisis, change perceptions of the organization in crisis, and reduce the negative effect generated by the crisis.</p> | COBIT 5 EDM03.02 |
| | | RC.CO-3 | <p>Low, Moderate and High</p> <p>Communicate recovery activities to all relevant stakeholders, and executive and management teams.</p> | CP-2 IR-4 |

DRAFT

Appendix A - Acronyms and Abbreviations

Selected acronyms and abbreviations used in the Manufacturing Profile are defined below.

| | |
|-----------------|--|
| CAN | Controller Area Network |
| CSF | Cybersecurity Framework |
| FIPS | Federal Information Processing Standards |
| HMI | Human Machine Interface |
| ICS | Industrial Control System |
| ICS-CERT | Industrial Control Systems Cyber Emergency Response Team |
| IEC | International Electrotechnical Commission |
| ISA | The International Society of Automation |
| IT | Information Technology |
| LAN | Local Area Network |
| NCCIC | National Cybersecurity & Communications Integration Center |
| NIST | National Institute of Standards and Technology |
| NVD | National Vulnerabilities Database |
| OT | Operational Technology |
| PLC | Programmable Logic Controller |
| RF | Radio Frequency |
| RTU | Remote Terminal Unit |
| US-CERT | United States Computer Emergency Readiness Team |
| VPN | Virtual Private Network |

Appendix B - Glossary

Selected terms used in the Manufacturing Profile are defined below.

Actuator - A device for moving or controlling a mechanism or system. It is operated by a source of energy, typically electric current, hydraulic fluid pressure, or pneumatic pressure, and converts that energy into motion. An actuator is the mechanism by which a control system acts upon an environment. The control system can be simple (a fixed mechanical or electronic system), software-based (e.g. a printer driver, robot control system), or a human or other agent. [800-82]

Business/Mission Objectives - Broad expression of business goals. Specified target outcome for business operations.

Capacity Planning - Systematic determination of resource requirements for the projected output, over a specific period. [businessdictionary.com]

Category - The subdivision of a Function into groups of cybersecurity outcomes closely tied to programmatic needs and particular activities.

Critical Infrastructure - Essential services and related assets that underpin American society and serve as the backbone of the nation's economy, security, and health. [DHS]

Criticality Reviews - A determination of the ranking and priority of manufacturing system components, services, processes, and inputs in order to establish operational thresholds and recovery objectives.

Critical Services - The subset of mission essential services required to conduct manufacturing operations. Function or capability that is required to maintain health, safety, the environment and availability for the equipment under control. [62443]

Cyber Risk - Risk of financial loss, operational disruption, or damage, from the failure of the digital technologies employed for informational and/or operational functions introduced to a manufacturing system via electronic means from the unauthorized access, use, disclosure, disruption, modification, or destruction of the manufacturing system.

Cybersecurity - The process of protecting information by preventing, detecting, and responding to attacks. [CSF]

Defense-in-breadth - The application of multiple countermeasures in a layered or stepwise manner to achieve security objectives. The methodology involves layering heterogeneous security technologies in the common attack vectors to ensure that attacks missed by one technology are caught by another. [62443 1-1]

Environmental Support – Any environmental factor for which the organization determines that it needs to continue to provide support in a contingency situation, even if in a degraded state.

This could include factors such as power, air conditioning, humidity control, fire protection, lighting, etc.

For example, while developing the contingency plan, the organization may determine that it is necessary to continue to ensure the appropriate temperature and humidity during a contingency situation so they would plan for the capacity to support that via supplemental/mobile air conditioning units, backup power, etc. and the associated procedures to ensure cutover operations. Such determinations are based on an assessment of risk, system categorization (impact level), and organizational risk tolerance.

Event - Any observable occurrence on a manufacturing system. Events can include cybersecurity changes that may have an impact on manufacturing operations (including mission, capabilities, or reputation). [CSF]

Fail to Known State – Upon a disruption event that causes the system to fail, it fails to a pre-determined state. Failure in a known safe state helps to prevent systems from failing to a state that may cause injury to individuals or destruction to property. Preserving manufacturing system state information facilitates system restart and return to the operational mode of organizations with less disruption of mission/business processes. [NVD.NIST]

Firmware - Software program or set of instructions programmed on the flash ROM of a hardware device. It provides the necessary instructions for how the device communicates with the other computer hardware. [Techterms.com]

Framework - The Cybersecurity Framework developed for defining protection of critical infrastructure. It provides a common language for understanding, managing, and expressing cybersecurity risk both internally and externally. Includes activities to achieve specific cybersecurity outcomes, and references examples of guidance to achieve those outcomes.

Function - Primary unit within the Cybersecurity Framework. Exhibits basic cybersecurity activities at their highest level.

Incident - An occurrence that actually or potentially jeopardizes the confidentiality, integrity, or availability of an information system or the information the system processes, stores, or transmits or that constitutes a violation or imminent threat of violation of security policies, security procedures, or acceptable use policies. [CSF]

Informative References - Specific sections of standards, guidelines, and practices common among critical infrastructure sectors that illustrate a method to achieve the outcomes associated with each Subcategory in the Cybersecurity Framework.

Integrator - A value-added engineering organization that focuses on industrial control and information systems, manufacturing execution systems, and plant automation, that has application knowledge and technical expertise, and provides an integrated solution to an engineering problem. This solution includes final project engineering, documentation, procurement of hardware, development of custom software, installation, testing, and commissioning. [CSIA.com]

Manufacturing Operations - Activities concerning the facility operation, system processes, materials input/output, maintenance, supply and distribution, health, and safety, emergency response, human resources, security, information technology and other contributing measures to the manufacturing enterprise.

Network Access - any access across a network connection in lieu of local access (i.e., user being physically present at the device).

Non-local Connection - A connection to the manufacturing system affording the user access to system resources and system functionality while physically not present.

Overlay - A fully specified set of security controls, control enhancements, and supplemental guidance derived from tailoring a security baseline to fit the user's specific environment and mission. [800-53]

Operational technology - Hardware and software that detects or causes a change through the direct monitoring and/or control of physical devices, processes and events in the enterprise. [Gartner.com]

Programmable Logical Controller - A solid-state control system that has a user-programmable memory for storing instructions for the purpose of implementing specific functions such as I/O control, logic, timing, counting, three mode (PID) control, communication, arithmetic, and data and file processing. [800-82]

Port - The entry or exit point from a computer for connecting communications or peripheral devices. [800-82]

Profile - A representation of the outcomes that a particular system or organization has selected from the Framework Categories and Subcategories. [CSF]

- Target Profile - the desired outcome or 'to be' state of cybersecurity implementation
- Current Profile - the 'as is' state of system cybersecurity

Protocol - A set of rules (i.e., formats and procedures) to implement and control some type of association (e.g., communication) between systems. [800-82]

Remote Access - Access by users (or information systems) communicating external to an information system security perimeter. Network access is any access across a network connection in lieu of local access (i.e., user being physically present at the device). [800-53]

Resilience Requirements - The business-driven availability and reliability characteristics for the manufacturing system that specify recovery tolerances from disruptions and major incidents.

Risk Assessment - The process of identifying risks to agency operations (including mission, functions, image, or reputation), agency assets, or individuals by determining the probability of occurrence, the resulting impact, and additional security controls that would mitigate this impact.

Part of risk management, synonymous with risk analysis. Incorporates threat and vulnerability analyses. [800-82]

Risk Tolerance - The level of risk that the Manufacturer is willing to accept in pursuit of strategic goals and objectives. [800-53]

Router - A computer that is a gateway between two networks at OSI layer 3 and that relays and directs data packets through that inter-network. The most common form of router operates on IP packets. [800-82]

Security Control - The management, operational, and technical controls (i.e., safeguards or countermeasures) prescribed for a system to protect the confidentiality, integrity, and availability of the system, its components, processes, and data. [800-82]

Subcategory - The subdivision of a Category into specific outcomes of technical and/or management activities. Examples of Subcategories include “External information systems are catalogued,” “Data-at-rest is protected,” and “Notifications from detection systems are investigated.” [CSF]

Supporting Services - Providers of external system services to the manufacturer through a variety of consumer-producer relationships including but not limited to: joint ventures; business partnerships; outsourcing arrangements (i.e., through contracts, interagency agreements, lines of business arrangements); licensing agreements; and/or supply chain exchanges. Supporting services include, for example, Telecommunications, engineering services, power, water, software, tech support, and security. [800-53]

Switch - A device that channels incoming data from any of multiple input ports to the specific output port that will take the data toward its intended destination. [Whatis.com]

System Categorization - The characterization of a manufacturing system, its components, and operations, based on an assessment of the potential impact that a loss of availability, integrity, or confidentiality would have on organizational operations, organizational assets, or individuals. [FIPS 199]

Third-Party Relationships - relationships with external entities. External entities may include, for example, service providers, vendors, supply-side partners, demand-side partners, alliances, consortiums, and investors, and may include both contractual and non-contractual parties. [DHS]

Third-party Providers - Service providers, integrators, vendors, telecommunications, and infrastructure support that are external to the organization that operates the manufacturing system.

Thresholds - Values used to establish concrete decision points and operational control limits to trigger management action and response escalation.

Appendix C - References

1. Executive Order 13636, *Improving Critical Infrastructure Cybersecurity* - <http://www.whitehouse.gov/the-press-office/2013/02/12/executive-order-improving-critical-infrastructure-cybersecurity>
2. National Institute of Standards and Technology, Framework for Improving Critical Infrastructure Cybersecurity, version 1.0, February 12, 2014, <http://www.nist.gov/cyberframework/upload/cybersecurity-framework-021214.pdf> [accessed 4/16/15].
3. National Institute of Standards and Technology, Special Publication (SP) 800-82 Revision 2, Guide to Industrial Control Systems (ICS) Security, National Institute of Standards and Technology, Gaithersburg, Maryland, May 2015, 240pp. <http://dx.doi.org/10.6028/NIST.SP.800-82r2>
4. National Institute of Standards and Technology, Special Publication (SP) 800-53 Revision 4, Security and Privacy Controls for Federal Information Systems and Organizations, National Institute of Standards and Technology, Gaithersburg, Maryland, April 2013 (including updates as of January 15, 2014), 460pp. <http://dx.doi.org/10.6028/NIST.SP.800-53r4>
5. ISA/IEC 62443 Series of Standards on Industrial Automation and Control Systems (IACS) Security. <http://isa99.isa.org/ISA99%20Wiki/Home.aspx>
6. Cybersecurity Framework site - <http://www.nist.gov/itl/cyberframework.cfm>
7. National Cybersecurity & Communications Integration Center (NCCIC) - <https://www.dhs.gov/national-cybersecurity-and-communications-integration-center>
8. Industrial Control Systems Cyber Emergency Response Team (ICS-CERT) - <http://ics-cert.us-cert.gov/ics-cert/>